mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





S9025PL / S9025PR **Mini RFID Panel Antenna**





902-928 MHz 5.5 dBi CP MINI RFID PANEL ANTENNA

available to the market that offers no-compromise performance in a small package. At only 5.2" square the antenna offers a gain specification of 5.5 dBic and axial ratio better than 2 dB. In effect the antenna is providing the performance one would expect of a much larger antenna. The antenna is not only mechanically robust but is less likely to be exposed to excessive damage by virtue of its reduced size.

S9025PR and S9025PL

Circular RH or Circular LH

White or Charcoal High Strengh PC

Threaded Stud 2x #10-32

902 - 928 MHz

5.5 dBi

1.5:1

100°

8 dB

10 Watts

50 Ohms

2.0 dB Typical .8 lbs (.37)

5.2" x 5.2" x .71"

-30°C to +70°C

1 lbs. Ball Drop, 24"

40°C to 85°C

MIL-STD-810

MIL-STD-810

IEC 68-2-27 IEC 68-2-30

DC Grounded IP 67

FEATURES <a>RoHs

- Circularly polarized
- · Low VSWR and axial ratio
- Rugged, ultra heavy duty construction
- IP 67 Rated

SPECIFICATIONS Antenna Part Number

3 dB Beamwidth - Azimuth

Frequency Range

Maxium VSWR

Polarization

Axial Ratio

Weight (Kg) Mechanical Size

Radome Mount Style

Salt

Vibration

Humidity

Shock

Front to Back Ratio

Maxium Input Power

Antenna vConnection

Temperature Operational

Storage Temperature Impact Resistance

Lightning Protection

Enclosure Rating

Input Impedence

Gain

- Weather and UV resistant radome
- High performance in a small package
- Wide range of connector and cable options
- · Left hand and right hand CP versions

APPLICATIONS

- Warehouse
- Distribution center
- · Airports and hospitals
- Transit terminals
- Conveyer belt

Type N Female, RP-TNC Female, RP-SMA Female, SMA Female

	345	15		
330	m	Myth	30	
315	+	+	245	
300	L	H/	ΧŽ	×60
285	$\langle \rangle$	/X	X	75
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Xtt	$1\times$	-	
270	Ð		-20	-10 90
	<b>X</b> A	HX -		105
200	$\langle \rangle  $			7 103
240	T		X,	7120
225	approx	MAN		5
210	$\mathcal{L}_{\mu}$	-	150	
195 ₁₈₀ 165				
910 MHz				

Americas: +1.847 839.6925 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: IAS-AsiaSales@lairdtech.com

### ANT-DS-S9025P 0317

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird waran warrantes as to the fitness, merchantability or the use and upulsation of Laird materials or products for any specific or general uses. Laird shall not be liable for incidential or consequential damages of any kind. All Laird products are sold pursuant to the Laird Ferms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or and Filiate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

www.lairdtech.com