



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: SAOM820HIRHSH1



Axial Oval Mount, Bolt Hole Diameter 0.31", PA66HIRHSUV, Black, 500/pkg

Article Number	151-29701
Type	SAOM82
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Positions bundles off cross members and frame rails to prevent abrasion and chafing.• Metal insert bushing accommodates high torque installation.• Made with high impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.
Quantity Per	bag
Product Description	HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.
Short Description	Axial Oval Mount, Bolt Hole Diameter 0.31", PA66HIRHSUV, Black, 500/pkg

Global Part Name

SAOM82-PA66HIRHSUV-BK

Length L (Imperial)

1.40

Length L (Metric)

34.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.0

Width W (Metric)

26.0

Cable Ties

T50 - T250

Height H (Imperial)

1.40

Height H (Metric)

35.0

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.31

Mounting Hole Diameter D (Metric)

8.0 mm

Mounting Hole Diameter D Min (Imperial)

0.31

Mounting Hole Diameter D Max (Imperial)

0.31

Mounting Hole Diameter D Max (Metric)

8.0

Stud Diameter (Metric)

8.0 mm

Stud Diameter (Imperial)	0.3125
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Metric)	10.8

