



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# SC104B

## SMD POWER INDUCTORS





### • Features

1. Open frame construction
2. Excellent Power Density
3. Engineered to Provide High Efficiency

## ELECTRICAL CHARACTERISTICS



Part Number	Inductance (uH) (1)	Test Frequency	DC Resistance (Ω MAX) (2)	Saturation Current <sup>(3)</sup> (A)	Temperature Current <sup>(4)</sup> (A)
SC104B-100	10	2.52MHZ	53m	2.38	3.60
SC104B-120	12	2.52MHZ	61m	2.13	3.20
SC104B-150	15	2.52MHZ	70m	1.87	2.90
SC104B-180	18	2.52MHZ	90m	1.73	2.70
SC104B-220	22	2.52MHZ	100m	1.60	2.30
SC104B-270	27	2.52MHZ	124m	1.44	2.10
SC104B-330	33	2.52MHZ	140m	1.26	1.90
SC104B-390	39	2.52MHZ	151m	1.20	1.80
SC104B-470	47	2.52MHZ	195m	1.10	1.60
SC104B-560	56	2.52MHZ	220m	1.01	1.55
SC104B-680	68	2.52MHZ	260m	0.91	1.50
SC104B-820	82	2.52MHZ	310m	0.85	1.30
SC104B-101	100	1KHZ	344m	0.74	1.20
SC104B-121	120	1KHZ	396m	0.69	1.08
SC104B-151	150	1KHZ	554m	0.61	0.98
SC104B-181	180	1KHZ	621m	0.56	0.88
SC104B-221	220	1KHZ	721m	0.53	0.80
SC104B-271	270	1KHZ	949m	0.45	0.74
SC104B-331	330	1KHZ	1.100	0.42	0.64
SC104B-391	390	1KHZ	1.245	0.38	0.54
SC104B-471	470	1KHZ	1.526	0.35	0.50
SC104B-561	560	1KHZ	1.904	0.32	0.48



- (1). Inductance tolerance  $\pm 20\%$  tested at 0.25V, 0ADC and 25°C.
- (2). DCR measured at 25°C.
- (3). The DC current at which the inductance decreases by 10% from its initial value.
- (4). The DC current that results in a 40°C temperature rise from 25°C ambient.

[Click here for QUANTITY PER REEL & PACKING INFORMATION](#)

**Custom versions available upon request.**