imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SC1212

SMD POWER INDUCTORS



• Features

- 1. Magnetically shielded construction
- 2 Low DCR
- 3 Small size
- 4 Excellent Power Density
- 5 Engineered to Provide High Efficiency



ELECTRICAL CHARACTERISTICS

Part Number	Inductance (uH)	Test Frequency	DC Resistance (Ω MAX)	Saturation Current	Current	SC1212 Inductance decrease by current
SC1212-561	(1) 560	1KHZ	(2) 8.0	(mA) 41	(mA) 190	
SC1212-501 SC1212-681	680	1KHZ	9.0	37	175	
SC1212-001 SC1212-102	1000	1KHZ	12.0	30	145	3 100
SC1212-162 SC1212-152	1500	1KHZ	15.0	25	130	Inductance (μ H)
SC1212-222	2200	1KHZ	23.5	20	110	
						1 0.1 1 10 100 1000
						DC current (mA)
						SC1212 Temperature rise by current
						80
						70
						222 40 40 561 102 561 102 561 102 561 102 561 102 561 102 561 102 561 102 561 561 561 561 561 561 561 561
						0 30 60 90 120 150 180 210 240 270 300 DC current (mA)
						· · · · · · · · · · · · · · · · · · ·

(1). Inductance tolerance±30% tested at 1.0V, 0ADC and 25°C

(2). DCR measured at 25°C.

(3). The DC current at which the inductance decreases by 30% from its initial value.

(4). The DC current that results in a 40°C temperature rise from 25° C ambient.

Click here for **QUANTITY PER REEL & PACKING INFORMATION**

Custom versions available upon request.

©2011 Signal Transformer –Specification subject to change without notice. 07.11

