imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SC3316FH

SMD POWER INDUCTORS



• Features

- 1. Open frame construction
- 2 Excellent Power Density
- 3 Engineered to Provide High Efficiency



ELECTRICAL CHARACTERISTICS

Part Number	Inductanc e (uH) (1)	Test Frequency	DC Resistance (Ω MAX) (2)	Saturation ₍₃₎ Current (A)	Temperature Current (A)	BC3316FH I nduct ance decrease by current
SC3316FH-R27	0.27	100KHZ	2.0m	20.0	17.8	
SC3316FH-R56	0.56	100KHZ	5.0m	13.0	11.5	
SC3316FH-1R0	1.0	100KHZ	6.0m	11.0	10.5	
SC3316FH-1R5	1.5	100KHZ	8.0m	9.0	8.5	
SC3316FH-2R2	2.2	100KHZ	11.0m	7.8	7.4	
SC3316FH-2R7	2.7	100KHZ	12.0m	7.0	6.4	0.01
SC3316FH-3R3	3.3	100KHZ	14.0m	6.4	6.4	DC current (mA)
SC3316FH-4R7	4.7	100KHZ	18.0m	5.4	5.4	
SC3316FH-6R8	6.8	100KHZ	22.0m	5.0	4.5	BC3316FH Temperature rise by current
						b c c c c c c c c

(1). Inductance tolerance for 0.27uH~3.3uH: ±30%, for 4.7uH~6.8uH: ±20%. Tested at 0.25V, 0ADC and 25°C.

(2). DCR measured at 25°C.

(3). The DC current at which the inductance decreases by 10% from its initial value.

(4). The DC current that results in a 40°C temperature rise from 25° C ambient.

Click here for QUANTITY PER REEL & PACKING INFORMATION

Custom versions available upon request.

 \tilde{O} 2011 Signal Transformer –Specification subject to change without notice. 07.11

