

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









# SC5012 SC5012Q

# High Efficiency 4-Ch, 150mA/Ch LED Driver with I<sup>2</sup>C Interface and Phase-Shifted PWM Dimming

## POWER MANAGEMENT

#### **Features**

- Input Voltage 4.5V to 45V
- Output Voltage Up to 65V
- Step-up (Boost) Controller
  - Ultra-Fast Transient Response
  - Programmable Switching Frequency
  - External Sync Frequency for Boost Controller
- Linear Current Sinks
  - 4 Strings, up to 150mA/String
  - Current Matching ±1%
  - Current Accuracy ±2%
- PWM Dimming
  - 5000:1 dimming ratio
  - String-by-String Phase Shifting
  - Dimming Frequency 100Hz-30kHz
  - User Selectable 9 or 10 Bits Dimming Resolution
  - Optional Synchronization to VSYNC Signal
- External Frequency Synchronization, FSYNC
- 8-bit Analog Dimming
- I<sup>2</sup>C Interface
  - Fault Status Open/Short LED, OTP
  - Device Control: SYNC Freq, PLL Setting
- Protection Features
  - Open/Shorted LED(s) and adjustable OVP
  - Over-Temperature
- 4mm X 4mm 24 Ld QFN Package
- AEC-Q100 (Grade2) Qualified Version Available

### **Applications**

- Medium-sized LCD Panel
- Automotive Car Navigation/Information Display
- LCD Monitors

# Description

The SC5012/Q is a 4-channel high-precision, high-efficiency step-up (Boost) HB LED driver designed for backlight applications. It features wide input voltage range (4.5V to 45V), flexible output configuration, wide analog and PWM dimming range, phase shifting, optional fading, external boost controller frequency synchronization (FSYNC), I<sup>2</sup>C interface, and numerous protection features.

The boost controller, with programmable switching frequency from 200kHz to 2.2MHz, can maximize efficiency by dynamically minimizing the output voltage while maintaining LED string current accuracy. It provides excellent line and load response with no external compensation components. Each linear current sink is matched within ±1% for superb lighting uniformity, and the accuracy of each string current is ±2%. An external resistor adjusts the current from 40-150mA per string. It also features PWM dimming resolution of 9 or 10 bits (user selectable) over a dimming frequency from 100Hz to 20kHz, synchronized to the SYNC signal or the boost oscillator. String-by-string phase shifting reduces the demand on the input/output capacitance, decreases EMI, and improves dimming linearity.

SC5012/Q is available in 4mm X 4mm 24 Ld QFN package.

The SC5012Q is an AEC-Q100 (Grade2) qualified version.

# **Typical Application Circuit**

