

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## MALLORY Mallory Sonalert Products, Inc. Part #: **SC628J** Revision: **Sales Outline Drawing** Specifications: Sound Level Category Medium Mode of Operation Slow Pulse @ 0.5 - 2.5 PPS Voltage Rating 6 to 28 VDC 2900 ± 500 Hz Frequency Loudness @ 2 FT 78 to 89 dB(A) Typ. **Current Draw** 6-26mA Duty Cycle (%) 50 6/6 Nylon, Color: Black Housing Material -40° to +85° C Storage Temperature Operating Temperature -30° to +65° C Panel Mounting Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. Used to attach part to panel. The max recommended torque is 10 in-lbs. Knurled Nut 1.6 oz (45g) Weight (Typical) NEMA 3R,4X, & 12 Approved with use of ACC03. **Options** Please contact factory. cUL Recognized **Dimensions:** Inches (mm) PART DIMENSIONS BEFORE CODE DATE: 0810 5 PART DIMENSIONS AFTER CODE DATE: 0811 1 1.31±.09 [33.17±2.29] 1.19±.09 [30.24±2.29] SONALERT® S□NALER™ 1.240 [31.50] 1.210 [30.73] 1.240 [31.50 1.210 [30.73 10000 (999) 1.687±.005 [42.85±.13] 1.13 [28.70] - 1.687±.005 [42.85±.13] -1.13 [28.70] 1.10 [27.94] 1 1/8-24 UNS 2A THD. 1 1/8-24 UNS 2A THD. MOLDED BLACK NYLON HOUSING KNURLED NUT KNURLED NUT -TERMINALS PARALLEL TO LOCKING FLATS WITHIN ±15° (SEE NOTE A) TERMINALS PARALLEL — TO LOCKING FLATS WITHIN ±15\* (SEE NOTE A) 1.313±.005 [ [33.34±.13] $\in$ .250±.005 [6.35±.13] 1.313±.005 [33.34±.13] .250±.005 [6.35±.13] $\Leftrightarrow$ .312±.005 [7.92±.13] -.312±.005 [7.92±.13] 44±.01 [11.17±.25] .375±.005 [9.53±.13] 44±.01 [11.17±.25] .375±.005 [9.52±.13] .031±.005 [.79±.13]--.031±.005 [.79±.13] .031±.005 [.79±.13]--.031±.005 [.79±.13] .47±.01 [11.94±.25] 1.37±.06 [34.80±1.52] .47±.01 [11.94±.25]-1.28±.01 [32.6±.25] -NOTE B: MOUNTING- REMOVE BLACK PLASTIC NUT AND INSERT THREADED FRONT THROUGH 1.25' HOLE PUNCHED IN PANEL, IF DRIENTATION IS NEEDED, NOTE LOCKING FLATS ON DRAWING SCREW NUT BACK ON. DO NOT OVERTIGHTEN. NOTE A: TERMINALS-032 BRASS TIN PLATED, TAPPED FOR #6-32 SCREW. TWO #6-32 NICKEL PLATED BRASS SCREWS INCLUBED. WILL ACCEPT 1/4' QUICK CONNECT. NOTE A: TERMINALS-032 BRASS TIN PLATED, TAPPED FOR #6-32 SCREW. TWO #6-32 NICKEL PLATED BRASS SCREWS INCLUBED. WILL ACCEPT 1/4\* QUICK CONNECT. NOTE B: MOUNTING- REMOVE BLACK PLASTIC NUT AND INSERT THREADED FRONT THROUGH 1.25' HOLE PUNCHED IN PANEL, IF DRIENTATION IS NEEDED, NOTE LOCKING FLATS ON DRAVING, SCREW NUT BACK ON. DO NOT OVERTIGHTEN.