



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SC63CB

SMD POWER INDUCTORS





• Features

1. Magnetically shielded construction
2. LOW Profile (3.0mm max. height x 6.3mm square)
3. Low DC resistance makes this product very suitable for large current applications



CHARACTERISTICS

| Part Number | Inductance (uH) (1) | Test Frequency | DC Resistance (Ω MAX) (2) | Saturation Current ⁽³⁾ (A) | Temperature Current ⁽⁴⁾ (A) |
|-------------|------------------------|----------------|------------------------------|--|---|
| SC63CB-2R0 | 2.0 | 100KHZ | 20m | 3.00 | 4.00 |
| SC63CB-2R7 | 2.7 | 100KHZ | 23m | 2.69 | 3.60 |
| SC63CB-3R3 | 3.3 | 100KHZ | 27m | 2.57 | 3.24 |
| SC63CB-4R7 | 4.7 | 100KHZ | 33m | 2.08 | 3.10 |
| SC63CB-6R2 | 6.2 | 100KHZ | 39m | 1.84 | 2.85 |
| SC63CB-8R2 | 8.2 | 100KHZ | 45m | 1.54 | 2.70 |
| SC63CB-100 | 10 | 100KHZ | 50m | 1.49 | 2.56 |
| SC63CB-120 | 12 | 100KHZ | 65m | 1.28 | 2.43 |
| SC63CB-150 | 15 | 100KHZ | 80m | 1.10 | 2.18 |
| SC63CB-180 | 18 | 100KHZ | 85m | 1.05 | 2.07 |
| SC63CB-220 | 22 | 100KHZ | 110m | 0.97 | 1.75 |
| SC63CB-270 | 27 | 100KHZ | 146m | 0.82 | 1.67 |
| SC63CB-330 | 33 | 100KHZ | 169m | 0.76 | 1.50 |
| SC63CB-390 | 39 | 100KHZ | 198m | 0.70 | 1.42 |
| SC63CB-470 | 47 | 100KHZ | 218m | 0.68 | 1.34 |
| SC63CB-560 | 56 | 100KHZ | 268m | 0.60 | 1.20 |
| SC63CB-680 | 68 | 100KHZ | 333m | 0.56 | 1.02 |
| SC63CB-820 | 82 | 100KHZ | 436m | 0.47 | 0.91 |
| SC63CB-101 | 100 | 100KHZ | 496m | 0.45 | 0.86 |
| SC63CB-151 | 150 | 100KHZ | 691m | 0.37 | 0.77 |



- (1). Inductance tolerance for 2.0uH~8.2uH: $\pm 30\%$, for 10uH~150uH: $\pm 20\%$. Tested at 0.25V, 0ADC and 25°C
- (2). DCR measured at 25°C.
- (3). The DC current at which the inductance decreases by 30% from its initial value.
- (4). The DC current that results in a 40°C temperature rise from 25°C ambient.

[Click here for QUANTITY PER REEL & PACKING INFORMATION](#)

Custom versions available upon request.