imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Elnk Segmented

Electronic Paper Displays

Sunlight Readable Wide Viewing Angle Low Power Consumption

E Ink Segmented displays are ultra-low power, thin, and rugged. E Ink's unique reflective display technology is sunlight readable and can display an image with no power.

This enables engineers and designers to add displays to products where power and space limitations have made it impossible to do so before.

Divided into discrete segments, these products can be controlled individually to convey information using letters, numbers and icons. Creative layouts enable overlapping images and unique fonts. The result is a black and white display with the readability of paper that is less than 650 microns thick.





Specifications

Parameter	14 Bar Capacity Gauge
Model #	SCD722003
Segments	14
Overall Dimmensions	8.5 x 37.50 mm
Active Area Dimmensions	3.00 x 21.50 mm
Thickness	580 um
Backplane Substrate	PET
Connection Pins	15
Tail Pitch	0.5 mm
Tail Connector	0.3 mm
Connection Type	Tyco 5-1734592-0
Drive Voltage	15v or 5v
Power Draw Image Static	0
Power Draw Image Static	0.5 micro-amps per cm2
Storage	-25c to 70c
Operating Range	-10c to 60c

Applications

Markets

Watches	Medical
Smartcards & Smart Locks	Industrial
Glucose Meters	Consumer
Usb Drives	Finance
Battery Indicators	Mobile
Fitness Devices	Retail