

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







MALLORY Mallory Sonalert Products, Inc. Part #: SCE028XD3QP1B Revision: **Sales Outline Drawing Specifications:** Sound Level Category Extra Loud Mode of Operation Quick Pulse @ 60 PPS Voltage Rating 16 to 28 VDC 2900 ± 500 Hz Frequency Loudness @ 2 FT 95 to 105 dB(A) Typ. **Current Draw** 40mA MAX Housing Material 6/6 Nylon, Color: Black Storage Temperature -40° to +85° C Operating Temperature -40° to +85° C Panel Mounting Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. Knurled Nut Used to attach part to panel. The max recommended torque is 10 in-lbs. Weight (Typical) 1.6 oz (45g) NEMA 3R,4X, & 12 Approved with use of ACC03. cUL Recognition cUL Recognized **Options** Please contact factory.

1 1/8-24 UNS 2A THD.

1.313±005 [33.34±13]

1.47±01 [11.94±25]

1.41±1 [35.85±254]

1.687±005 [42.85±13]

Sourtions

Sourtions

FlugGable Screw

TERMINAL BLock

cUL Recognized

Dimensions: Inches (mm)

ROHS Compliant