

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








## SCMD4D10

#### **SMD POWER INDUCTORS**





- Features
- 1. Open frame construction
- 2 Excellent Power Density
- 3 Engineered to Provide High Efficiency

#### **ELECTRICAL CHARACTERISTICS**



	Inductance	Test	DC Resistance	Saturation <sub>(3)</sub>	Temperature
Part Number	(uH)	Frequency	$(\Omega MAX)$	Current (3)	Current
	(1)		(2)	(A)	(A)
SCMD4D10-3R3	3.3	100KHZ	0.20	1.37	1.16
SCMD4D10-4R7	4.7	100KHZ	0.28	1.12	0.96
SCMD4D10-6R8	6.8	100KHZ	0.38	1.10	0.80
SCMD4D10-100	10	100KHZ	0.60	0.82	0.64
SCMD4D10-150	15	100KHZ	0.90	0.67	0.50
SCMD4D10-220	22	100KHZ	1.30	0.55	0.42
SCMD4D10-330	33	100KHZ	1.75	0.45	0.36
SCMD4D10-470	47	100KHZ	2.80	0.40	0.30





- (1). Inductance tolerance  $\pm 20\%$  tested at 0.25V, 0ADC and 25°C.
- (2). DCR measured at 25°C.
- (3). The DC current at which the inductance decreases by 10% from its initial value.
- (4). The DC current that results in a 40°C temperature rise from 25°C ambient.

### Click here for QUANTITY PER REEL & PACKING INFORMATION



©2011 Signal Transformer - Specification subject to change without notice. 07.11

