



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832



Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







PACKAGE DIMENSIONS INCH [mm]



CHIP DIMENSIONS INCH [mm]



TO-46 PACKAGE

FEATURES

- Low noise
- Low dark current
- High response

DESCRIPTION

The SD 012-11-41-211 is a high sensitivity low noise characteristics InGaAs photodiode packaged in a leaded hermetic TO-46 metal package.

APPLICATIONS


- Communication
- Industrial
- Medical

ABSOLUTE MAXIMUM RATING (TA)= 23°C UNLESS OTHERWISE NOTED

SYMBOL	PARAMETER	MIN	MAX	UNITS
V _{BR}	Reverse Voltage		75	V
T _{STG}	Storage Temperature	-55	+100	°C
T _O	Operating Temperature	-40	+85	°C
T _S	Soldering Temperature*		+260	°C

* 1/16 inch from case for 3 seconds max.

SPECTRAL RESPONSE



ELECTRO-OPTICAL CHARACTERISTICS RATING (TA)= 23°C UNLESS OTHERWISE NOTED

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I _D	Dark Current	V _R = 5V		1	5.0	nA
R _{SH}	Shunt Resistance	V _R = 10 mV	50	150		MΩ
C _J	Junction Capacitance	V _R = 5V, f = 1 MHz		6	9	pF
λ range	Spectral Application Range	Spot Scan	800		1700	nm
R	Responsivity	λ = 1310nm, V _R = 5V	0.83	0.92		A/W
V _{BR}	Breakdown Voltage	I = 1 μA		18		V
NEP	Noise Equivalent Power	V _R = 5V @ λ = 1310nm		1.79X10 ⁻¹⁴		W/√Hz
t _r	Response Time**	RL = 50 Ω, V _R = 5V			1.15	nS

**Response time of 10% to 90% is specified at 1310nm wavelength light.

Information in this technical datasheet is believed to be correct and reliable. However, no responsibility is assumed for possible inaccuracies or omission. Specifications are subject to change without notice.