



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





DESCRIPTION

The SD197-121-041 is a high sensitivity, low capacitance and noise, 5mm diameter active area InGaAs photodiode, sensitive to wavelengths in visible extended (450-1700nm) spectral range and used for imaging and sensing applications. The photodetector is assembled in a TO-5 package.

FEATURES

- Low Noise
- Low Dark Current and Capacitance
- High Sensitivity
- Detection in LWIR

RELIABILITY

This API high-reliability detector is in principle able to meet military test requirements (Mil-STD-750, Mil-STD-883) after proper screening and group test.

Contact API for recommendations on specific test conditions and procedures.

APPLICATIONS

- Industrial Sensing
- Security and Defense
- Communication
- Medical

ABSOLUTE MAXIMUM RATINGS

SYMBOL	MIN	MAX	UNITS
Operating Temperature	0	+85	°C
Storage Temperature	-25	+85	°C
Soldering Temperature	-	+240	°C
Wavelength Range	450	1700	nm
Reverse Voltage	-	20	V

T_a = 23°C
non condensing
see recommended reflow profile

OPTO-ELECTRICAL PARAMETERS

$T_a = 23^\circ\text{C}$ unless noted otherwise

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Breakdown Voltage	$I_{\text{bias}} = 100 \mu\text{A}$	10	-	-	V
Responsivity	$\lambda = 660 \text{ nm}$	-	0.35	-	A/W
Responsivity	$\lambda = 1200 \text{ nm}$	-	0.90	-	A/W
Shunt Resistance	$V_{\text{bias}} = 10 \text{ mV}$	-	30	-	$\text{M}\Omega$
Dark Current	$V_{\text{bias}} = 5\text{V}$	-	-	10	nA
Capacitance	$V_{\text{bias}} = 0\text{V}; f = 1 \text{ MHz}$	-	-	100	pF
Rise Time (50 Ω load)	$V_{\text{bias}} = 24\text{V}; \lambda = 826 \text{ nm}$	-	5	-	ns
Noise Equivalent Power	$\lambda = 900 \text{ nm}$	-	10	-	$10^{-14} \text{ W/Hz}^{0.5}$

TYPICAL PERFORMANCE

SPECTRAL RESPONSE

