



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



D-USB Connectors



Specification

> <u>Standard</u> (SDB) D-SUB	> <u>High Density</u> (HDB) High Density D-SUB
---	--

Number of Contacts

09, 15, 25, 26...78 Contacts
Ex. 09 Pin = **(09)**

Connector Body (Style)

> <u>For Receptacle</u> (P) Front Fastened	> <u>For Overmolded with Cable</u> (A) With Strain Relief > <u>For Field installable</u> (B) Without Strain Relief
--	---

Connector (Housing) Gender

(M) Male Connector	(F) Female Connector
---------------------------	-----------------------------

Contact Gender

(M) Male (Plug)	(F) Female (Jack)
------------------------	--------------------------

Assemble Style

> <u>For Receptacle</u> (S) Solder Type (P) PCB Type (90° / 180°)	> <u>For Overmolded with Cable</u> (M) Overmolded with Cable > <u>For Field Installable</u> (A) Field Installable (Solder) (C) Field Installable (Crimped)
---	---

Mating Style

(S) Screw Thread	(Q) Automated Latch
-------------------------	----------------------------

Backshell

> <u>For Receptacle</u> (With Board Lock) (A) Straight (B) Right Angle (Without Board Lock) (L) Straight (R) Right Angle	> <u>For Overmolded with Cable</u> (Without Board Lock) (L) Straight > <u>For Field Installable</u> (Without Board Lock) (L) Straight
--	--

Waterproof Rating

(7) IP 67
(8) IP 68

More Information

> <u>For Receptacle</u> (001), (002)..... Without Cable : Different Versions	> <u>For Overmolded with Cable</u> (□) + (■) : Cable Type + Cable Length EX. (A01) = UL2464 Cable + 1M <u>(□) : Cable Type</u> <u>(■) : Cable Length</u> (A) UL2464 Cable From 1M to 99M EX. (01) = 1M
--	---