



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Light Meter/Datalogger

 **Records data on an SD card in Excel[®] format**
For easy transfer to a PC for analysis

Features:

- Wide range to 10,000Fc or 100kLux
- Cosine and color-corrected measurements
- Utilizes precision silicon photo diode and spectral response filter
- Datalogger date/time stamps and stores readings on an SD card in Excel[®] format for easy transfer to a PC
- Offset adjustment used for zero function to make relative measurements
- Adjustable data sampling rate: 1 to 3600 seconds
- Stores 99 readings manually and 20M readings via 2G SD card
- Type K/J Thermocouple input for high temperature measurements
- Large backlit LCD display
- Record/Recall MIN, MAX readings
- Data Hold plus Auto power off with disable function
- Complete with 6 x AA batteries, SD card, hard carrying case and light sensor with 45" (1.1m) cable and protective cover



Measures a wide range of light conditions

Specifications	Range	Resolution	Basic Accuracy
Fc Range	200, 2000, 10kFc	0.1Fc	±4%rdg
Lux Range	2000, 20k, 100kLux	1Lux	±4%rdg
Type K Temperature	-148 to 2372°F (-100 to 1300°C)	0.1°	±(0.4% + 1.8°F/1°C)
Type J Temperature	-148 to 2192°F (-100 to 1200°C)	0.1°	±(0.4% + 1.8°F/1°C)
Memory	20M data records using 2G SD card		
Dimensions	7.2 x 2.9 x 1.9" (182 x 73 x 47.5mm)		
Weight	16.2oz (475g)		

Ordering Information:

- SDL400Light Meter/Datalogger
 SDL400-NISTSDL400 w/Certificate of Calibration Traceable to NIST standards
 872502Type J Bead Wire Probe (-328 to 392°F/-200 to 200°C)
 TP870Type K Bead Wire Probe (-40 to 482°F/-40 to 250°C)
 TP200Type K Clamp Probe (-4 to 200°F/-20 to 93°F)
 TP400Type K Clamp Probe (-4 to 450°F/-20 to 232°C)
 153117117V AC Adaptor
 UA100-240100-240V AC Adaptor with 4 plugs (US, EU, UK, AU)

