



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SDL900 AC/DC Magnetic Field Meter/Datalogger



Extech's SDL900 measures and datalogs both AC and DC Magnetic Field in Gauss and mT (milli Tesla) with a uniaxial Hall effect sensor and built-in ATC. Internal memory stores up to 99 readings, while SD memory card (included) allows continuous datalogging and readings can easily be exported to an Excel[®] format for further analysis.

Applications:

- Electric transmission equipment
- Power line
- Microwave oven
- Air conditioner
- Refrigerator
- Computer monitor
- Video/audio device
- Particle accelerators
- MRI
- Industrial & research labs
- Transportation Systems
- Elevators
- Battery Power
- Wind Power



Features

- Utilizes Hall effect sensor with ATC (Automatic Temperature Compensation)
- Adjustable data sampling rate: 1 to 3600 seconds
- Memory stores 99 readings manually
- Datalogging feature records readings with date and time stamp on an SD card (included) in Excel[®] format
- N pole/S pole indicator
- Zero button for DC measurement
- Data Hold and Min/Max
- Auto power off with disable
- Complete with uniaxial magnetic probe sensor with protective cover, SD memory card, Universal AC Adaptor with multi-plugs (US, EU, UK, AUS), 6 AA batteries, and hard carrying case

Specifications	Range	Max Resolution	Basic Accuracy
DC milli Tesla	300.00mT	0.01mT	±(5% + 10d)
	3000.0mT	0.1mT	±(5% + 10d)
DC Gauss	3000.0G	0.1G	±(5% + 10d)
	30,000G	1G	±(5% + 10d)
AC milli Tesla	150.00mT	0.01mT	±(5% + 20d)
	1500.0mT	0.1mT	±(5% + 20d)
AC Gauss	1500.0G	0.1G	±(5% + 20d)
	15,000G	1G	±(5% + 20d)
Number of Axis	Uniaxial		
AC Bandwidth	50Hz/60Hz		
Sampling Rate	1 to 3600 seconds		
Datalogging	Datalog readings on SD card (included)		
Dimensions/ Weight	7.1x2.9x1.9" (182x73x48mm)/ 10.7oz (303g)		

Ordering

SDL900 AC/DC Magnetic Field Meter/Datalogger



UPC Code: 793950439012