



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Product Summary (Per Leg)

| $V_{RRM}$ (V) | $I_O$ (A) | $V_F$ Max (V)<br>@ +25°C | $I_R$ Max (μA)<br>@ +25°C |
|---------------|-----------|--------------------------|---------------------------|
| 100           | 10        | 0.67                     | 100                       |

## Description and Applications

The Trench Schottky provides very low  $V_F$  and extremely excellent reverse leakage stability at high temperatures. It is ideal for use as a rectifier, freewheel diode or blocking diode in:

- DC-DC Converters
- AC-DC Adaptors

## Features

- Low Forward Voltage Drop
- Low Power Loss
- Excellent High Temperature Stability
- Soft, Fast Switching Capability
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

## Mechanical Data


- Case: TO220AB (Generic), ITO220AB (Type HE)
- Case Material: Molded Plastic, UL Flammability Classification Rating 94V-0
- Terminals: Matte Tin Finish Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 @3
- Weight: TO220AB (Generic) - 1.85 grams (Approximate)  
ITO220AB (Type HE) - 1.69 grams (Approximate)



TO220AB (Generic)  
Top View




TO220AB (Generic)  
Bottom View



ITO220AB (Type HE)  
Top View



ITO220AB (Type HE)  
Bottom View



Package Pin Out  
Configuration


## Ordering Information (Note 4)

| Part Number   | Case               | Packaging      |
|---------------|--------------------|----------------|
| SDT20A100CT   | TO220AB (Generic)  | 50 Pieces/Tube |
| SDT20A100CTFP | ITO220AB (Type HE) | 50 Pieces/Tube |

- Notes:
1. EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant. All applicable RoHS exemptions applied.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
  4. For packaging details, go to our website at <https://www.diodes.com/design/support/packaging/diodes-packaging/>.


## Marking Information

TO220AB (Generic)



 = Manufacturer's Marking  
 SDT20A100CT = Product Type Marking Code  
 AB = Foundry and Assembly Code  
 YYWW = Date Code Marking  
 YY = Last Two Digits of Year (ex: 17 = 2017)  
 WW = Week (01 to 53)

ITO220AB (Type HE)



 = Manufacturer's Marking  
 SDT20A100CTFP = Product Type Marking Code  
 AB = Foundry and Assembly Code  
 YYWW = Date Code Marking  
 YY = Last Two Digits of Year (ex: 17 = 2017)  
 WW = Week (01 to 53)

## Maximum Ratings (Per Leg) (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

| Characteristic                                                                                      | Symbol           | Value    | Unit |
|-----------------------------------------------------------------------------------------------------|------------------|----------|------|
| Peak Repetitive Reverse Voltage                                                                     | V <sub>RRM</sub> | 100      | V    |
| Working Peak Reverse Voltage                                                                        | V <sub>RWM</sub> |          |      |
| DC Blocking Voltage                                                                                 | V <sub>RM</sub>  |          |      |
| Average Rectified Output Current per Device (Per Leg)<br>(Total)                                    | I <sub>O</sub>   | 10<br>20 | A    |
| Non-Repetitive Peak Forward Surge Current 8.3ms<br>Single Half Sine-Wave Superimposed on Rated Load | I <sub>FSM</sub> | 200      | A    |

## Thermal Characteristics (Per Leg)






| Characteristic                          | Symbol                            | Value       | Unit |
|-----------------------------------------|-----------------------------------|-------------|------|
| Typical Thermal Resistance (Note 5)     |                                   |             |      |
| Package = TO220AB (Generic)             | R <sub>θJC</sub>                  | 2           | °C/W |
| Package = ITO220AB (Type HE)            |                                   | 4           |      |
| Operating and Storage Temperature Range | T <sub>J</sub> , T <sub>STG</sub> | -55 to +150 | °C   |

## Electrical Characteristics (Per Leg) (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Characteristic           | Symbol         | Min | Typ          | Max          | Unit     | Test Condition                                                                                  |
|--------------------------|----------------|-----|--------------|--------------|----------|-------------------------------------------------------------------------------------------------|
| Forward Voltage Drop     | V <sub>F</sub> | —   | 0.61<br>0.57 | 0.67<br>0.63 | V        | I <sub>F</sub> = 10A, T <sub>J</sub> = +25°C<br>I <sub>F</sub> = 10A, T <sub>J</sub> = +125°C   |
| Leakage Current (Note 6) | I <sub>R</sub> | —   | 8<br>5       | 100<br>20    | μA<br>mA | V <sub>R</sub> = 100V, T <sub>J</sub> = +25°C<br>V <sub>R</sub> = 100V, T <sub>J</sub> = +125°C |

Notes: 5. With 50mm\*50mm\*23mm Al heatsink.  
6. Short duration pulse test used to minimize self-heating effect.






## Package Outline Dimensions


Please see <http://www.diodes.com/package-outlines.html> for the latest version.

### (1) Package Type: TO220AB (Generic)



| TO220AB (Generic)    |       |       |       |
|----------------------|-------|-------|-------|
| Dim                  | Min   | Max   | Typ   |
| A                    | 3.56  | 4.82  | -     |
| A1                   | 0.51  | 1.39  | -     |
| A2                   | 2.04  | 2.92  | -     |
| b                    | 0.39  | 1.01  | 0.81  |
| b2                   | 1.15  | 1.77  | 1.24  |
| c                    | 0.356 | 0.61  | -     |
| D                    | 14.22 | 16.51 | -     |
| D1                   | 8.39  | 9.01  | -     |
| D2                   | 11.45 | 12.87 | -     |
| e                    | -     | -     | 2.54  |
| e1                   | -     | -     | 5.08  |
| E                    | 9.66  | 10.66 | -     |
| E1                   | 6.86  | 8.89  | -     |
| H1                   | 5.85  | 6.85  | -     |
| L                    | 12.70 | 14.73 | -     |
| L1                   | -     | 4.42  | -     |
| L2                   | 15.80 | 17.51 | 16.00 |
| P                    | 3.54  | 4.08  | -     |
| Q                    | 2.54  | 3.42  | -     |
| All Dimensions in mm |       |       |       |

### (2) Package Type: ITO220AB (Type HE)



| ITO220AB (Type HE)   |          |       |       |
|----------------------|----------|-------|-------|
| Dim                  | Min      | Max   | Typ   |
| A                    | 4.50     | 4.90  | 4.70  |
| A1                   | 2.34     | 2.74  | 2.54  |
| A2                   | 2.56     | 2.96  | 2.76  |
| A4                   | 0.30     | 0.60  | 0.45  |
| b                    | 0.70     | 0.95  | 0.80  |
| b1                   | 1.18     | 1.43  | 1.28  |
| b1a                  | 1.25     | 1.55  | 1.35  |
| c                    | 0.45     | 0.60  | 0.50  |
| D                    | 15.57    | 16.17 | 15.87 |
| e                    | 2.54 BSC |       |       |
| E                    | 9.96     | 10.36 | 10.16 |
| H1                   | 6.70 REF |       |       |
| L                    | 12.68    | 13.28 | 12.98 |
| L1                   | 3.03     | 3.43  | 3.23  |
| Q                    | 3.15     | 3.45  | 3.30  |
| ØP                   | 3.03     | 3.38  | 3.18  |
| ØP3                  | 3.15     | 3.65  | 3.45  |
| All Dimensions in mm |          |       |       |

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2017, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)