



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**DATA SHEET**

**SE5012T: 5 GHz Front End Module with Power Detector**

**Applications**

- 5 GHz WLAN (IEEE802.11a/g/n)
- Access Points, PCMCIA, PC cards

**Features**

- 5GHz Front End Module with PA, LNA and T/R Switch
- Integrated power amplifier enable pin (V<sub>EN</sub>)
- Buffered, temperature compensated power detector
- High and Low-Linearity mode
- 5V or Direct-to-Battery operation
- 3% EVM, 64 QAM, 54 Mbps: 17dBm @3.3V or 21dBm @5V
- 30 dB Typical Gain
- Lead Free and RoHS compliant, halogen free package
- 16 pin 3 mm x 3 mm x 0.6 mm QFN, MSL1

**Product Description**

The SE5012T is a 5GHz front end module offering high linear power for wireless LAN applications. It incorporates a power detector for control of the output power.

The SE5012T offers a high level of integration for a simplified design, providing quicker time to market and higher application board production yield. The device integrates the input match, inter-stage match, a temperature compensated, load insensitive power detector with 20dB of dynamic range, a 3.8GHz notch filter, a T/R switch and LNA.


For wireless LAN applications, the device meets the requirements of IEEE802.11a and delivers approximately 17dBm of linear output power at VCC=3.3V or 21dBm at VCC=5.0V. It also features a low linearity mode control to reduce current consumption at low power modes.

The SE5012T integrates the reference voltage generator, allowing for a true 1.8V CMOS compatible digital EN (enable) function to turn the power amplifier on and off.

**Ordering Information**

Part Number	Package	Remark
SE5012T	16 Pin QFN	Samples
SE5012T-R	16 Pin QFN	Tape and Reel
SE5012T-EK1	Evaluation Kit	Standard

**Functional Block Diagram**



**Figure 1: Functional Block Diagram**

**DATA SHEET**  
**SE5012T: 5 GHz Front End Module with Power Detector**

**Pin Out Diagram**




Figure 2: SE5012T Pin-Out Diagram

**Pin Out Description**

Pin No.	Name	Description
1	EN	PA Enable
2	GND	Ground
3	TXIN	5GHz TX RF Input Signal
4	GND	Ground
5	RX	5GHz LNA Output Signal
6	GND	Ground
7	C0	Switch Control Logic 1
8	C1	Switch Control Logic 2

Pin No.	Name	Description
9	VDD	LNA Supply Voltage
10	GND	Ground
11	ANT	5GHz Antenna output
12	GND	Ground
13	DET	Power Detector Output
14	H/L Lin	High-Low linearity Control
15	VCC1	Power Amplifier Supply Voltage
16	VCC2	Power Stage Supply Voltage

**DATA SHEET**

**SE5012T: 5 GHz Front End Module with Power Detector**

**Absolute Maximum Ratings**

These are stress ratings only. Exposure to stresses beyond these maximum ratings for a long period of time may cause permanent damage to, or affect the reliability of the device. Avoid operating the device outside the recommended operating conditions defined below. This device is ESD sensitive. Handling and assembly of this device should be at ESD protected workstations.

Symbol	Definition	Min.	Max.	Unit
V <sub>CC</sub>	Supply Voltage on pins VCC1, VCC2	-0.3	5.5	V
V <sub>DD</sub>	Supply Voltage on pin VDD	-0.3	3.6	V
EN	DC input on Enable	-0.3	3.6	V
TXIN	RF Input Power, RFout into 50Ω match	-	12	dBm
T <sub>STG</sub>	Storage Temperature Range	-40	150	°C
ESD <sub>HBM</sub>	JEDEC JESD22-A114 all pins	-	500	V

**Recommended Operating Conditions**

Symbol	Parameter	Min.	Max.	Unit
V <sub>CC</sub>	Supply Voltage on pins VCC1, VCC2	3.0	5.5	V
V <sub>DD</sub>	Supply Voltage on pin VDD	3.0	3.6	V
T <sub>A</sub>	Ambient Temperature	-40	85	°C

**Control Logic Characteristics**

Conditions: V<sub>CC</sub> = 5.0 V; V<sub>DD</sub> = V<sub>EN</sub> = 3.3 V, T<sub>A</sub> = 25 °C, as measured on Skyworks Solutions' SE5012T-EV1 evaluation board, unless otherwise noted.

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I <sub>CC-802.11a</sub>	Supply Current, Transmit Mode	P <sub>OUT</sub> = 21 dBm, 54 Mbps, 64 QAM, VCC = 5.0V, H/L Lin = 3.3V (High Linearity)	-	270	-	mA
		P <sub>OUT</sub> = 17 dBm, 54 Mbps, 64 QAM, VCC = 3.3V, H/L Lin = 3.3V (High Linearity)	-	195	-	
		P <sub>OUT</sub> = 13 dBm, 54 Mbps, 64 QAM, VCC = 3.3V, H/L Lin = 0V (Low Linearity)	-	165	-	
I <sub>DD</sub>	LNA Supply Current	V <sub>EN</sub> = C0 = 0V; C1 = 3.3V		13		
I <sub>OFF</sub>	Supply Current	V <sub>EN</sub> = 0 V, No RF, C0=C1=0 V Measured on VCC, VDD pins	-	20	50	μA
V <sub>ENH</sub>	Logic High Voltage	-	2.8	-	3.6	V
V <sub>ENL</sub>	Logic Low Voltage	-	-0.3	-	0.3	V
I <sub>ENH</sub>	Input Current Logic High Voltage	10Kohm on chip pull down resistor	-	330	400	μA
I <sub>ENL</sub>	Input Current Logic Low Voltage	-	-	<1	-	μA

**DATA SHEET**

**SE5012T: 5 GHz Front End Module with Power Detector**

**Switch Logic Characteristics**

Conditions:  $V_{CC} = 3.0\text{ V to }5.5\text{ V}$ ,  $V_{DD} = V_{EN} = 3.3\text{ V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5012T-EK1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
ON	Low Loss Switch Control Voltage	High State = $V_{CTL\_ON} - V_{CTL\_OFF}$	2.8	-	3.6	V
OFF	High Loss Switch Control Voltage	Low State = $V_{CTL\_OFF} - V_{CTL\_OFF}$	0	-	0.3	V
$C_{CTL}$	Control Input Capacitance	-	-	-	100	pF
$I_{CTL}$	Control Line Current	$V_{CTL} = V_{CTL\_ON}$	-	2	10	$\mu\text{A}$

**Switch Control Logic Table**

C0	C1	EN	Hi/L Lin	ANT
ON	OFF	ON	OFF	<b>TX Low Linearity</b>
ON	OFF	ON	ON	<b>TX High Linearity</b>
OFF	OFF	OFF	D/C	<b>Rx Bypass</b>
OFF	ON	OFF	D/C	<b>Rx LNA ON</b>
ON	ON	Un-supported state		

Note: D/C = don't care



**DATA SHEET**
**SE5012T: 5 GHz Front End Module with Power Detector**
**AC Electrical Characteristics**
**Transmit Characteristics**

Conditions:  $V_{CC} = 5.0V$ ,  $V_{DD} = V_{EN} = C0 = H/L Lin = 3.3V$ ,  $C1 = 0V$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5012T-EV1 evaluation board, unless otherwise noted

Symbol	Parameter		Conditions	Min.	Typ.	Max.	Unit
f <sub>L-U</sub>	Frequency Range		-	5.15	-	5.85	GHz
P <sub>OUT</sub>	Output Power OFDM Signal, 64QAM, EVM = 3%	High Linearity Mode H/L Lin = 3.3V	VCC = 5.0 V	-	21	-	dBm
			VCC = 3.3 V	-	17	-	
		Low Linearity Mode H/L Lin = 0V	VCC = 5.0 V	-	17	-	
			VCC = 3.3 V	-	13	-	
P <sub>1dB</sub>	Output 1dB compression point, No Modulation		VCC = 5.0V	-	27	-	dBm
			VCC = 3.3V	-	23	-	
S <sub>11</sub>	Input Return Loss		P <sub>IN</sub> = -25 dBm	-	12	-	dB
S <sub>21</sub>	Small Signal Gain, P <sub>IN</sub> = -25dBm		5V, High or Low Linearity Mode	29	-	35	dB
			3.3V, High or Low Linearity Mode	28	-	33	
ΔS <sub>21</sub>	Small Signal Gain Variation		Gain variation over single 40MHz channel	-	-	0.5	dB
			Gain Variation over band	-	3.5	-	
S <sub>21_3.8</sub>	Out of Band Gain		Gain at 3.8GHz	-	-	15	dB
2f	Harmonic		P <sub>OUT</sub> = 17 dBm, OFDM	-	-50	-45.2	dBm/MHz
3f				-	-50	-45.2	
t <sub>r</sub> , t <sub>f</sub>	Rise and Fall Time		-	-	0.5	-	us
STAB	Stability		P <sub>OUT</sub> = 17 dBm, 54 Mbps, 64 QAM, VSWR = 6:1, all phases	All non-harmonically related outputs less than -50 dBc/100 kHz			
Ruggedness	Tolerance to output load mismatching		Constant P <sub>IN</sub> equal to P <sub>OUT</sub> = 21 dBm at 50ohms, 54 Mbps, 64 QAM, VCC = 5.5V, VSWR = 6:1, all phases	No damage			
Robust	Robustness to input power		P <sub>IN</sub> = 12dBm, CW, VSWR = 6:1, all phases	No damage			

**DATA SHEET**  
**SE5012T: 5 GHz Front End Module with Power Detector**

**Receive Characteristics**

Conditions:  $V_{CC} = 3.0\text{ V to }5.5\text{ V}$ ,  $V_{DD} = C1 = 3.3\text{V}$ ,  $V_{EN} = C0 = 0\text{V}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5012T-EK1 evaluation board, all unused ports terminated with 50 ohms, unless otherwise noted.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
F <sub>OUT</sub>	Frequency Range	-	5.15	-	5.85	GHz
RX	Insertion Loss	Bypass Mode: C0 = C1 = 0V	-	-5	-	dB
	RX Gain	High Gain Mode	11	12	-	
NF	Noise Figure	High Gain Mode	-	2.5	-	dB
RX <sub>RL</sub>	Input Return Loss	At the Antenna port	-	-11	-	dB
	Output Return Loss	At RX RF output	-	-8	-	
RxIP1DB	Input P1DB	Measured at ANT Port; High Gain Mode	-	-5	-	dBm
		LNA Bypass Mode	-	10	-	
Rx_2.4int	Max 2.4Ghz interferer power	1 dB degradation of IP1DB	-	-	0	dBm
TX <sub>LEAK</sub>	Transmit Power at RX Output	$V_{EN} = C0 = \text{H/L Lin} = 3.3\text{V}$ , $C1 = 0\text{V}$ 24dBm at the ANT port	-	-13	-	dBm
T <sub>on/off</sub>	T/R on/off switching speed	C0, C1 (50%) to RF output (10% or 90%)	-	300	-	nSec


**DATA SHEET**

**SE5012T: 5 GHz Front End Module with Power Detector**

**Power Detector Characteristics**

Conditions:  $V_{CC} = 3.0\text{ V to }5.5\text{ V}$ ,  $V_{DD} = V_{EN} = C0 = 3.3\text{V}$ ,  $C1 = 0\text{V}$ ,  $f = 5.4\text{ GHz}$ ,  $T_A = 25\text{ }^\circ\text{C}$ , as measured on Skyworks Solutions' SE5012T-EV1 evaluation board, unless otherwise noted

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
PDR	P <sub>OUT</sub> detect range	-	0	-	P <sub>1dB</sub>	dBm
VDET <sub>22</sub>	Detector voltage	P <sub>OUT</sub> = 22 dBm	0.7	-	0.9	V
VDET <sub>16</sub>	Detector voltage	P <sub>OUT</sub> = 16 dBm	0.50	-	0.60	V
VDET <sub>2</sub>	Detector voltage	P <sub>OUT</sub> = 2 dBm	0.25	-	0.35	V
PDZ <sub>OUT</sub>	Output Impedance	-	-	5	-	KΩ




**Figure 3: SE5012T Power Detector Characteristic**



**DATA SHEET**  
**SE5012T: 5 GHz Front End Module with Power Detector**

**Package Diagram**

This package is Pb free and RoHS compliant. The product is rated MSL1.



**Figure 4: SE5012T Package Diagram**

**DATA SHEET**  
**SE5012T: 5 GHz Front End Module with Power Detector**

**Recommended Land and Solder Patterns**




Figure 5: SE5012T Recommended Land and Solder Pattern

**Package Handling Information**

Because of its sensitivity to moisture absorption, instructions on the shipping container label must be followed regarding exposure to moisture after the container seal is broken, otherwise, problems related to moisture absorption may occur when the part is subjected to high temperature during solder assembly. The SE5012T is capable of withstanding a Pb free solder reflow. Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment. If the part is manually attached, precaution should be taken to insure that the device is not subjected to temperatures above its rated peak temperature for an extended period of time. For details on both attachment techniques, precautions, and handling procedures recommended, please refer to:


- “Quad Flat No-Lead Module Solder Reflow & Rework Information”, *Document Number QAD-00045*
- “Handling, Packing, Shipping and Use of Moisture Sensitive QFN”, *Document Number QAD-00044*



Caution! Class 1B ESD sensitive device

**DATA SHEET**  
**SE5012T: 5 GHz Front End Module with Power Detector**


**Branding Information**



**Figure 6: SE5012T Branding**

**Tape and Reel Information**


Parameter	Value
Devices Per Reel	3000
Reel Diameter	13 inches
Tape Width	12 millimeters



**Figure 7: SE5012T-R Tape and Reel Information**

**Document Change History**

Revision	Date	Notes
1.0	Nov 05, 2010	Created
1.1	Nov 14, 2011	Updated package outline drawing Updated Max 2.5Ghz interferer power specification for LNA Add TX leakage at RX output port Update operating frequency Update TX gain slope
1.2	Jan 31, 2012	Updated current at 13dBm RX S11, S22
1.3	Apr 03, 2012	Updated with Skyworks logo and disclaimer statement
1.4	Jun 14, 2012	Updated LNA gain



**SKYWORKS®**

## **DATA SHEET**

### **SE5012T: 5 GHz Front End Module with Power Detector**

---

Copyright © 2012 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at [www.skyworksinc.com](http://www.skyworksinc.com), are incorporated by reference.