

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Self-Laminating Adhesive Sign Carriers





Material Chart

Material	Print Method	Temperature Range	Features
Rigid Vinyl	Pre-Printed		Indoor/outdoor rated; rigid material accepts ink; resistant to UV light, chemical atmosphere, and abrasion; excellent for applications where adhesives will not work.

	Height		Carriers Per	Std. Pkg.	Std. Ctn.					
Part Number	ln.	mm	ln.	mm	Pkg.	Qty.	Qty.			
Adhesive										
SEZ-SNC4	7.00	178.0	6.00	152.0	5	1	10			
SEZ-SNC3	12.00	305.0	6.00	152.0	5	1	10			
SEZ-SNC2	10.50	267.0	7.00	178.0	5	1	10			
SEZ-SNC1	12.00	305.0	9.50	241.0	5	1	10			
Non-Adhesive										
SEZ-RSC1	7.00	178.0	6.00	152.0	5	1	10			
SEZ-RSC2	10.50	267.0	7.00	178.0	5	1	10			
SEZ-RSC3	12.00	305.0	9.50	241.0	5	1	10			
SEZ-RSC4	12.00	305.0	6.00	152.0	5	1	10			

Self-Laminating Cable Marker Holders for Large Cables or Cable Bundles



Material Chart

Material	Print Method	Temperature Range	Features
Rigid Vinyl, Self-Laminating	Pre-Printed	0°F to 176°F (-18°C to 80°C)	Indoor/outdoor rated; high quality, rugged material resistant to abrasion; legend is protected by overlaminate; use where adhesives will not work.

		Width		Height		Tags Per	Std. Pkg.	Std. Ctn.
Part Number	Color	ln.	mm	ln.	mm	Pkg.	Qty.	Qty.
SLCT-IG	Gray	3.00	76.2	1.31	33.3	25	1	4
SLCT-OR	Orange	3.00	76.2	1.31	33.3	25	1	4
SLCT-WH	White	3.00	76.2	1.31	33.3	25	1	4
SLCT-YL	Yellow	3.00	76.2	1.31	33.3	25	1	4
SLCT-3	White	4.00	101.6	0.50	12.7	25	1	4
SLCT-3OR	Orange	4.00	101.6	0.50	12.7	25	1	4
SLCT-3YL	Yellow	4.00	101.6	0.50	12.7	25	1	4

Attach with Panduit Intermediate or Standard Cross-Section Cable Ties.

Component Labe	els for Laser/Ink Jet Pri	nters S	upplied	l on 8.	5" x 11	I" She	eets	
C200X100V.I.I	White polyester label	2.00	50.8	1.00	25.4	_	1000	500

C200X100YJT White, polyester label. 2.00 50.8 1.00 25.4 — 2500 10000	Component Labels for Thermal Transfer Desktop Printers Supplied on Rolls										
	C200X100YJT	White, polyester label.	2.00	50.8	1.00	25.4	_	2500	10000		

Component Cass	ettes for Panther™ LS8	Hand-	Held Th	ermal	Trans	fer Pri	inter	
C200X100YJC	White, polyester label, 200/cassette.	2.00	50.8	1.00	25.4	_	1	10

A. System Overview

B1. Cable Ties

B2. Cable Accessories

> B3. ainless eel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

> D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/ Tagout & Safety

> F. Index