



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**SF1186E-1**

**1575.42 MHz  
SAW Filter**



**SM3030-6**

- **Low-loss GPS RF SAW Filter**
- **No Matching Required for 50 Ω Source/Load Impedances**
- **Complies with Directive 2002/95/EC (RoHS)**



**Absolute Maximum Ratings**

| Rating   | Value       | Units |
|--|-------------|-------|
| Input Power Level                                      | +10         | dBm   |
| DC Voltage on any Non-grounded Terminal                | 3           | V     |
| Operating Temperature Range                            | -40 to +85  | °C    |
| Storage Temperature Range in Tape and Reel             | -40 to +85  | °C    |
| Storage Temperature Range of Filter                    | -50 to +100 | °C    |
| Maximum Soldering Profile, 5 cycles/10 seconds maximum | 265         | °C    |

**Electrical Characteristics**

| Characteristic   | Sym                                     | Notes | Min | Typ     | Max   | Units             |
|--|---|-------|-----|---------|-------|-------------------|
| Center Frequency   | $f_c$                                   |       |     | 1575.42 |       | MHz               |
| Insertion Loss, 1574.42 to 1576.42 MHz                           | IL                                      |       |     | 2.9     | 4.0   | dB                |
| Amplitude Ripple, 1574.42 to 1576.42 MHz                         |   |       |     | 0.1     | 1.5   | dB <sub>P-P</sub> |
| Input/Output VSWR, 1574.42 to 1576.42 MHz                        |   |       |     | 1.55:1  | 2.5:1 |                   |
| Attenuation, Referenced to 0 dB:                                 |   |       |     |         |       | dB                |
| 1 to 890 MHz   |   |       | 40  | 60      |       |                   |
| 890 to 1475 MHz  |   |       | 36  | 55      |       |                   |
| 1475.42 MHz  |   |       | 36  | 50      |       |                   |
| 1535.42 MHz  |   |       | 29  | 50      |       |                   |
| 1615.42 MHz  |   |       | 25  | 42      |       |                   |
| 1675.42 MHz  |   |       | 40  | 55      |       |                   |
| 1700 to 3000 MHz   |   |       | 25  | 38      |       |                   |
| Source Impedance   | $Z_S$                                   |       |     | 50      |       | Ω                 |
| Load Impedance   | $Z_L$                                   |       |     | 50      |       | Ω                 |
| Case Style   | SM3030-6 3.0 x 3.0 mm Nominal Footprint |       |     |         |       |                   |
| Lid Symbolization (Y=year, WW=week, S=shift) dot=pin 1 indicator | 978, YWWS                               |       |     |         |       |                   |
| Standard Reel Quantity   | Reel Size 7 inch                        |       |     |         |       | 500 Pieces/Reel   |
|  | Reel Size 13 inch                       |       |     |         |       | 3000 Pieces/Reel  |

**Electrical Connections**


| Connection  | Terminals  |
|-------------|------------|
| Input       | 2          |
| Output      | 5          |
| Case Ground | All others |

**CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.**


**NOTES:**

1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50 Ω and measured with 50 Ω network analyzer.
2. Unless noted otherwise, all frequency specifications are referenced to the nominal center frequency,  $f_c$ .
3. Rejection is measured as attenuation below the minimum IL point in the passband. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
4. "LRIP" or "L" after the part number indicates "low rate initial production" and "ENG" or "E" indicates "engineering prototypes."
5. The design, manufacturing process, and specifications of this filter are subject to change.
6. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
7. US and international patents may apply.
8. Murata, stylized Murata logo, and Murata N.A., Inc. are registered trademarks of Murata Manufacturing Co., Ltd.



# Filter Passband Response





# Filter Broadband Response



## Filter Input SWR and Impedance





## Filter Output SWR and Impedance



# SM3030-6 Case

## 6-Terminal Ceramic Surface-Mount Case 3.0 X 3.0 mm Nominal Footprint



PCB Footprint Top View


### Case and PCB Footprint Dimensions

| Dimension | mm   |      |      | Inches |       |       |
|-----------|------|------|------|--------|-------|-------|
|           | Min  | Nom  | Max  | Min    | Nom   | Max   |
| A         | 2.87 | 3.00 | 3.13 | 0.113  | 0.118 | 0.123 |
| B         | 2.87 | 3.00 | 3.13 | 0.113  | 0.118 | 0.123 |
| C         | 1.12 | 1.25 | 1.38 | 0.044  | 0.049 | 0.054 |
| D         | 0.77 | 0.90 | 1.03 | 0.030  | 0.035 | 0.040 |
| E         | 2.67 | 2.80 | 2.93 | 0.105  | 0.110 | 0.115 |
| F         | 1.47 | 1.60 | 1.73 | 0.058  | 0.063 | 0.068 |
| G         | 0.72 | 0.85 | 0.98 | 0.028  | 0.033 | 0.038 |
| H         | 1.37 | 1.50 | 1.63 | 0.054  | 0.059 | 0.064 |
| I         | 0.47 | 0.60 | 0.73 | 0.019  | 0.024 | 0.029 |
| J         | 1.17 | 1.30 | 1.43 | 0.046  | 0.051 | 0.056 |
| K         |      | 3.20 |      |        | 0.126 |       |
| L         |      | 1.70 |      |        | 0.067 |       |
| M         |      | 1.05 |      |        | 0.041 |       |
| N         |      | 0.81 |      |        | 0.032 |       |
| O         |      | 0.38 |      |        | 0.015 |       |



### Case Materials

| Materials          |  |
|--------------------|--|
| Solder Pad Plating | 0.3 to 1.0 $\mu\text{m}$ Gold over 1.27 to 8.89 $\mu\text{m}$ Nickel |
| Lid Plating        | 2.0 to 3.0 $\mu\text{m}$ Nickel                                      |
| Body               | $\text{Al}_2\text{O}_3$ Ceramic                                      |
| Pb Free            |  |


### TOP VIEW



### BOTTOM VIEW



## Tape and Reel Specifications



| "B"    |             | Quantity Per Reel |
|--------|-------------|-------------------|
| Inches | millimeters |                   |
| 7      | 178         | 500               |
| 13     | 330         | 3000              |

## COMPONENT ORIENTATION and DIMENSIONS

| Carrier Tape Dimensions |         |
|-------------------------|---------|
| Ao                      | 3.35 mm |
| Bo                      | 3.35 mm |
| Ko                      | 1.40 mm |
| Pitch                   | 8.0 mm  |
| W                       | 12.0 mm |

