



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






## .050" [1.27 mm] Contact Centers, IDC Sockets, .100" [2.54 mm] Row Spacing Insulation Displacement With or Without Strain Relief - SFH Series Mates with SBH41 series (See opposite page)

### SPECIFICATIONS

- Centered Polarizing Key
- Operating Temperature: -40°C to +105°C
- UL Flammability Rating: 94V-0
- Contact Resistance: 30 Megohms Max.
- Current Rating: 1 Amp
- Dielectric Withstanding: 500 VAC
- Insulation Resistance: 1000 Megohms



### PART NUMBER OPTIONS

SFH41 - P P P B - D 10 - ID - BK

#### SERIES

- SFH41 = IDC Socket Without Strain Relief, .050" [1.27 mm] Contact Centers by .100" [2.54 mm] Row Spacing
- SFH413 = IDC Socket With Strain Relief, .050" [1.27 mm] Contact Centers by .100" [2.54 mm] Row Spacing

#### INSULATOR MATERIAL

P = PBT

#### CONTACT MATERIAL

P = Phosphor Bronze

#### CONTACT FINISH - RoHS Compliant

P = Gold Flash Overall

E = .000100" Pure Tin, Matte, Overall

V = Gold Flash on Contact Surface, Nickel on Termination

#### COLOR

BK = Black

#### TERMINATION TYPE

ID = Insulation Displacement

#### NUMBER OF CONTACT POSITIONS

05, 08, 10, 13, 15, 17, 20, 25, 30, 34, 40, 50


#### NUMBER OF ROWS

D = Dual Row



#### CONTACT CENTERS

B = .050" [1.27 mm]


### DIMENSIONS For complete drawings, go to [www.sullincorp.com](http://www.sullincorp.com) or e-mail [techsupport@sullincorp.com](mailto:techsupport@sullincorp.com) Dimensions in [ ] are in millimeters, all others are in inches.



**INSULATION DISPLACEMENT (ID) without Strain Relief**  
Requires SFH41  
Example P/N: SFH41-PPPB-D20-ID-BK



**INSULATION DISPLACEMENT (ID) with Strain Relief**  
Requires SFH413  
Example P/N: SFH413-PPPB-D20-ID-BK



Headers