

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







**Model: SFTD Series** 

## **Disconnects**

## Description

Some circuits require disconnecting means without re-wiring. B&B Electronics offers 2 types of screwless disconnects, both with a rating of 24A. 20pieces/package. Beige.





	67.0		L 67.0 −−	
	SFTD3 width: 8mm		SFTD4 width: 8mm	
Electrical ratings				
Voltage/Current/Cross section	500V~/10A/4mm <sup>2</sup>		500V~/10A/4mm <sup>2</sup>	
UL/UL	600V~/10A		600V~/10A	
Insulation stripping length	12mm		12mm	
Connection Data				
Solid Strand, Screw Connection	0.54mm <sup>2</sup>		0.54mm <sup>2</sup>	
Fine Strand, Screw Connection	0.54mm <sup>2</sup>		0.54mm <sup>2</sup>	
AWG Conductor	2610		2610	
Ordering Data	Cat. No	Qty	Cat. No	Qty
Poliammide 6.6	SFTD3BEIGE	20	SFTD4BEIGE	20
Mounting Rails	Type Cat. No	Qty	Type Cat. No	Qty
MR 35 X 7.5 Slotted MR 35 X 15 Slotted	Slotted ERS35	1m	Slotted ERS35	1m
	Slotted ERS35-HI	PP 1m	Slotted ERS35-HP	P 1m
ERS35 ERS35-HPP				
End Bracket	Cat. No	Qty	Cat. No	Qty
ES1 For 35mm Din	ES4BEIGE	100	ES4BEIGE	100
End Plate				
Thickness 1.5mm EP Poliammide 6.6	EPSCF3BEIGE	10	EPSCF3BEIGE	10
Cross-Connection				
11 111 111	CCS4/2	25	CCS4/2	25
been but to	CCS4/3	20	CCS4/3	20
2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	CCS4/4	15	CCS4/4	15
	CCS4/10	5	CCS4/10	5
Group Marking				
GM	GMBEIGE	50	GMBEIGE	50