



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



20A single phase

SL20.110/.111

- Input: AC 115/230V Auto Select
- Output: 24...28V / 480W (600W)
- 90% Efficiency
- Ideal for parallel operation
- Overload behaviour adjustable!
(Continuous current / Hiccup)



PULS

CB
Scheme
IEC60950

cUL[®]US
UL508 LISTED
IND. CONT. EQ.
18 WM, 60°C

C[®]UL[®]US
UL60950 E137006
CUL/CSA-C22.2
No 60950

Type approval
acc. to:
• IEC / EN60950
• EN50178
• Overvolt. cat. III
• EN60204

CE
EMC and
Low Volt.
Directive

Data sheet

Input

Input voltage	AC 100-120V/200-240V, 47-63Hz Auto Select
Rated tolerances	
• Continuous operation	AC 85-132V resp. AC 184-264V
• Short-term (1 min) at 24V/20A	AC 85-140V resp. AC 170-280V
Input current I_n	<10A (115V range) <5A (230V range)
Inrush current limiting with active bypass of the limiting resistor (NTC).	
Inrush current I_{pk}	<18A at AC 264V ($T_{amb} = +25^\circ\text{C}$, cold start) <37A at AC 264V ($T_{amb} = +50^\circ\text{C}$, cold start)
Fuse loading I^2t	<5A ² s ($T_{amb} = +25^\circ\text{C}$, cold start) <8A ² s ($T_{amb} = +50^\circ\text{C}$, cold start)
To be fused with a 16A, B-type 'circuit-breaker' switch based on the usual thermomagnetic overload sensing principle (used anyway to fuse the input lines).	
Harmonic current emissions (PFC)	SL20.110: no SL20.111: acc. to EN 61000-3-2
Transient handling	Transient resistance acc. to VDE 0160 / W2 (750V / 1.3ms), for <i>all</i> load conditions.
Hold-up time	30ms at 24V/20A, AC 230Vin 30ms at 24V/20A, AC 120Vin 15ms at 24V/20A, AC 100Vin

Efficiency, Reliability etc.*

Efficiency	typ. 90% (AC 230V, 24V/20A)
Losses	typ. 53W (AC 230V, 24V/20A)
MTBF	519.000h acc. to Siemensnorm SN29500 (24V/20A, 230V, $T_{amb} = 40^\circ\text{C}$)
Life cycle (electrolytics)	The unit exclusively uses longlife electrolytics, specified for +105°C (cf. 'The SilverLine', p.2). High reliability, as <ul style="list-style-type: none"> • only five aluminium electrolytics and • no small aluminium electrolytics are used.

* For further information see data sheets „The SilverLine“, „SilverLine Family Branches“ and mechanics data sheet

Order information

Order number	SL20.110 (without PFC) SL20.111 (including PFC)	Description	SLZ02 (wall mounting set; contains 2 pcs.)
---------------------	--	--------------------	--

Output

Output voltage	DC 24...28V, adjustable by (covered) front panel potentiometer. Adjust. range guaranteed
Output noise suppression	EN 61000-6-3 (class B) is fulfilled even when using long, unshielded output cables
Ambient temperature range T_{amb}	Operation: 0°C...+70°C (>60°C: Derating) Storage: -25°C...+85°C
Rated continuous loading with convection cooling:	
• $T_{amb}=0^\circ\text{C} - 60^\circ\text{C}$	24V/20A resp. 28V/18A short-term (<30s) 24V/25A resp. 28V/22A
Derating	12W/K (at $T_{amb} = 60-70^\circ\text{C}$)
Voltage regulation	better than 2% over all
Ripple	(incl. spikes (20MHz bandw.), 50Ω measurem.)
• Output charact. S	<20mV _{pp} (<0.1%)
• Output charact. P	<40mV _{pp} (In: AC 230V, Out: 24V/20A)
(S/P: Single/Parallel Mode)	<100mV _{pp} (In: AC 184V, Out: 24V/20A)
Over-voltage protection	At 31V ± 3%: switch to hiccup mode
Front panel indicators:	
• Green LED on, when $V_{out} > U_T$, where U_T is appr. 2V below V_{out} adjusted (24V...28V)	
• Red LED on, when $V_{out} < U_T$	
Parallel operation	Yes, up to ten SL20
To achieve current sharing:	
• Plug jumper into pos. 'Output parallel use'. This alters the output V/I characteristic to be 'softer' (25V at 0.4A, 24V at 20A). The output voltage can still be adjusted.	
• Missing jumper = 'parallel use', i.e. 'soft' characteristic	
Power back immunity	max. 30V

Construction / Mechanics*

Housing dimensions and Weight

- W x H x D 220mm x 124mm x 102mm (+ DIN rail)
- Free space for ventilation above/below 70mm recommended left/right 25mm recommended
- Weight 1.8kg (SL20.110) resp. 2.5kg (SL20.111)

Design advantages:

- All connection blocks are easy to reach as mounted at the front panel.
- PVC insulated cable can be used for all connections, as the connection blocks are mounted in the cooler area on the underside of the unit.

Start / Overload Behaviour

Startup delay	typ. 0.55s
Rise time	appr. 20-80ms, depending on load
Overload behaviour (see characteristic on the right)	<ul style="list-style-type: none"> • Power Boost: Short-term (<30s) 125% output power without voltage drop. • Electronic current limiting, protects from overload and short-circuit. • High overload/short-circuit behaviour ($V_{out} < 14V$) switchable between PULS Overload Design and hiccup mode. Switching by jumper on bottom of the unit; it is not necessary to open the unit for this purpose.

PULS Overload Design™ (continuous current):

- No disconnection/hiccup, thus overloading is possible also for a longer period of time (load start-up), ideal for parallel operation.
- High overload/short-circuit current due to straight characteristic; each bias point of the V/I characteristic extends 20A.

Advantage: Due to the high and continuously supplied overload current the unit starts reliably even with awkward loads (DC-DC converters, motors). No 'sticking' such as can occur with fold-back characteristics, and secondary fuses trigger more reliably.


Hiccup mode:

- Unit switches off when high overload occurs ($V_{out} < \text{appr. } 14V$) with subsequent periodical switch-on attempts (hiccup mode):
 - Duration of switch-on attempts:
 - appr. 0.1s at short-circuit or appr. 1s at overload
 - Duration between switch-on attempts: appr. 1.5s
- $V_{out} > \text{appr. } 14V$: The output current is continuous. The V/I characteristic equals that of the PULS Overload Design™; each bias point of the V/I characteristic extends 20A.


Further information

- Further information, especially about
- EMC
 - Connections
 - Safety, Approvals
 - Mechanics und Mounting,
- see page 2 of the „The SilverLine“ data sheet
- For detailed dimensions**
see SilverLine mechanics data sheet SL20


Output characteristic (typ.)



Efficiency (typ., at $V_{out}=24V$)




Hold-up time (min., at $V_{out}=24V$)



Unless otherwise stated, specifications are valid for AC 230V input voltage, +25°C ambient temperature, and 5 min. run-in time. They are subject to change without prior notice. All data is valid for the SL20.110. Regarding the SL20.111 (including PFC) some values may differ (please contact us if necessary).

Your partner in power supply:



PULS GmbH
 Arabellastraße 15
 D-81925 München
 Tel.: +49 89 9278-0
 Fax: +49 89 9278-199
 www.puls-power.com