

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Specification Sheet

Part Number: SM1BK75MT



Self-Extinguishing Flexiform Grommet, Panel Thickness 0.039"-0.079", PVC, Black, 75m/roll

Article Number	800-00004
Туре	SM1
Color	Black (BK)
Features & Benefits	• Fits in holes of all shapes and sizes without the aid of tools or adhesives, making installation easy. • Easily cut to the right length with scissors, thus reducing stock and eliminating waste. • Can be used on any type of material including wood, steel, aluminum, plexiglass and glass, ensuring flexibility of application.
Quantity Per	reel

Product Description

EdgeGuard is used to cover panel edging to protect cables, prevent chafing and provide an attractive finish. The EdgeGuard is manufactured from a flexible PVC compound ensuring ease of use.

Short Description	Self-Extinguishing Flexiform Grommet, Panel Thickness 0.039"-0.079", PVC, Black, 75m/roll
Global Part Name	SM1-PVC-BK
Length L (Imperial)	246.1
Length L (Metric)	75
Width W (Imperial)	0.1969
Width W (Metric)	5.0
Height H (Imperial)	0.248
Height H (Metric)	6.3
Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.079
Panel Thickness Min (Metric)	1.00
Panel Thickness Max (Metric)	2.00
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 HB

Halogen free	No
Operating Temperature (Metric)	-85°F to +221°F (-65°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	246.1
Package Quantity (Metric)	75
Customs Number	3926909987
Content Unit(BMEcat)	metre
Weight (Metric)	2.56

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2018} HellermannTyton. All rights reserved.