

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









4:1 Shrinkable Polyolefin Tubing Flexible · Dual Wall

Smaller Sizes



Description: DAFLEX SM278 is a flexible, large ratio, heat shrinkable tubing with a meltable adhesive liner. When 120°C is applied, the tubing will shrink to 25% of its supplied size (4:1). Longitudinal shrinkage is 10% maximum. As the outer wall shrinks, the inner adhesive liner melts and flows. When cooled, it offers protection for a variety of electrical applications as well as "sealed-in" protection from chemicals and oils.

Because of its large shrink ratio and adhesive liner it offers excellent protection for cable repairs and retrofitting.

Operating Temperature: -55°C to +135°C.

Meets or exceeds MIL-I-23053/4 Class 3.

UL VW-1, CSA OFT (outer wall only).

Daburn Cat. No.	Nom. Size	Expanded ID		Recovered ID		Min. Rec. Wall		Standard	Click to Order
		IN.	mm	IN.	mm	IN.	mm	Put-Up	Prototype Quantities
SM278-3/16	3/16	.157	4	.039	1	.0354	.90	200ft Spl*	<u>Order</u>
SM278-5/16	5/16	.315	8	.079	2	.0354	.90	100ft Spl**	<u>Order</u>
SM278-1/2	1/2	.472	12	.118	3	.0512	1.30	400ft 4ft lgths	<u>Order</u>
SM278-3/4	3/4	.630	16	.157	4	.0630	1.60	200ft 4ft lgths	<u>Order</u>
SM278-1"	1"	.945	24	.236	6	.0827	2.10	100ft 4ft lgths	<u>Order</u>
SM278-1 1/4"	1 1/4"	1.260	32	.315	8	.0906	2.30	80ft 4ft lgths	<u>Order</u>

Standard Color: Black. Clear and other colors are available to order. **Standard Package:** *1000FT, **600FT. All others Standard Package shown.

To additional <u>Heat Shrinkable Tubing</u>.
To <u>Heat Shrinkable Tubing Cross Reference</u> Property Chart.
Back to DABURN'S <u>Home Page</u>.

Daburn electronics & cable corp. 224 Pegasus Ave. Northvale, NJ 07647 Tel: 201-768-5400 Fax: 201-768-9642

E-Mail: daburn@daburn.com URL: http://www.daburn.com/