



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## TAA-Compliant SmartPro 120V 500VA 300W Line-Interactive UPS, 1U Rack/Tower, Network Card Options, USB, DB9 Serial

MODEL NUMBER: **SMART500RT1UTAA**



### Description

Tripp Lite's SMART500RT1UTAA intelligent, line-interactive rack/tower uninterruptible power supply prevents data loss, downtime and equipment damage due to power outages, voltage fluctuations and transient surges. Requires only one rack space (1U) in a 2 or 4 post rack, with included accessories for upright tower placement. Large internal batteries offer 14.6 minutes half load runtime and 3.2 minutes at full load. Maintains regulated 120V nominal output without using battery power during brownouts as low as 90V. 500VA/300 watt power handling capability is compatible with networking, telecom and other sensitive electronic applications. Includes 6 UPS supported outlets with a single outlet load bank that can be individually controlled via software interface to reboot select equipment on demand or shed less significant loads to extend battery runtime for more critical equipment. Includes 1 surge-only outlet for peripherals not requiring battery backup.

Supports simultaneous remote monitoring of UPS and site power conditions via built-in USB and DB9 monitoring ports. PowerAlert UPS monitoring and unattended shutdown software is available via free download. Emergency Power Off (EPO) interface offers option for instantaneous power-off of UPS and connected equipment in the case of fire or emergency. Multi-function audible alarms and set of 5 front panel LEDs offer at-a-glance notification of UPS and line power status. Network-grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges and line noise. Attractive all-black color scheme.

### Features

- Federal Trade Agreements Act / TAA compliant for GSA schedule purchases
- Tripp Lite SMART500RT1UTAA .5 kVA / 500VA / 300 watt line interactive UPS
- 1U rack / tower compatible form factor
- NEMA 5-15P input connection; 7 NEMA 5-15R output receptacles

### Highlights

- Federal Trade Agreements Act / TAA compliant for GSA schedule purchases
- 500VA line-interactive 1U rack/tower UPS
- 120V nominal output during brownouts as low as 90V
- USB, RS232, EPO and slot for Network Management Card options
- Front panel status LEDs; 1 switched output load bank
- NEMA 5-15P input; 7 NEMA 5-15R outlets

### Package Includes

- SMART500RT1UTAA UPS System
- Mounting hardware
- Cabling for USB & DB9 monitoring and EPO switching
- Instruction manual



- Installed depth of only 11.8 in / 29.8 cm
- Large internal batteries offer runtimes of 14.6 minutes at half load (250VA/150 watts) and 3.2 minutes at full load (500VA/300 watts)
- Maintains regulated 120V nominal output during brownouts as low as 90V
- Includes 6 UPS-supported outlets and 1 surge-only outlet
- One of the UPS supported outlets is switched for remote load shedding or rebooting of an individual device
- USB & Serial ports enable data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert)
- Supports detailed monitoring of equipment load levels, self-test data, and utility power condition via built-in RS-232 and USB interfaces
- Compatible with Tripp Lite UPS management card options TLNETCARD, WEBCARDLX and SNMPWEBCARD
- Supports Tripp Lite's WatchDog software application to restore operation to locked equipment through soft reboot of application, OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications (requires optional WATCHDOGSW)
- Emergency Power Off (EPO) interface with cable
- Multi-function audible alarms and set of 5 front panel LEDs
- Network-grade AC surge suppression
- Field-replaceable, hot-swappable internal UPS batteries

## Specifications

| OVERVIEW                                 |                                     |
|--|-------------------------------------|
| UPC Code                                 | 037332204134                        |
| OUTPUT                                   |                                     |
| Output Volt Amp Capacity (VA)            | 500                                 |
| Output Watt Capacity (Watts)             | 300                                 |
| Nominal Output Voltage(s) Supported      | 110V; 115V; 120V                    |
| Nominal Voltage Details                  | 120v nominal output in battery mode |
| Frequency Compatibility                  | 60 Hz                               |
| Output Voltage Regulation (Line Mode)    | -15%, +13%                          |
| Output Voltage Regulation (Battery Mode) | +/- 5%                              |
| Output Receptacles                       | (6) 5-15R                           |



|   |   |
|---|---|
| UPS Output Receptacles (Surge Suppression Only) | 6 UPS outlets, 1 surge-only outlet  |
| Load Management Receptacles                     | One switchable single-outlet 5-15R load bank  |
| Output AC Waveform (AC Mode)                    | Sine wave   |
| Output AC Waveform (Battery Mode)               | PWM sine wave   |
| <b>INPUT</b>                                    |   |
| Rated input current (Maximum Load)              | 5.6A  |
| Nominal Input Voltage(s) Supported              | 120V AC   |
| UPS Input Connection Type                       | 5-15P   |
| Input Circuit Breakers                          | 15A   |
| UPS Input Cord Length (ft.)                     | 10  |
| UPS Input Cord Length (m)                       | 3.1   |
| Recommended Electrical Service                  | 15A 120V  |
| Input Phase                                     | Single-Phase  |
| <b>BATTERY</b>                                  |   |
| Full Load Runtime (min.)                        | 3.2 min. (300w)   |
| Half Load Runtime (min.)                        | 14.6 min. (150w)  |
| DC System Voltage (VDC)                         | 12  |
| Battery Recharge Rate (Included Batteries)      | Less than 4 hours from 10% to 90%   |
| Internal UPS Replacement Battery Cartridge      | &nbsp;<a class="productLink" href="//www.tripplite.com/1U-UPS-Replacement-12VDC-Battery-Cartridge-Select-Tripp-Lite-SmartPro-UPS~RBC62-1U">RBC62-1U</a>&nbsp; |
| Battery Access                                  | Battery access door   |
| Battery Replacement Description                 | Hot-swappable, user replaceable batteries   |
| Expandable Runtime                              | No  |
| <b>VOLTAGE REGULATION</b>                       |   |
| Voltage Regulation Description                  | Automatic voltage regulation (AVR) maintains line power operation with input voltage as low as 90   |
| Undervoltage Correction                         | Input voltages between 90 and 108 are boosted by 14%  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>    |   |
| Switches  | 2 Switches control off/on power status and alarm-cancel/self-test operation   |
| Alarm Cancel Operation                          | Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status                                 |
| Audible Alarm                                   | Audible alarm indicates power-failure, overload and low-battery conditions  |
| LED Indicators                                  | 5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status  |



| <b>SURGE / NOISE SUPPRESSION</b>                              |  |
|---|--|
| UPS AC Suppression Joule Rating                               | 567  |
| UPS Dataline Suppression                                      | 1 line TEL/DSL (1 in / 1 out)                              |
| EMI / RFI AC Noise Suppression                                | Yes  |
| AC Suppression Joule Rating                                   | 567  |
| AC Suppression Response Time                                  | Instantaneous  |
| <b>PHYSICAL</b>   |  |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount; 2 post 19 inch rackmount         |
| Primary Form Factor   | Rackmount  |
| UPS Power Module Dimensions (hwd, in.)                        | 1.73 x 17.32 x 11.26                                       |
| UPS Power Module Dimensions (hwd, cm)                         | 4.39 x 43.99 x 28.60                                       |
| Rack Height (U Spaces)  | 1  |
| Minimum Required Rack Depth (inches)                          | 14.26  |
| Minimum Required Rack Depth (cm)                              | 36.22  |
| UPS Power Module Weight (lbs.)                                | 17.6   |
| UPS Power Module Weight (kg)                                  | 7.98   |
| Shipping Dimensions (hwd / in.)                               | 15.400 x 4.800 x 22.100                                    |
| Shipping Dimensions (hwd / cm)                                | 39.12 x 12.19 x 56.13                                      |
| Shipping Weight (lbs.)  | 20.9000  |
| Shipping Weight (kg)  | 9.48   |
| UPS Housing Material  | Steel  |
| Primary UPS Height (mm)                                       | 44   |
| Primary UPS Width (mm)  | 440  |
| Primary UPS Depth (mm)  | 286  |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius  |
| Storage Temperature Range                                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity   | 0 to 95%, non-condensing                                   |
| AC Mode BTU / Hr. (Full Load)                                 | 44   |
| Battery Mode BTU / Hr. (Full Load)                            | 360  |
| AC Mode Efficiency Rating (100% Load)                         | 94%  |



| <b>COMMUNICATIONS</b>                                       |   |
|---|---|
| Communications Interface                                    | USB (HID enabled); DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface   |
| Network Management Cards                                    | SNMPWEBCARD; TLNETCARD; &nbsp;<a class="productLink" href="//www.tripplite.com/Web-Management-Accessory-Card~WEBCARDLX">WEBCARDLX</a>&nbsp;   |
| Network Monitoring Port Description                         | Supports detailed monitoring of UPS and site power conditions   |
| PowerAlert Software   | For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a>  |
| Communications Cable  | USB and DB9 cabling included  |
| WatchDog Compatibility                                      | Supports Watchdog application, OS and hard-reboot restart options for remote applications   |
| Network UPS Tools Compatibility                             | NUT compatible. See the full list of Tripp Lite NUT compatible UPS systems at <a href="http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp+Lite">http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp Lite</a> |
| <b>LINE / BATTERY TRANSFER</b>                              |   |
| Transfer Time   | 2-4 milliseconds  |
| Low Voltage Transfer to Battery Power (Setpoint)            | 90  |
| High Voltage Transfer to Battery Power (Setpoint)           | 136   |
| <b>SPECIAL FEATURES</b>                                     |   |
| Grounding Lug   | Back panel grounding lug  |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported  |
| High Availability UPS Features                              | Hot swappable batteries   |
| <b>CERTIFICATIONS</b>                                       |   |
| UPS Certifications  | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI); TAA Compliant   |
| <b>WARRANTY</b>   |   |
| Product Warranty Period (Worldwide)                         | 2-year limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$250,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;   |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>