



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Solder Wire Sn62/Pb36/Ag2 No-Clean with 2.2% Flux Core 2oz Spool

Product Highlights

No-Clean Water-Washable Synthetic Flux Core

The clear, non-corrosive, non-conductive residue is meant to be left on the board. Residues that do remain are water soluble if you want to remove them. Clean with hot water at 60°C (140°F) minimum.

2.2% flux core

Halogen content: None

Specifications

| | |
|----------------------|-----------------------------------|
| Alloy: | Sn62/Pb36/Ag2 |
| Wire Diameter: | 0.020" (0.5mm) |
| Flux Type: | No-Clean Water-Washable Synthetic |
| Flux Classification: | ROL0 |
| Melting Point: | 179°C (354°F) |
| Packaging: | 2oz spool |

Test Results

| Test J-STD-004 or other requirements as stated | Test Requirement | Result |
|--|--|--|
| Copper Mirror | IPC-TM-650: 2.3.32 | L: No breakthrough |
| Corrosion | IPC-TM-650: 2.6.15 | L: No corrosion |
| Quantitative Halides | IPC-TM-650: 2.3.28.1 | L: <0.5% |
| Electrochemical Migration | IPC-TM-650: 2.6.14.1 | L: <1 decade drop (No-clean) |
| Surface Insulation Resistance 85°C, 85% RH @ 168 Hours | IPC-TM-650: 2.6.3.7 | L: ≥100MΩ (No-clean) |
| Visual | IPC-TM-650: 3.4.2.5 | Clear and free from precipitation |
| Conflict Minerals Compliance | Electronic Industry Citizenship Coalition (EICC) | Compliant |
| REACH Compliance | Articles 33 and 67 of Regulation (EC) No 1907/2006 | Contains Lead (Pb) CAS# 7439-92-1 No other SVHC present |

Conforms to the following Industry Standards:

| | |
|---|-----|
| J-STD-004B, Amendment 1 (Solder Fluxes): | Yes |
| J-STD-006C, Amendments 1 & 2 (Solder Alloys and Fluxed/Non-Fluxed Solders): | Yes |
| RoHS 2 Directive 2011/65/EU: | No |

ChipQuik® Solder Wire Orderable Part Numbers:

| Flux Core | Alloy | Melting Point | Diameter | Size | Orderable Part Number | |
|---|-----------|-----------------------|----------------|---------------|-----------------------|-----------------|
| No-Clean Water-Washable Synthetic Flux Core 2.2% (Except .006" and .008" diameter wire which are 1.2%) | Sn63/Pb37 | 183°C (361°F) | .015" (0.38mm) | 100g (3.5oz) | SMDSW.015 100g | |
| | | | | 0.4 oz | SMDSW.020 .4OZ | |
| | | | .020" (0.5mm) | 1 oz | SMDSW.020 1OZ | |
| | | | | 2 oz | SMDSW.020 2OZ | |
| | | | | 4 oz | SMDSW.020 4OZ | |
| | | | | 1/2 lb | SMDSW.020 8OZ | |
| | | | | 1 lb | SMDSW.020 1LB | |
| | | | .031" (0.8mm) | 0.7 oz | SMDSW.031 .7OZ | |
| | | | | 1 oz | SMDSW.031 1OZ | |
| | 2 oz | SMDSW.031 2OZ | | | | |
| | 4 oz | SMDSW.031 4OZ | | | | |
| | 1/2 lb | SMDSW.031 8OZ | | | | |
| | 1 lb | SMDSW.031 1LB | | | | |
| | Sn60/Pb40 | 183-188°C (361-370°F) | .015" (0.38mm) | 100g (3.5oz) | SMD2SW.015 100g | |
| | | | | 0.4 oz | SMD2SW.020 .4OZ | |
| | | | .020" (0.5mm) | 1 oz | SMD2SW.020 1OZ | |
| | | | | 2 oz | SMD2SW.020 2OZ | |
| | | | | 4 oz | SMD2SW.020 4OZ | |
| | | | | 1/2 lb | SMD2SW.020 8OZ | |
| | | | | 1 lb | SMD2SW.020 1LB | |
| | | | .031" (0.8mm) | 0.7 oz | SMD2SW.031 .7OZ | |
| | | | | 1 oz | SMD2SW.031 1OZ | |
| | | | | 2 oz | SMD2SW.031 2OZ | |
| | | | | 4 oz | SMD2SW.031 4OZ | |
| | | | | 1/2 lb | SMD2SW.031 8OZ | |
| | | | | 1 lb | SMD2SW.031 1LB | |
| | | | Sn62/Pb36/Ag2 | 179°C (354°F) | .015" (0.38mm) | 100g (3.5oz) |
| 0.4 oz | | | | | | SMD3SW.020 .4OZ |
| .020" (0.5mm) | 1 oz | SMD3SW.020 1OZ | | | | |
| | 2 oz | SMD3SW.020 2OZ | | | | |
| | 4 oz | SMD3SW.020 4OZ | | | | |
| | 1/2 lb | SMD3SW.020 8OZ | | | | |
| | 1 lb | SMD3SW.020 1LB | | | | |
| .031" (0.8mm) | 0.7 oz | SMD3SW.031 .7OZ | | | | |
| | 1 oz | SMD3SW.031 1OZ | | | | |
| | 2 oz | SMD3SW.031 2OZ | | | | |
| | 4 oz | SMD3SW.031 4OZ | | | | |
| | 1/2 lb | SMD3SW.031 8OZ | | | | |
| | 1 lb | SMD3SW.031 1LB | | | | |

Continued on next page

ChipQuik® Solder Wire Orderable Part Numbers:

Continued from previous page

| Flux Core | Alloy | Melting Point | Diameter | Size | Orderable Part Number |
|---|--------------------|-----------------------|-----------------|-------------------|-----------------------|
| No-Clean Water-Washable Synthetic Flux Core 2.2% (Except .006" and .008" diameter wire which are 1.2%) | Sn96.5/Ag3.0/Cu0.5 | 217-220°C (423-428°F) | .006" (0.15mm) | 50g (1.8oz) | SMDSWLF.006 50g |
| | | | .008" (0.20mm) | 50g (1.8oz) | SMDSWLF.008 50g |
| | | | .015" (0.38mm) | 0.3 oz | SMDSWLF.015 .3OZ |
| | | | | 1 oz | SMDSWLF.015 1OZ |
| | | | | 2 oz | SMDSWLF.015 2OZ |
| | | | | 4 oz | SMDSWLF.015 4OZ |
| | | | | 1/2 lb | SMDSWLF.015 8OZ |
| | | | | 1 lb | SMDSWLF.015 1LB |
| | | | .020" (0.5mm) | 0.4 oz | SMDSWLF.020 .4OZ |
| | | | | 1 oz | SMDSWLF.020 1OZ |
| | | | | 2 oz | SMDSWLF.020 2OZ |
| | | | | 4 oz | SMDSWLF.020 4OZ |
| | | | | 1/2 lb | SMDSWLF.020 8OZ |
| | | | | 1 lb | SMDSWLF.020 1LB |
| | | | .031" (0.8mm) | 0.7 oz | SMDSWLF.031 .7OZ |
| | 1 oz | SMDSWLF.031 1OZ | | | |
| | 2 oz | SMDSWLF.031 2OZ | | | |
| | 4 oz | SMDSWLF.031 4OZ | | | |
| | 1/2 lb | SMDSWLF.031 8OZ | | | |
| | 1 lb | SMDSWLF.031 1LB | | | |
| | Sn99.3/Cu0.7 | 227°C (441°F) | .012" (0.3mm) | 100g (3.5oz) | SMD2SWLF.012 100g |
| | | | .015" (0.38mm) | 0.3 oz | SMD2SWLF.015 .3OZ |
| | | | | 1 oz | SMD2SWLF.015 1OZ |
| | | | | 2 oz | SMD2SWLF.015 2OZ |
| | | | | 4 oz | SMD2SWLF.015 4OZ |
| | | | | 1/2 lb | SMD2SWLF.015 8OZ |
| | | | | 1 lb | SMD2SWLF.015 1LB |
| .020" (0.5mm) | | | 0.4 oz | SMD2SWLF.020 .4OZ | |
| | | | 1 oz | SMD2SWLF.020 1OZ | |
| | | | 2 oz | SMD2SWLF.020 2OZ | |
| | | | 4 oz | SMD2SWLF.020 4OZ | |
| | | | 1/2 lb | SMD2SWLF.020 8OZ | |
| | | | 1 lb | SMD2SWLF.020 1LB | |
| .031" (0.8mm) | | | 0.7 oz | SMD2SWLF.031 .7OZ | |
| | | | 1 oz | SMD2SWLF.031 1OZ | |
| | 2 oz | SMD2SWLF.031 2OZ | | | |
| | 4 oz | SMD2SWLF.031 4OZ | | | |
| | 1/2 lb | SMD2SWLF.031 8OZ | | | |
| | 1 lb | SMD2SWLF.031 1LB | | | |
| Solid Wire (No Flux) | Sn42/Bi57/Ag1 | 138°C (281°F) | .030" (0.762mm) | 32 feet | SMDSWLTLP32 |
| | In100 | 157°C (315°F) | .031" (0.8mm) | 10 feet | SMDIN100 |
| | In52/Sn48 | 118°C (244°F) | .031" (0.8mm) | 10 feet | SMDIN52SN48 |
| | In97/Ag3 | 143°C (289°F) | .031" (0.8mm) | 10 feet | SMDIN97AG3 |