



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SMF Series



Agency Approvals


| AGENCY | AGENCY FILE NUMBER |
|---|--------------------|
|  | E230531 |

Maximum Ratings and Thermal Characteristics (T_A = 25°C unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---|------------------|------------|------|
| Peak Pulse Power Dissipation at T _A = 25°C by 10/1000µs (Note 1) | P _{PPM} | 200 | W |
| Thermal Resistance Junction- to-Ambient | R _{θJA} | 220 | °C/W |
| Thermal Resistance Junction- to-Lead | R _{θJL} | 100 | °C/W |
| Operating Temperature Range | T _J | -65 to 150 | °C |
| Storage Temperature Range | T _{STG} | -65 to 175 | °C |

Notes:
1. Non-repetitive current pulse, per Fig. 4 and derated above T_J (initial) = 25°C per Fig. 3.

Functional Diagram



Description

The SMF series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

SMF package is 50% smaller in footprint when compare to SMA package and delivering one of the low height profiles (1.1mm) in the industry.

Features

- 200W peak pulsepower capability at 10/1000µs waveform, repetition rate (duty cycle): 0.01 %
- Compatible with industrial standard package SOD-123FL
- Low profile: maximum height of 1.1mm.
- Low inductance, excellent clamping capability
- For surface mounted applications to optimize board space
- High temperature to reflow soldering guaranteed: 260°C/40sec
- Typical failure mode is short from over-specified voltage or current
- Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c
- IEC-61000-4-2 ESD 30kV(Air), 30kV (Contact)
- ESD protection of data lines in accordance with IEC 61000-4-2
- EFT protection of data lines in accordance with IEC 61000-4-4
- Fast response time: typically less than 1.0ns from 0 Volts to V_{BR} min
- Glass passivated junction
- Built-in strain relief
- Plastic package is flammability rated V-0 per Underwriters Laboratories
- Meet MSL level1, per J-STD-020, LF maximum peak of 260°C
- Matte tin lead-free plated
- Halogen-free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/ JEDEC J-STD-609A.01)

Applications

SMF devices are ideal for the protection of I/O interfaces, V_{CC} bus and other vulnerable circuit used in cellular phones, portable devices, business machines, power supplies and other consumer applications.

Additional Information



Datasheet



Resources



Samples


Electrical Characteristics (T_A=25°C unless otherwise noted)

| Part Number | Marking Code | Breakdown Voltage V _{BR} (Volts) @ I _T | | Test Current I _T (mA) | Reverse Stand off Voltage V _R (V) | Maximum Reverse Leakage @ V _R I _R (µA) | Maximum Peak Pulse Current I _{PP} (A) | Maximum Clamping Voltage @ I _{PP} V _C (V) | Agency Approval |
|-------------|--------------|--|--------|----------------------------------|--|--|--|---|-----------------|
| | | MIN | MAX | | | | | | |
| SMF5.0A | AE | 6.40 | 7.00 | 10 | 5.0 | 400 | 21.7 | 9.2 | X |
| SMF6.0A | AG | 6.67 | 7.37 | 10 | 6.0 | 400 | 19.4 | 10.3 | X |
| SMF6.5A | AK | 7.22 | 7.98 | 10 | 6.5 | 250 | 17.9 | 11.2 | X |
| SMF7.0A | AM | 7.78 | 8.60 | 10 | 7.0 | 100 | 16.7 | 12.0 | X |
| SMF7.5A | AP | 8.33 | 9.21 | 1 | 7.5 | 50 | 15.5 | 12.9 | X |
| SMF8.0A | AR | 8.89 | 9.83 | 1 | 8.0 | 25 | 14.7 | 13.6 | X |
| SMF8.5A | AT | 9.44 | 10.40 | 1 | 8.5 | 10 | 13.9 | 14.4 | X |
| SMF9.0A | AV | 10.00 | 11.10 | 1 | 9.0 | 5 | 13.0 | 15.4 | X |
| SMF10A | AX | 11.10 | 12.30 | 1 | 10 | 2.5 | 11.8 | 17.0 | X |
| SMF11A | AZ | 12.20 | 13.50 | 1 | 11 | 2.5 | 11.0 | 18.2 | X |
| SMF12A | BE | 13.30 | 14.70 | 1 | 12 | 2.5 | 10.1 | 19.9 | X |
| SMF13A | BG | 14.40 | 15.90 | 1 | 13 | 1.0 | 9.3 | 21.5 | X |
| SMF14A | BK | 15.60 | 17.20 | 1 | 14 | 1.0 | 8.6 | 23.2 | X |
| SMF15A | BM | 16.70 | 18.50 | 1 | 15 | 1.0 | 8.2 | 24.4 | X |
| SMF16A | BP | 17.80 | 19.70 | 1 | 16 | 1.0 | 7.7 | 26.0 | X |
| SMF17A | BR | 18.90 | 20.90 | 1 | 17 | 1.0 | 7.2 | 27.6 | X |
| SMF18A | BT | 20.00 | 22.10 | 1 | 18 | 1.0 | 6.8 | 29.2 | X |
| SMF20A | BV | 22.20 | 24.50 | 1 | 20 | 1.0 | 6.2 | 32.4 | X |
| SMF22A | BX | 24.40 | 26.90 | 1 | 22 | 1.0 | 5.6 | 35.5 | X |
| SMF24A | BZ | 26.70 | 29.50 | 1 | 24 | 1.0 | 5.1 | 38.9 | X |
| SMF26A | CE | 28.90 | 31.90 | 1 | 26 | 1.0 | 4.8 | 42.1 | X |
| SMF28A | CG | 31.10 | 34.40 | 1 | 28 | 1.0 | 4.4 | 45.4 | X |
| SMF30A | CK | 33.30 | 36.80 | 1 | 30 | 1.0 | 4.1 | 48.4 | X |
| SMF33A | CM | 36.70 | 40.60 | 1 | 33 | 1.0 | 3.8 | 53.3 | X |
| SMF36A | CP | 40.00 | 44.20 | 1 | 36 | 1.0 | 3.4 | 58.1 | X |
| SMF40A | CR | 44.40 | 49.10 | 1 | 40 | 1.0 | 3.1 | 64.5 | X |
| SMF43A | CT | 47.80 | 52.80 | 1 | 43 | 1.0 | 2.9 | 69.4 | X |
| SMF45A | CV | 50.00 | 55.30 | 1 | 45 | 1.0 | 2.8 | 72.7 | X |
| SMF48A | CX | 53.30 | 58.90 | 1 | 48 | 1.0 | 2.6 | 77.4 | X |
| SMF51A | CZ | 56.70 | 62.70 | 1 | 51 | 1.0 | 2.4 | 82.4 | X |
| SMF54A | DE | 60.00 | 66.30 | 1 | 54 | 1.0 | 2.3 | 87.1 | X |
| SMF58A | RG | 64.40 | 71.20 | 1 | 58 | 1.0 | 2.1 | 93.6 | |
| SMF60A | RK | 66.70 | 73.70 | 1 | 60 | 1.0 | 1.8 | 96.8 | |
| SMF64A | RM | 71.10 | 78.60 | 1 | 64 | 1.0 | 1.7 | 103.0 | |
| SMF70A | RP | 77.80 | 86.00 | 1 | 70 | 1.0 | 1.5 | 113.0 | |
| SMF75A | RR | 83.30 | 92.10 | 1 | 75 | 1.0 | 1.4 | 121.0 | |
| SMF78A | RT | 86.70 | 95.80 | 1 | 78 | 1.0 | 1.4 | 126.0 | |
| SMF85A | RV | 94.40 | 104.00 | 1 | 85 | 1.0 | 1.3 | 137.0 | |

Notes:

1. V_{BR} measured after I_T applied for 300µs, I_T = square wave pulse or equivalent.
2. Surge current waveform per 10/1000µs exponential wave and derated per Fig.2.
3. All terms and symbols are consistent with ANSI/IEEE C62.35.

I-V Curve Characteristics



- P_{PPM} Peak Pulse Power Dissipation** – Max power dissipation
- V_R Stand-off Voltage** – Maximum voltage that can be applied to the TVS without operation
- V_{BR} Breakdown Voltage** – Maximum voltage that flows through the TVS at a specified test current (I_T)
- V_C Clamping Voltage** – Peak voltage measured across the TVS at a specified I_{ppm} (peak impulse current)
- I_R Reverse Leakage Current** – Current measured at V_R
- V_F Forward Voltage Drop for Uni-directional**

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Figure 1 - TVS Transients Clamping Waveform





Figure 2 - Peak Pulse Power Rating Curve



continues on next page.

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted) (Continued)

Figure 3 - Peak Pulse Power Derating Curve




Figure 4 - Pulse Waveform - 10/1000 μS




Figure 5 - Forward Voltage




Figure 6 - Typical Junction Capacitance




Figure 7 - Peak Forward Voltage Drop vs. Peak Forward Current






Figure 8 - Maximum Non-Repetitive Forward Surge Current Uni-Directional Only



Soldering Parameters

| | | |
|--|------------------------------------|-------------------------|
| Reflow Condition | | Lead-free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 150°C |
| | - Temperature Max ($T_{s(max)}$) | 200°C |
| | - Time (min to max) (t_s) | 60 – 180 secs |
| Average ramp up rate (Liquidus Temp (T_A) to peak) | | 3°C/second max |
| $T_{s(max)}$ to T_A - Ramp-up Rate | | 3°C/second max |
| Reflow | - Temperature (T_A) (Liquidus) | 217°C |
| | - Time (min to max) (t_s) | 60 – 150 seconds |
| Peak Temperature (T_p) | | 260 ^{+0/-5} °C |
| Time within 5°C of actual peak Temperature (t_p) | | 20 – 40 seconds |
| Ramp-down Rate | | 6°C/second max |
| Time 25°C to peak Temperature (T_p) | | 8 minutes Max. |
| Do not exceed | | 260°C |




Physical Specifications

| | |
|-----------------|--|
| Case | SOD-123FL plastic over glass passivated junction |
| Polarity | Color band denotes cathode except bipolar |
| Terminal | Matte tin-plated leads, solderable per JESD22-B102 |


Environmental Specifications

| | |
|----------------------------|--------------------------|
| High Temp. Storage | JESD22-A103 |
| HTRB | JESD22-A108 |
| Temperature Cycling | JESD22-A104 |
| MSL | JEDEC-J-STD-020, Level 1 |
| H3TRB | JESD22-A101 |
| RSH | JESD22-A111 |

Dimensions - SOD-123FL Package




Mounting Pad Layout




| Dimensions | Millimeters | | Inches | |
|------------|-------------|------|--------|--------|
| | Min | Max | Min | Max |
| A | 2.50 | 2.90 | 0.0984 | 0.1142 |
| B | 3.40 | 3.90 | 0.1339 | 0.1535 |
| C | 0.70 | 1.20 | 0.0275 | 0.0472 |
| D | 1.50 | 2.00 | 0.0591 | 0.0787 |
| E | 0.35 | 0.90 | 0.0138 | 0.0354 |
| F | 0.05 | 0.26 | 0.0020 | 0.0102 |
| G | 0.00 | 0.10 | 0.000 | 0.0039 |
| H | 0.95 | 1.10 | 0.0374 | 0.0433 |

Part Numbering System



Part Marking System



Packaging Options

| Part number | Component Package | Quantity | Packaging Option | Packaging Specification |
|-------------|-------------------|----------|---------------------------------|-------------------------|
| SMFXXX | SOD-123FL | 3000 | Tape & Reel – 8mm tape/7" reel | EIA RS-481 |
| SMFXXX-T13 | SOD-123FL | 10000 | Tape & Reel – 8mm tape/13" reel | EIA RS-481 |

Tape and Reel Specification

