



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Features

- RoHS compliant\*
- Surface Mount SMC package
- Standoff Voltage: 5.0 to 170 volts
- Power Dissipation: 3000 watts

## Applications

- IEC 61000-4-2 ESD (Min. Level 4)
- IEC 61000-4-4 EFT
- IEC 61000-4-5 Surge

# SMLJ Transient Voltage Suppressor Diode Series

## General Information

The markets of portable communications, computing and video equipment are challenging the semiconductor industry to develop increasingly smaller electronic components.

Bourns offers Transient Voltage Suppressor Diodes for surge and ESD protection applications, in compact chip package DO-214AB (SMC) size format. The Transient Voltage Suppressor series offers a choice of Working Peak Reverse Voltage from 5 V up to 170 V and Breakdown Voltage up to 200 V. Typical fast response times are less than 1.0 ps for unidirectional devices and less than 5.0 ps for bidirectional devices from 0 V to Minimum Breakdown Voltage.

Bourns® Chip Diodes conform to JEDEC standards, are easy to handle with standard pick and place equipment and the flat configuration minimizes roll away.

## Electrical Characteristics (@ T<sub>A</sub> = 25 °C Unless Otherwise Noted)

| Parameter  | Symbol             | Value       | Unit  |
|--|--------------------|-------------|-------|
| Minimum Peak Pulse Power Dissipation (T <sub>P</sub> = 1 ms) (Note 1,2)  | P <sub>PK</sub>    | 3000        | Watts |
| Peak Forward Surge Current<br>8.3 ms Single Half Sine Wave Superimposed on Rated Load<br>(JEDEC Method) (Note 3) | I <sub>FSM</sub>   | 300         | Amps  |
| Steady State Power Dissipation @ T <sub>L</sub> = 75 °C  | P <sub>M(AV)</sub> | 5.0         | Watts |
| Maximum Instantaneous Forward Voltage @ I <sub>PP</sub> = 100 A<br>(For Unidirectional Units Only)               | V <sub>F</sub>     | 3.5<br>5.0  | Volts |
| Operating Temperature Range  | T <sub>J</sub>     | -55 to +150 | °C    |
| Storage Temperature Range  | T <sub>STG</sub>   | -55 to +150 | °C    |

1. Non-repetitive current pulse, per Pulse Waveform graph and derated above T<sub>A</sub> = 25 °C per Pulse Derating Curve.
2. Thermal Resistance Junction to Lead.
3. 8.3 ms Single Sine Wave duty cycle = 4 pulses maximum per minute (unidirectional units only).

# BOURNS®

### Asia-Pacific:

Tel: +886-2 2562-4117  
Email: asiacus@bourns.com

### Europe:

Tel: +36 88 520 390  
Email: eurocus@bourns.com

### The Americas:

Tel: +1-951 781-5500  
Email: americus@bourns.com  
[www.bourns.com](http://www.bourns.com)

## How to Order

**SMLJ 5.0 CA - H**

Package \_\_\_\_\_  
SMLJ = SMC/DO-214AB

Working Peak Reverse Voltage \_\_\_\_\_  
5.0 = 5.0 V<sub>RWM</sub> (Volts)

Suffix \_\_\_\_\_  
A = 5 % Tolerance Unidirectional Device  
CA = 5 % Tolerance Bidirectional Device

Reel \_\_\_\_\_  
(blank) = 13 inch reel  
-H = 7 inch reel

\*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

# SMLJ Transient Voltage Suppressor Diode Series

## Electrical Characteristics (@ T<sub>A</sub> = 25 °C Unless Otherwise Noted)

| Unidirectional Device |              | Bidirectional Device |              | Breakdown Voltage V <sub>BR</sub> (Volts) |      |                       | Working Peak Reverse Voltage | Maximum Reverse Leakage @ V <sub>RWM</sub> | Maximum Reverse Voltage @ I <sub>RSM</sub> | Maximum Reverse Surge Current |
|-----------------------|--------------|----------------------|--------------|---|------|-----------------------|------------------------------|--|--|-------------------------------|
| Part Number           | Part Marking | Part Number          | Part Marking | Min.                                      | Max. | @ I <sub>T</sub> (mA) | V <sub>RWM</sub> (Volts)     | I <sub>R</sub> (μA)                        | V <sub>RSM</sub> (Volts)                   | I <sub>RSM</sub> (Amps)       |
| SMLJ5.0A              | HDE          | SMLJ5.0CA            | IDE          | 6.40                                      | 7.00 | 10                    | 5                            | 1000                                       | 9.2  | 326.00                        |
| SMLJ6.0A              | HDG          | SMLJ6.0CA            | IDG          | 6.67                                      | 7.37 | 10                    | 6                            | 1000                                       | 10.3                                       | 291.30                        |
| SMLJ6.5A              | HDK          | SMLJ6.5CA            | IDK          | 7.22                                      | 7.98 | 10                    | 6.5                          | 500  | 11.2                                       | 267.90                        |
| SMLJ7.0A              | HDM          | SMLJ7.0CA            | IDM          | 7.78                                      | 8.60 | 10                    | 7                            | 200  | 12   | 250.00                        |
| SMLJ7.5A              | HDP          | SMLJ7.5CA            | IDP          | 8.33                                      | 9.21 | 1                     | 7.5                          | 100  | 12.9                                       | 232.60                        |
| SMLJ8.0A              | HDR          | SMLJ8.0CA            | IDR          | 8.89                                      | 9.83 | 1                     | 8                            | 50   | 13.6                                       | 220.60                        |
| SMLJ8.5A              | HDT          | SMLJ8.5CA            | IDT          | 9.44                                      | 10.4 | 1                     | 8.5                          | 25   | 14.4                                       | 208.40                        |
| SMLJ9.0A              | HDV          | SMLJ9.0CA            | IDV          | 10.0                                      | 11.1 | 1                     | 9                            | 10   | 15.4                                       | 194.80                        |
| SMLJ10A               | HDX          | SMLJ10CA             | IDX          | 11.1                                      | 12.3 | 1                     | 10                           | 5  | 17   | 176.40                        |
| SMLJ11A               | HDZ          | SMLJ11CA             | IDZ          | 12.2                                      | 13.5 | 1                     | 11                           | 5  | 18.2                                       | 164.80                        |
| SMLJ12A               | HEE          | SMLJ12CA             | IEE          | 13.3                                      | 14.7 | 1                     | 12                           | 2  | 19.9                                       | 150.60                        |
| SMLJ13A               | HEG          | SMLJ13CA             | IEG          | 14.4                                      | 15.9 | 1                     | 13                           | 2  | 21.5                                       | 139.40                        |
| SMLJ14A               | HEK          | SMLJ14CA             | IEK          | 15.6                                      | 17.2 | 1                     | 14                           | 2  | 23.2                                       | 129.40                        |
| SMLJ15A               | HEM          | SMLJ15CA             | IEM          | 16.7                                      | 18.5 | 1                     | 15                           | 2  | 24.4                                       | 123.00                        |
| SMLJ16A               | HEP          | SMLJ16CA             | IEP          | 17.8                                      | 19.7 | 1                     | 16                           | 2  | 26   | 115.40                        |
| SMLJ17A               | HER          | SMLJ17CA             | IER          | 18.9                                      | 20.9 | 1                     | 17                           | 2  | 27.6                                       | 106.60                        |
| SMLJ18A               | HET          | SMLJ18CA             | IET          | 20.0                                      | 22.1 | 1                     | 18                           | 2  | 29.2                                       | 102.80                        |
| SMLJ20A               | HEV          | SMLJ20CA             | IEV          | 22.2                                      | 24.5 | 1                     | 20                           | 2  | 32.4                                       | 92.60                         |
| SMLJ22A               | HEX          | SMLJ22CA             | IEX          | 24.4                                      | 26.9 | 1                     | 22                           | 2  | 35.5                                       | 84.40                         |
| SMLJ24A               | HEZ          | SMLJ24CA             | IEZ          | 26.7                                      | 29.5 | 1                     | 24                           | 2  | 38.9                                       | 77.20                         |
| SMLJ26A               | HFE          | SMLJ26CA             | IFE          | 28.9                                      | 31.9 | 1                     | 26                           | 2  | 42.1                                       | 71.20                         |
| SMLJ28A               | HFG          | SMLJ28CA             | IFG          | 31.1                                      | 34.4 | 1                     | 28                           | 2  | 45.4                                       | 66.00                         |
| SMLJ30A               | HFK          | SMLJ30CA             | IFK          | 33.3                                      | 36.8 | 1                     | 30                           | 2  | 48.4                                       | 62.00                         |
| SMLJ33A               | HFM          | SMLJ33CA             | IFM          | 36.7                                      | 40.6 | 1                     | 33                           | 2  | 53.3                                       | 56.20                         |
| SMLJ36A               | HFP          | SMLJ36CA             | IFP          | 40  | 44.2 | 1                     | 36                           | 2  | 58.1                                       | 51.60                         |
| SMLJ40A               | HFR          | SMLJ40CA             | IFR          | 44.4                                      | 49.1 | 1                     | 40                           | 2  | 64.5                                       | 46.40                         |
| SMLJ43A               | HFT          | SMLJ43CA             | IFT          | 47.8                                      | 52.8 | 1                     | 43                           | 2  | 69.4                                       | 43.20                         |
| SMLJ45A               | HFV          | SMLJ45CA             | IFV          | 50  | 55.3 | 1                     | 45                           | 2  | 72.7                                       | 41.20                         |
| SMLJ48A               | HFX          | SMLJ48CA             | IFX          | 53.3                                      | 58.9 | 1                     | 48                           | 2  | 77.4                                       | 38.80                         |
| SMLJ51A               | HFZ          | SMLJ51CA             | IFZ          | 56.7                                      | 62.7 | 1                     | 51                           | 2  | 82.4                                       | 36.40                         |
| SMLJ54A               | HGE          | SMLJ54CA             | IGE          | 60  | 66.3 | 1                     | 54                           | 2  | 87.1                                       | 34.40                         |
| SMLJ58A               | HGG          | SMLJ58CA             | IGG          | 64.4                                      | 71.2 | 1                     | 58                           | 2  | 93.6                                       | 32.00                         |
| SMLJ60A               | HGK          | SMLJ60CA             | IGK          | 66.7                                      | 73.7 | 1                     | 60                           | 2  | 96.8                                       | 31.00                         |
| SMLJ64A               | HGM          | SMLJ64CA             | IGM          | 71.1                                      | 78.6 | 1                     | 64                           | 2  | 103  | 29.20                         |
| SMLJ70A               | HGP          | SMLJ70CA             | IGP          | 77.8                                      | 86.0 | 1                     | 70                           | 2  | 113  | 26.60                         |
| SMLJ75A               | HGR          | SMLJ75CA             | IGR          | 83.3                                      | 92.1 | 1                     | 75                           | 2  | 121  | 24.80                         |
| SMLJ78A               | HGT          | SMLJ78CA             | IGT          | 86.7                                      | 95.8 | 1                     | 78                           | 2  | 126  | 22.80                         |
| SMLJ85A               | HGV          | SMLJ85CA             | IGV          | 94.4                                      | 104  | 1                     | 85                           | 2  | 137  | 20.80                         |
| SMLJ90A               | HGX          | SMLJ90CA             | IGX          | 100                                       | 111  | 1                     | 90                           | 2  | 146  | 20.60                         |
| SMLJ100A              | HGZ          | SMLJ100CA            | IGZ          | 111                                       | 123  | 1                     | 100                          | 2  | 162  | 18.60                         |
| SMLJ110A              | HHE          | SMLJ110CA            | IHE          | 122                                       | 135  | 1                     | 110                          | 2  | 177  | 16.80                         |
| SMLJ120A              | HHG          | SMLJ120CA            | IHG          | 133                                       | 147  | 1                     | 120                          | 2  | 193  | 15.60                         |
| SMLJ130A              | HHH          | SMLJ130CA            | IHH          | 144                                       | 159  | 1                     | 130                          | 2  | 209  | 14.40                         |
| SMLJ150A              | HHM          | SMLJ150CA            | IHM          | 167                                       | 185  | 1                     | 150                          | 2  | 243  | 12.40                         |
| SMLJ160A              | HHP          | SMLJ160CA            | IHP          | 178                                       | 197  | 1                     | 160                          | 2  | 259  | 11.60                         |
| SMLJ170A              | HHR          | SMLJ170CA            | IHR          | 189                                       | 209  | 1                     | 170                          | 2  | 275  | 11.00                         |

### Notes:

- Suffix 'A' denotes a 5 % tolerance unidirectional device.
- Suffix 'CA' denotes a 5 % tolerance bidirectional device.
- For bidirectional devices with a V<sub>R</sub> of 10 volts or less, the I<sub>R</sub> limit is double.


Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

# SMLJ Transient Voltage Suppressor Diode Series

**BOURNS®**


## Product Dimensions



| Dimension | SMC (DO-214AB)                        |
|-----------|---------------------------------------|
| A         | $\frac{6.60 - 7.11}{(0.260 - 0.280)}$ |
| B         | $\frac{5.59 - 6.22}{(0.220 - 0.245)}$ |
| C         | $\frac{2.90 - 3.20}{(0.114 - 0.126)}$ |
| D         | $\frac{0.15 - 0.31}{(0.006 - 0.112)}$ |
| E         | $\frac{7.75 - 8.13}{(0.305 - 0.320)}$ |
| F         | $\frac{0.05 - 0.20}{(0.002 - 0.008)}$ |
| G         | $\frac{2.00 - 2.62}{(0.079 - 0.103)}$ |
| H         | $\frac{0.76 - 1.52}{(0.030 - 0.060)}$ |

DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

## Recommended Footprint



| Dimension | SMC (DO-214AB)         |
|-----------|------------------------|
| a (Max.)  | $\frac{4.69}{(0.185)}$ |
| b (Min.)  | $\frac{3.07}{(0.121)}$ |
| c (Min.)  | $\frac{1.52}{(0.060)}$ |

DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

## Physical Specifications


Case .....Molded plastic per UL Class 94V-0  
 Polarity..... Cathode band indicates unidirectional device  
 No cathode band indicates bidirectional device

# SMLJ Transient Voltage Suppressor Diode Series




## Rating & Characteristic Curves


### Pulse Derating Curve




### Maximum Non-Repetitive Surge Current




### Pulse Waveform




### Typical Junction Capacitance



### Pulse Rating Curve



### Steady State Power Derating Curve




Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

# SMLJ Transient Voltage Suppressor Diode Series

**BOURNS®**

## Packaging Information

The product will be dispensed in tape and reel format (see diagram below).



Devices are packed in accordance with EIA standard RS-481-A and specifications shown here.

| Item                   | Symbol         | SMC (DO-214AB)                                   |                        |
|------------------------|----------------|--|------------------------|
|                        |                | 7 Inch Reel                                      | 13 Inch Reel           |
| Carrier Width          | A              | $\frac{6.0 \pm 2.0}{(0.236 - 0.079)}$            |                        |
| Carrier Length         | B              | $\frac{8.3 \pm 0.20}{(0.327 \pm 0.008)}$         |                        |
| Carrier Depth          | C              | $\frac{2.5 \pm 0.20}{(0.098 \pm 0.008)}$         |                        |
| Sprocket Hole          | d              | $\frac{1.50 \pm 0.10}{(0.059 \pm 0.004)}$        |                        |
| Reel Outside Diameter  | D              | $\frac{178}{(7.008)}$                            | $\frac{330}{(12.992)}$ |
| Reel Inner Diameter    | D <sub>1</sub> | $\frac{50.0}{(1.969)}$ MIN.                      |                        |
| Feed Hole Diameter     | D <sub>2</sub> | $\frac{13.0 +0.50/-0.20}{(0.512 +0.020/-0.008)}$ |                        |
| Sprocket Hole Position | E              | $\frac{1.75 \pm 0.10}{(0.069 \pm 0.004)}$        |                        |
| Punch Hole Position    | F              | $\frac{7.50 \pm 0.10}{(0.295 \pm 0.004)}$        |                        |
| Punch Hole Pitch       | P              | $\frac{8.00 \pm 0.10}{(0.315 \pm 0.004)}$        |                        |
| Sprocket Hole Pitch    | P <sub>0</sub> | $\frac{4.00 \pm 0.10}{(0.157 \pm 0.004)}$        |                        |
| Embossment Center      | P <sub>1</sub> | $\frac{2.00 \pm 0.10}{(0.079 \pm 0.004)}$        |                        |
| Overall Tape Thickness | T              | $\frac{0.30 \pm 0.10}{(0.012 \pm 0.004)}$        |                        |
| Tape Width             | W              | $\frac{16.00 \pm 0.30}{(0.630 \pm 0.012)}$       |                        |
| Reel Width             | W <sub>1</sub> | $\frac{22.4}{(0.882)}$ MAX.                      |                        |
| Quantity per Reel      | --             | 500  | 3,000                  |

REV. 06/16

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.