



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Surface Mount SMS69273 Antenna

North America: LTE, Cellular, PCS, AWS, MDS  
Europe: GSM 900, DCS, UMTS, UMTS 2600



## SURFACE MOUNT SMS69273 ANTENNA

The SMS69273 antenna, features broadband and omnidirectional gain performance. It is an excellent solution for wireless access points and cellular applications. As a surface mount antenna, it features an integrated anti-theft locking mechanism.

It is ideal for both indoor and outdoor applications due to its durable and weather-proof antenna radome design.

### FEATURES & BENEFITS

- Multi-band operation
- Available in various cable and connector configurations
- Wide bandwidth and omnidirectional gain performance
- Durable and weatherized radome design
- Conformance to RoHS

### APPLICATIONS

- Wireless Terminal, Point-of-Sale, Machine to Machine,
- Automatic Meter Reading and Home Security

### SPECIFICATIONS

TYPICAL ELECTRICAL SPECIFICATIONS	
Frequency	698 MHz ~ 960 MHz, 1710 MHz ~ 2700 MHz
Gain	0.8 dBi @ 698 MHz~960 MHz; 0.2 dBi @ 1700 MHz~2200 MHz; 0.2dBi @ 2500 MHz~2700 MHz
Average Efficiency	64% @ 698 MHz~960 MHz, 52% @ 1700 MHz~ 2200 MHz, 45% @ 2500 MHz~ 2700 MHz
Elevation Plane 3dB Beamwidth	60° @ 698 MHz~960 MHz, 50° @ 1700 MHz~ 2200 MHz, 40° @ 2500 MHz~ 2700 MHz
VSWR	2.0:1 Maximum
Polarization	Linear, Omnidirectional Radiation Pattern
Nominal Impedance	50 Ohms
Power, max.	3 Watts
Cable	LMR-195 or Equivalent (Length = 4572 mm +/- 113 mm)
RF Connector	TNC Male
Radome	PC, UV stabilized, Black
Material Substance Compliance	RoHS
Flame Retardancy	UL-94 V0
Operating Temperature Range	-30°C to +70°C
Storage Temperature Range	-40°C to +85°C
IP Rating	IP-67
Dimensions	87 mm (height) x 200 mm (diameter)
Antenna Weight	0.60 kg

### CABLES AND CONNECTORS

MODEL NUMBER	CABLE TYPE	CONNECTOR
SMS69273-91TNM	36" LMR195	TNC MALE

global solutions: local support™

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.(0).1628.858941  
IAS-EUSales@lairdtech.com


Asia: +86.21.5855.0827.127  
IAS-AsiaSales@lairdtech.com

www.lairdtech.com


# Surface Mount SMS69273 Antenna

North America: LTE, Cellular, PCS, AWS, MDS  
Europe: GSM 900, DCS, UMTS, UMTS 2600


## TYPICAL RADIATION PATTERNS



698-960 MHz Band



1710-2200 MHz Band



2400-2700 MHz Band

ANT-DS-SMS69273 1112

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.