



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## SmartPro 230V 1kVA 750W Medical-Grade Line-Interactive Tower UPS with 6 Outlets, Full Isolation, Expandable Runtime

MODEL NUMBER: **SMX1200XLHG**



Provides UL 60601-1 compliant, medical-grade 1kVA/750W power backup, ideal for use in patient-care vicinities. The built-in isolation transformer offers full isolation while maintaining AC surge protection in all modes.

### Description

Tripp Lite's SMX1200XLHG medical-grade UPS system provides dependable battery backup and is fully compliant with UL 60601-1 regulations when plugged into a hospital-grade outlet, making it ideal for use in patient-care vicinities. The 1kVA/750W capacity provides up to 27.5 minutes of runtime for a half load, or 11 minutes for a full load so you can work through short power failures and perform an orderly system shutdown in a prolonged blackout.

Built-in line-interactive voltage regulation corrects brownouts as low as 155V and overvoltages as high as 274V to normal 230V nominal output, without drawing battery power. The SMX1200XLHG's built-in isolation transformer with Faraday shield offers full isolation and removes common mode noise while maintaining full AC surge suppression in all modes. Cumulative leakage current of all connected equipment is less than 100 microamps.

This UPS system features six IEC320 C13 hospital-grade outlets and has a hospital-grade IEC320 C14 plug on a 15 cm (6 in.) dongle. All six outlets provide both backup protection and surge protection, rated to 340 joules.

The SMX1200XLHG also features diagnostic LEDs, as well as a USB port and a DB9 serial port that work with Tripp Lite's included PowerAlert software for safe, unattended system shutdown and file saves in the event of a prolonged power failure.

### Application Usage

This UPS contains a lead acid battery designed to be connected continuously to an AC power source, except during brief power outages. It is not intended for frequent charge/discharge cycles, such as mobile cart applications where the UPS is often disconnected from the power source. Using the SMX1200XLHG in this type of application will void the battery warranty.

### Features

**Provides Ideal UPS Backup in Healthcare Facilities**

### Highlights

- Supports a half load up to 27.5 minutes; full load up to 11 minutes
- Six IEC320 C13 hospital-grade outlets and IEC320 C14 hospital-grade plug
- Leakage current less than 100 microamps
- 340 joule surge suppression rating protects connected equipment
- Alarm mute/alarm quiet control is ideal for use around patients

### Package Includes

- SMX1200XLHG 1kVA/750W Medical-Grade Tower UPS System
- USB monitoring cable, 1.8 m (6 ft.)
- DB9 serial monitoring cable, 1.8 m (6 ft.)
- PowerAlert software
- Owner's Manual



- Compliant with UL 60601-1 standards for use in patient-care vicinities, when plugged into a hospital-grade outlet
- Built-in isolation transformer with Faraday shield offers full isolation and removes common mode noise

#### **Battery Backup and Full Surge Protection**

- 27.5 minutes runtime for half load (375W); 11 minutes for full load (750W)
- All six hospital-grade outlets provide surge protection rated to 340 joules
- EMI/RFI noise filtering ensures equipment runs smoothly without line noise interference
- Resistant to electrostatic discharge

#### **LEDs and Audible Alarms Keep You Aware of Power Status**

- Indicator lights on the front of the unit show you when the UPS is on and supplying utility power, when operating in voltage correction mode or in battery mode, relative load level and low-battery warning
- Audible alarms alert you to power failure, overload and low battery conditions; the alarm's mute/quiet mode ensures patients are not disturbed

#### **Saves Your Files, Even When You're Away**

- Works with Tripp Lite PowerAlert software (included) to enable safe, unattended system shutdown and files saves during prolonged power failures
- Connects to your computer via either the DB9 port or USB port

## **Specifications**

| <b>OVERVIEW</b>                       |                                      |
|---------------------------------------|--------------------------------------|
| UPC Code                              | 037332140425                         |
| <b>OUTPUT</b>                         |                                      |
| Output Volt Amp Capacity (VA)         | 1000                                 |
| Output Watt Capacity (Watts)          | 750                                  |
| Nominal Output Voltage(s) Supported   | 220V; 230V; 240V                     |
| Nominal Voltage Details               | 230v nominal inverter output voltage |
| Frequency Compatibility               | 50 / 60 Hz                           |
| Frequency Compatibility Details       | Automatic frequency selection        |
| Output Voltage Regulation (Line Mode) | -18%, +8%                            |
| Output Receptacles                    | (6) C13                              |
| Output AC Waveform (Battery Mode)     | PWM sine wave                        |



| <b>INPUT</b>                                 |   |
|--|---|
| Rated input current (Maximum Load)           | 5A  |
| Nominal Input Voltage(s) Supported           | 230V AC   |
| UPS Input Connection Type                    | C14 inlet   |
| UPS Input Cord Length (ft.)                  | 0.50  |
| UPS Input Cord Length (m)                    | 0.2   |
| Recommended Electrical Service               | 10A 230V  |
| Voltage Compatibility (VAC)                  | 230   |
| Input Phase                                  | Single-Phase  |
| <b>BATTERY</b>                               |   |
| Full Load Runtime (min.)                     | 11 min. (750w)  |
| Half Load Runtime (min.)                     | 27.5 min. (375w)  |
| Expandable Battery Runtime                   | Supports extended runtime with optional <a href="#">BP36V15-2U~BP36V15-2U</a> (limit 1) and <a href="#">BP36V42-3U~BP36V42-3U</a> external battery pack (multi-pack compatible)   |
| External Battery Pack Compatibility          | <a href="#">BP36V15-2U~BP36V15-2U</a> (limit 1); <a href="#">BP36V42-3U~BP36V42-3U</a> (multi-pack compatible); <a href="#">BP36V27-2US~BP36V27-2US</a> (multi-pack compatible)   |
| DC System Voltage (VDC)                      | 36  |
| Battery Recharge Rate (Included Batteries)   | Less than 4.5 hours from 10% to 90%   |
| Internal UPS Replacement Battery Cartridge   | <a href="#">RBC53</a>   |
| Battery Access                               | Battery access door allows hot swap battery replacement without powering connected equipment off  |
| Typical Battery Lifespan                     | 3-6 years, depending on usage   |
| Expandable Runtime                           | Yes   |
| <b>VOLTAGE REGULATION</b>                    |   |
| Voltage Regulation Description               | Line interactive UPS offers 2 boost levels of brownout correction and a single level of overvoltage adjustment to maintain usable, computer grade output without consuming battery power over an input voltage range of 155 to 274V AC. |
| Overvoltage Correction                       | Input voltages between 245 and 274V AC are reduced by 9%  |
| Undervoltage Correction                      | Input voltages between 183 and 199 are boosted by 10%   |
| Severe Undervoltage Correction               | Input voltages between 156 and 182 are boosted by 21%   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Switches                                     | Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions  |



|   |  |
|---|--|
| Audible Alarm   | Audible Alarm is factory muted for silent operation; Audible alarm can be restored to indicate power failure, overload conditions and Low Battery events using our Free Power Alert UPS management software. |
| LED Indicators  | 5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status   |
| <b>SURGE / NOISE SUPPRESSION</b>                              |  |
| UPS AC Suppression Joule Rating                               | 340  |
| EMI / RFI AC Noise Suppression                                | Yes  |
| AC Suppression Response Time                                  | Instantaneous  |
| <b>PHYSICAL</b>   |  |
| Installation Form Factors Supported with Optional Accessories | Wallmount (UPSWM - tower mounting kit)   |
| Primary Form Factor   | Tower  |
| UPS Power Module Dimensions (hwd, in.)                        | 12.7 x 7.5 x 9.1   |
| UPS Power Module Dimensions (hwd, cm)                         | 32.26 x 19.05 x 23.11  |
| UPS Power Module Weight (lbs.)                                | 45.5   |
| UPS Power Module Weight (kg)                                  | 20.64  |
| Shipping Dimensions (hwd / in.)                               | 18.500 x 12.200 x 13.380   |
| Shipping Dimensions (hwd / cm)                                | 46.99 x 30.99 x 33.99  |
| Shipping Weight (lbs.)  | 48.8000  |
| Shipping Weight (kg)  | 22.14  |
| Cooling Method  | UPS cooling via rear-exit fan  |
| UPS Housing Material  | PVC  |
| Primary UPS Height (mm)                                       | 323  |
| Primary UPS Width (mm)  | 191  |
| Primary UPS Depth (mm)  | 231  |
| <b>ENVIRONMENTAL</b>  |  |
| Operating Temperature Range                                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius  |
| Storage Temperature Range                                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius   |
| Relative Humidity   | 0 to 95%, non-condensing   |
| AC Mode BTU / Hr. (Full Load)                                 | 252.2  |
| Battery Mode BTU / Hr. (Full Load)                            | 252.2  |
| <b>COMMUNICATIONS</b>   |  |
| Communications Interface                                      | USB; DB9 Serial  |



| <b>LINE / BATTERY TRANSFER</b>                              |   |
|---|---|
| Transfer Time   | 2-4 milliseconds                                    |
| Low Voltage Transfer to Battery Power (Setpoint)            | 155   |
| High Voltage Transfer to Battery Power (Setpoint)           | 274   |
| <b>SPECIAL FEATURES</b>                                     |   |
| Grounding Lug   | Ground Potential Equalization Connector: POAG-S6/20 |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported                      |
| <b>CERTIFICATIONS</b>                                       |   |
| UPS Certifications  | CE; Tested to UL60601-1 (medical grade)             |
| <b>WARRANTY</b>   |   |
| Product Warranty Period (International)                     | 2-year limited warranty                             |
| Product Warranty Period (Mexico)                            | 2-year limited warranty                             |
| Product Warranty Period (Puerto Rico)                       | 2-year limited warranty                             |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>