

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







AMPROBE®

Data Sheet



No hassle warranty

No waiting.





(note: \$500 MSLP limit)

authorized to replace it, on the spot.

SOLAR 600 Solar Analyzer

Professional analyzer for testing, maintenance, troubleshooting and efficiency of solar panels. The analyzer is used in the installation of solar panels to determine the proper inverter size, optimum power output position of panels and identifies broken or worn-out cells.

- I-V Curve test for solar cell
- Maximum Solar Power (Pmax) search by auto-scan (60V, 12A)
- Maximum Voltage (Vmaxp) at Pmax
- Maximum Current (Imaxp) at Pmax
- Voltage at open circuit (Vopen)
- Current at short circuit (Ishort)
- I-V curve with cursor
- Calculation of panel efficiency (%)
- Manual single point test
- Real Time data logging
- PC Download





SOLAR 600 Solar Analyzer

Data Sheet

General Specifications

Battery Type	Rechargeable Lithium Battery, 11.1Vdc, 3400mAh	
Battery Life	400 times of linear scan from 60V to 0V and 0A to 12A	
Data Logging Memory Size	99 records	
AC Adaptor	AC 110V or 220V input DC 15V / 1~3A output	
Dimension	257(L) x 155(W) x 57(H) mm (10.12 x 6.1 x 2.24 inch)	
Weight	1160g / 40.0oz (Batteries included)	
Operation Environment	0°C to 50°C (32°F to 122°F), 85% RH	
Temperature Coefficient	0.1% of full scale / °C (<18°C or >28°C)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F), 75% RH	



SOLAR 600 Solar Analyzer

Data Sheet

Electrical Specifications

	Range	Accuracy	
DC Voltage	0.000-9.999V	±1% ± (1% of Vopen ± 0.1V)	
	10.00-60.00V		
DC Current	0.01-9.99A	±1% ± (1% of Ishort ± 9mA)	
	10.0-12.0A	$\pm 1\% \pm (1\% \text{ of Ishort } \pm 0.09A)$	
DC Current Simulation	0.01 ~ 9.999 A	± 1 % ± 9 mA	
	10 ~ 12 A	± 1 % ± 0.09A	
	If current is greater than 12A, test (Auto-Scan, Scan, or Test) can not be performed.		
Included Accessories	Soft carrying case, Users manual, AC Adaptor, RS232C (to USB Bridge) Cable, Rechargeable Lithium Battery Pack, Software CD, Software manual, Kelvin Clips (12A max, 1 pair)		



SOLAR 600 Solar Analyzer

Data Sheet



Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203

Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2010 Amprobe Test Tools. All rights reserved. 6/2010 SOLAR-600_DS Rev A