



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Product information SPIDER II 8TX PoE

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER PoE-Switches:SPIDER II 8TX PoE

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-211393-65228/en/conf/uistate>

Name	SPIDER II 8TX PoE
	
	Entry Level Industrial Ethernet Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Entry Level Industrial Ethernet Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
Port type and quantity	8 x 10/100BASE-TX, 4 x PoE according to IEEE802.3af, TP-cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity
Type	SPIDER II 8TX PoE
Order No.	942 008-001
<b>More interfaces</b>	
Power supply/signaling contact	1 plug-in terminal block, 3-pin, no signaling contact
<b>Network size - length of cable</b>	
Twisted pair (TP)	0 - 100 m
Multimode fiber (MM) 50/125 µm	n/a
Multimode fiber (MM) 62.5/125 µm	n.v.
Single mode fiber (SM) 9/125 µm	n/a
Single mode fiber (LH) 9/125 µm (long haul transceiver)	n/a
<b>Network size - cascading</b>	
Line - / star topology	Any
<b>Power requirements</b>	
Operating voltage	18 V DC - 32 V DC
Current consumption at 24 V DC	0,189 A (without PoE) / 3,12 A (with PoE)
Power consumption	max. 75 Watt
Power output in Btu (IT) h	234.2
<b>Service</b>	
Diagnostics	LEDs (power, link status, data, data rate)
<b>Redundancy</b>	
Redundancy functions	n.v.
<b>Ambient conditions</b>	
Operating temperature	-10 °C to +60 °C
Storage/transport temperature	-20 °C to +70 °C
Relative humidity (non-condensing)	10% to 95%
MTBF	479,015 hrs (Telcordia SR-332)
<b>Mechanical construction</b>	
Dimensions (W x H x D)	35 mm x 138 mm x 121 mm
Mounting	DIN Rail 35 mm
Weight	560 g
Protection class	IP 30
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	3,5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)



## Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER PoE-Switches:SPIDER II 8TX PoE

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-211393-65228/en/conf/uistate>

<b>EN 61000-4-4 fast transients (burst)</b>	2 kV power line, 4 kV data line
<b>EN 61000-4-5 surge voltage</b>	power line: 2 kV (linie/earth), 1 kV (linie/line), 2 kV data line
<b>EN 61000-4-6 conducted immunity</b>	10 V (150 kHz - 80 kHz)
<b>EMC emitted immunity</b>	
<b>FCC CFR47 Part 15</b>	FCC CFR47 Part 15 Class A
<b>EN 55022</b>	EN 55022 Class A
<b>Approvals</b>	
<b>Safety of industrial control equipment</b>	cUL 508
<b>EMV regulations for assembly in vehicles</b>	n/a
<b>Employment in vehicles</b>	E1
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	Device, terminal block, operating manual
<b>Accessories to order separately</b>	Rail power supply RPS 80 EEC or RPS 120 EEC, 19" installation frame

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.