imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Split SPL026285 Old item no.: 16010SG

LUXO

Split LED T31 Ag 206 930 CLA NA

Split is a powerful task light for large, demanding work places. It has twice the light output of our traditional task lights. Split is dimmable, and equipped with automatic shut-off in order to save energy. Edge clamp mount. Color: silver grey.

Lightsource	
Number of lamps	1
Lamp power (W)	11
Lightsource	LED
CRI and/or Color Temperature	CRI 90, 3200K
Lumen/Watt	5 5
Lumen Out	600
LLMF LED 50000h Ta25	0.70
MacAdam step	3,5
Average useful life (IEC 62717) Ta25	50000h L70B50

Termination

Optic	ASY
Plug type	N A
Cord length (ft)	6
Mounting	Edge clamp

Ballast

Wiring Accessories	Integrated PIR sensor
Type of Ballast	AC/DC = alternating current/ direct current

Body

Body color Silver grey





Electrical data	
Maximum voltage (V)	240
Maximum frequency (Hz)	6 0
Minimum frequency (Hz)	5 0
Voltage from (V)	100
Total consumption (W)	1 1
Dimensions	
Net weight (kg)	1
Arm length (in.)	31.5
Technical data	
IP classification	2 0
Optic	

•		
Light distribution	Up/Down	0/100