



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Split

**SPL026287**

Old item no.: 16010BK

**Split LED T31 BI 206 930 CLA NA**

Split is a powerful task light for large, demanding work places. It has twice the light output of our traditional task lights. Split is dimmable, and equipped with automatic shut-off in order to save energy. Edge clamp mount. Color: black.

**Lightsource**

Number of lamps	1
Lamp power (W)	11
Lightsource	LED
CRI and/or Color Temperature	CRI 90, 3200K
Lumen/Watt	5.5
Lumen Out	600
LLMF LED 50000h Ta25	0.70
MacAdam step	3.5
Average useful life (IEC 62717) Ta25	50000h L70B50

**Termination**

Optic	ASY
Plug type	NA
Cord length (ft)	6
Mounting	Edge clamp

**Ballast**

Wiring Accessories	Integrated PIR sensor
Type of Ballast	AC/DC = alternating current/ direct current

**Body**

Body color	Black
------------	-------

**Electrical data**

Maximum voltage (V)	240
Maximum frequency (Hz)	60
Minimum frequency (Hz)	50
Voltage from (V)	100
Total consumption (W)	11

**Dimensions**

Net weight (kg)	1
Arm length (in.)	31.5

**Technical data**

IP classification	20
-------------------	----

**Optic**

Light distribution Up/Down	0/100
----------------------------	-------