



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SQF-S25 630

SATA III (6.0Gb) 2.5" SSD

SQF-S25 830

SATA III (6.0Gb) 2.5" SSD



Features

- 2.5" SSD
- Interface: SATA III (6.0 Gbps)
- Supports 72 bit ECC correct per 1K Byte data
- Universal wear-leveling and bad block management hardware write protect (optional)
- Shock resistance, anti-vibration and low power consumption
- GUI management tool & software API package

Features

- Compliant with SATA III and SATA v3.0 standard
- Supports 120 bit ECC correct per 2K Byte data
- Supports Fragment Writing and Flush Manager
- Optional support for AES and voltage stabilizer
- Shock resistance, anti-vibration and low power consumption
- GUI management tool & software API package

Specifications

Connector Type	2.5" SSD
Flash Type	SLC / Ultra MLC / MLC
Capacity	SLC: 1 to 64GB Ultra MLC: 2 to 128GB MLC: 4 to 256GB
Transfer Mode	SATA III (6.0 Gbps)
Sustained R/W Performance*	SLC: up to 500/150 MB/sec MLC: up to 510/190 MB/sec
Operating Temperature	Commercial grade: 0 to +70 °C Industrial grade: -40 to +85 °C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Dimensions (mm)	100.0 x 69.9 x 7.0

* These values are for reference only; they may change according to the flash memory used.

Specifications

Connector Type	Standard 7+15-pin SATA connector
Flash Type	SLC / Ultra MLC / MLC
Capacity	SLC: 64 to 512GB Ultra MLC: 64 to 512GB MLC: 128GB to 2TB
Transfer Mode	SATA III (6.0 Gbps)
Max. Power Consumption	2A
Sustained R/W Performance*	SLC and MLC up to 540/520 MB/sec
Operating Temperature	Commercial Grade: 0 to +70 °C Industrial Grade: -40 to +85 °C
Shock Resistance	1,500 G, Peak / 0.5 ms
Vibration Resistance	20 G, Peak / 80 ~ 2000 Hz
Dimensions (mm)	100.20 x 69.85 x 7

(*) The values are for reference only; they may change according to the flash memory used.

Ordering Information

PN	Description
SQF-S25S2-8G-S9C	SQFlash 630 series 2.5" SSD, SLC, 8GB (0 ~ 70 °C)
SQF-S25S4-XG-S9C	SQFlash 630 series 2.5" SSD, SLC, 16/32/64 GB (0 ~ 70 °C)
SQF-S25S2-8G-S9E	SQFlash 630 series 2.5" SSD, SLC, 8GB (-40 ~ 85 °C)
SQF-S25S4-XG-S9E	SQFlash 630 series 2.5" SSD, SLC, 16/32/64 GB (-40 ~ 85 °C)
SQF-S25U4-XG-S9C	SQFlash 630 series 2.5" SSD, UltraMLC, 8/16/32/64/128 GB (0 ~ 70 °C)
SQF-S25U4-XG-S9E	SQFlash 630 series 2.5" SSD, UltraMLC, 8/16/32/64/128 GB (-40 ~ 85 °C)
SQF-S25M2-8G-S9C	SQFlash 630 series 2.5" SSD, MLC, 8GB (0 ~ 70 °C)
SQF-S25M4-XG-S9C	SQFlash 630 series 2.5" SSD, MLC, 16/32/64/128/256 GB (0 ~ 70 °C)
SQF-S25M2-XG-S9E	SQFlash 630 series 2.5" SSD, MLC, 8GB (-40 ~ 85 °C)
SQF-S25M4-XG-S9E	SQFlash 630 series 2.5" SSD, MLC, 16/32/64/128/256 GB (-40 ~ 85 °C)

Note: X stands for different capacities

Ordering Information

Part No.	Product Description
SQF-S25S8-x-SAC	SQFlash 830 series 2.5" SSD SLC 64/128/256/512G (0 ~ 70 °C)
SQF-S25S8-x-SAE	SQFlash 830 series 2.5" SSD SLC 64/128/256/512G (-40 ~ 85 °C)
SQF-S25U8-x-SAC	SQFlash 830 series 2.5" SSD Ultra MLC 64/128/256/512G/1T (0 ~ 70 °C)
SQF-S25U8-x-SAE	SQFlash 830 series 2.5" SSD Ultra MLC 64/128/256/512G/1T (-40 ~ 85 °C)
SQF-S25M8-x-SAC	SQFlash 830 series 2.5" SSD MLC 128/256/512G/1T/2T (0 ~ 70 °C)
SQF-S25M8-x-SAE	SQFlash 830 series 2.5" SSD MLC 128/256/512G/1T/2T (-40 ~ 85 °C)

Note: X stands for different capacities