

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 **SR5200** 

### **Features**

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- High Current Capability
- Low Forward Voltage Drop
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

## **Maximum Ratings**

Operating Temperature: -65°C to +150°C
Storage Temperature: -65°C to +150°C

MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SR5200	SR5200	200V	140V	200V

### Electrical Characteristics @ 25°C Unless Otherwise Specified


iietu itai viiai attei 1311t3 👑 23 t viiie33 viiiei wi36 3petiiieu					
Average Forward Current	$I_{F(AV)}$	5.0A	T <sub>L</sub> = 100°C		
Peak Forward Surge Current	I <sub>FSM</sub>	150A	8.3ms, half sine		
Maximum Instantaneous Forward Voltage (Note2)	V <sub>F</sub>	0.95V	I <sub>FM</sub> = 5.0A; T <sub>A</sub> = 25°C		
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	0.5mA 25mA	T <sub>A</sub> = 25°C T <sub>A</sub> = 100°C		
Typical Junction Capacitance(Note3)	CJ	400pF			

### Note:

- 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.
- 2. Pulse test: Pulse width 300 usec, Duty cycle 1%
- 3. Measured at 1 MHz and reverse voltage of 4.0 volts

## 5 Amp Schottky Barrier Rectifier 200 Volts

### DO-201AD



DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.287	.374	7.30	9.50		
В	.189	.208	4.80	5.30		
С	.048	.052	1.20	1.30		
D	1 000		25.40			


www.mccsemi.com




# SR5200

#### •


#### FIG.1-FORWARD CURRENT DERATING CURVE




# FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




### FIG.5-TYPICAL JUNCTION CAPACITANCE




## FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



#### FIG.4-TYPICAL REVERSE CHARACTERISTICS



### FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE





### **Ordering Information:**

Device	Packing	
Part Number-TP	Tape&Reel: 1.2Kpcs/Reel	
Part Number-AP	Ammo Packing: 1.2Kpcs/Ammo Box	
Part Number-BP	Bulk: 12 Kpcs/Carton	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.