

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









SolidRun's MicroSoM™:

# ClearFog | SolidRun-uSOM **ARMADA 38x**



SolidRun's leading micro System on a Module (Micro-SOM™) family is designed for embedded systems product developers and OEMs. SolidRun packed a Marvell ARMADA 38X SoC (System-on-Chip), memory subsystem, I/O and interconnected subsystems into a single ultracompact system-on-module.

The tightly packed Micro-SOM™, gives engineers a unique set of off-the-shelf design features and benefits. SolidRun's SR-uSOM-ARMADA 38X delivers faster time to market, lowers design costs, and reduces design risks.

- > Reduces TTM and Design Risks
- > Provides Complete Design Freedom
- > Extremely Small SOM (35mm×50mm)
- > Lowers Costs





## **Applications**

#### NAS (Network Attached Storage)

- > WEB Servers
- > Printers Servers
- › Network Appliances
- > Operators

## **Security**

- > VPN
- > Server Security
- > Firewall
- > Cyber
- > Encryption

### WAP (WiFi Access Point)

- › Location-Based Services
- > Enterprise/SMB Network solutions
- > Financial Services
- > Travel Services
- > Home Automation

#### Surveillance

- > Portable Proxy Recorders
- > DVR
- > NVR
- > Cameras connected to the cloud

#### **Monitoring & Control**

- > Home Automation, Smart Grid
- > Health
- > Transportation & Aviation
- > Environmental Sensors



	MicroSoM-a1	MicroSoM-a2
System on Chip	Marvell Armada 380 (88F6810)	Marvell Armada 388 (88F6828)
Соге		
Processor Core	Single core ARM Cortex A9	Dual core ARM Cortex A9
Processor Speed	Up to 1.6GHz in commercial grade Up to 1.3GHz in industrial grade	Up to 1.6GHz in commercial grade Up to 1.3GHz in industrial grade
Floating Point	$\odot$	$\bigcirc$
SIMD	Neon	Neon
L1 Cache	32KB	32KB per core
L2 Cache	1MB	1MB shared
Memory Type	16 bit DDR3L	32 bit DDR3L
ECC	Optional *	Optional
Memory Size	256MB	1GB
SPI Flash	32Mbit	32Mbit
eMMC	Optional	Optional
Connectivity		
10/100/1000 Mbps MAC	2 ports	3 ports
On MicroSoM GE PHY	1	1
SDIO	$\odot$	$\bigcirc$
I2S / SPDIF / TDM	$\odot$	$\odot$
USB 2.0	3	3
RTC Support (battery on carrier)	$\odot$	$\odot$
GPIO pins	$\odot$	$\odot$
Power Managements Signaling	Optional	Optional
JTAG	$\odot$	$\odot$
Connectivty - MUXED SERDES In	terfaces **	
Total MUXED SERDES	5	6
SATA	2xGen III	4xGen III
PCIE 2.0 x1	3xGen II	4xGen II
USB 3.0 (Requires USB 2.0 port too)	2	2
QSGMII	$\otimes$	1xQSGMII (3 MACs)
OS Support		
U-Boot	$\odot$	$\odot$
Linux Kernel 3.x	$\odot$	$\odot$
OpenWrt	$\odot$	$\odot$
Yocto	$\odot$	$\odot$
Mechanical and Electronic specif	ications	
	Commercial (0°C ~ 70°C ambient)	Commercial (0°C ~ 70°C ambient)
Temperature Range ***	Industrial (-40°C ~ 85°C ambient)	Industrial (-40°C ~ 85°C ambient)
Supply Voltage	3.3V - 5V	3.3V - 5V
I/O Voltage	3.3V, 1.8V	3.3V, 1.8V
SoM Interface	Hirose DF40 connectors 1.5mm, 3mm mating height	Hirose DF40 connectors 1.5mm, 3mm mating height
Dimensions (WxL)	35mm x 50mm	35mm x 50mm

 $<sup>\</sup>mbox{\ensuremath{\star}}$  Optional means not supported by default. Can be supported per customer's request.

sales@solid-run.com

www.solid-run.com

<sup>\*\*\*</sup> ARMADA 38x SoC maximum die temperature must be below 115°C in both Commercial and Industrial grades.





© SolidRun 2015

All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this brochure has been carefully checked and is believed to be accurate; however, no responsibilty is assumed for inaccurancies. All brand or product names are trademarks or registered trademarks of their respective owners.

SolidRun Ltd., 3 Dolev, 3rd floor, P.O. Box 75, Migdal Tefen 2495900, Israel

<sup>\*\*</sup> Refer to the SR-Armada-MicroSoM-Refence-Manual for complete table.