



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## Features

- Shielded construction
- Inductance range: 10 to 1000  $\mu$ H
- Heating current up to 2.1 A
- Dimensions: 7.3 x 7.3 x 4.5 mm
- AEC-Q200 qualified
- RoHS compliant\* and halogen free\*\*

## Applications

- Automotive systems:
  - Driver assistant
  - Entertainment
  - Information
  - Lighting
- DC/DC converters
- Power supplies


# SRR0745A Series - Shielded Power Inductors

### Electrical Specifications @ 25 °C

Bourns Part Number	Inductance @ 1 kHz / 1 V		DCR ( $\Omega$ ) Max.	I rms (A)	I sat (A)	***K-Factor
	L ( $\mu$ H)	Tol. (%)				
SRR0745A-100M	10	$\pm$ 20	0.052	2.1	2.5	112
SRR0745A-120M	12	$\pm$ 20	0.062	2.0	2.3	98
SRR0745A-150M	15	$\pm$ 20	0.075	1.9	2.1	88
SRR0745A-180M	18	$\pm$ 20	0.09	1.8	1.95	83
SRR0745A-220M	22	$\pm$ 20	0.096	1.65	1.75	72
SRR0745A-270M	27	$\pm$ 20	0.13	1.45	1.62	66
SRR0745A-330M	33	$\pm$ 20	0.15	1.35	1.45	59
SRR0745A-390M	39	$\pm$ 20	0.19	1.17	1.3	55
SRR0745A-470M	47	$\pm$ 20	0.21	1.05	1.2	50
SRR0745A-560M	56	$\pm$ 20	0.24	0.95	1.1	47
SRR0745A-680M	68	$\pm$ 20	0.3	0.86	0.96	41
SRR0745A-820M	82	$\pm$ 20	0.4	0.78	0.9	38
SRR0745A-101M	100	$\pm$ 20	0.45	0.7	0.78	34
SRR0745A-121M	120	$\pm$ 20	0.55	0.6	0.7	32
SRR0745A-151M	150	$\pm$ 20	0.76	0.48	0.58	29
SRR0745A-181M	180	$\pm$ 20	0.82	0.46	0.54	26
SRR0745A-221M	220	$\pm$ 20	0.95	0.42	0.5	23
SRR0745A-271M	270	$\pm$ 20	1.2	0.38	0.46	22
SRR0745A-331M	330	$\pm$ 20	1.5	0.34	0.4	20
SRR0745A-391M	390	$\pm$ 20	1.85	0.32	0.36	18
SRR0745A-471M	470	$\pm$ 20	2.2	0.29	0.34	16
SRR0745A-561M	560	$\pm$ 20	2.6	0.26	0.3	15
SRR0745A-681M	680	$\pm$ 20	2.8	0.24	0.28	13
SRR0745A-821M	820	$\pm$ 20	3.5	0.22	0.26	12
SRR0745A-102M	1000	$\pm$ 20	4.1	0.2	0.24	11

\*\*\*K-Factor: To calculate core flux density,  $B_p$ -p (gauss) =  $K \times L(\mu H) \times \Delta I$  (peak-to-peak ripple current, A), determine core loss from *Core Loss vs. Flux Density* plot.

### Core Loss vs. Flux Density




### General Specifications

Operating Temperature .....-40 °C to +125 °C  
 (Temperature rise included)  
 Storage Temperature .....-40 °C to +125 °C  
 Resistance to Solder Heat .....+250 °C for 10 sec.  
 Temperature Rise .....40 °C typ. at rated I rms  
 Inductance drop..... 25 % at I sat


### Materials

Core.....Ferrite  
 Wire.....Enameled copper  
 Terminal Finish.....Sn  
 Packaging..... 1000 pcs. per reel

### Product Dimensions



### Recommended Layout



\* RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

\*\* Bourns follows the prevailing definition of "halogen free" in the industry. Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.




Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.




# SRR0745A Series - Shielded Power Inductors

**BOURNS®**

## Inductance vs. IDC



## Temperature Rise vs. IDC




## How to Order

**SRR0745A - 100M**

Model \_\_\_\_\_  
Value Code (see table) \_\_\_\_\_

## Electrical Schematic




# SRR0745A Series - Shielded Power Inductors


**BOURNS®**

## Soldering Profile

Peak Temperature: 250 °C max.  
 Max. Peak Temperature -5 °C: 30 sec. max.  
 Max. Time Above 217 °C: 60-150 sec. max.



## Packaging Specifications



USER DIRECTION OF FEED →

QTY: 1000 PCS. PER REEL

DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$

REV. 02/17

Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.