

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# SmartRack 12U Low-Profile Switch-Depth-Plus Wall-Mount Rack Enclosure Cabinet

#### MODEL NUMBER: SRW12UDP











Wall-mount cabinet secures and organizes 12U of 19-inch rack equipment in network closets, classrooms and other locations with limited floor space. Houses network switches and patch panels up to 20.5 inches deep.

#### Description

The SRW12UDP SmartRack 12U Low-Profile Switch-Depth-Plus Wall-Mount Rack Enclosure Cabinet is designed to house EIA-standard 19-inch rack equipment in network wiring closets, retail locations, classrooms, back offices and other areas with limited floor space where you need equipment to be secure, organized and out of the way. Constructed from heavy-duty steel with a durable black powder-coated finish, the cabinet has a maximum load capacity of 200 pounds.

To ensure your valuable equipment stays secure, the side panels and front door lock securely to help prevent damage, tampering or theft. The front, top, bottom and removable side panels are vented, which allows air to flow freely through the cabinet toand keep equipment cool. The reversible front door can open left or right by rotating the cabinet 180° before mounting. Convenient top and bottom ports allow easy cable routing through the cabinet.

The SRW12UDP comes fully assembled and ready to mount to the wall, or use Tripp Lite's optional SRCASTER rolling caster kit to make it a mobile rack. Square and threaded mounting holes and numbered rack spaces make equipment installation easy. The vertical mounting rails adjust in 7/8-inch increments to accommodate equipment up to 20.5 inches deep, such as such as network switches and patch panels.

#### **Features**

#### Saves Valuable Workspace

 Perfect for network wiring closets, retail locations, classrooms, back offices and other areas with limited floor space where you need equipment to be secure, organized and out of the way

#### **Highlights**

- Maximum load capacity of 200
   lb.
- Locking steel cabinet vented at sides, front, top and bottom
- Flow-through ventilation keeps equipment cool
- Secures 12U of 19 in. rack equipment up to 20.5 in. deep
- Mounts to wall or rolls on floor (with optional SRCASTER)

#### **Package Includes**

- SRW12UDP SmartRack 12U
   Low-Profile Switch-Depth-Plus
   Wall-Mount Rack Enclosure
   Cabinet
- (20) M6 screws
- (20) M6 cage nuts
- (20) M6 washers
- (20) 12-24 screws
- (2) Keys
- Owner's manual



- Houses EIA-standard 19 in. rack equipment in 12U of space
- Maximum load capacity of 200 lb.

#### **Keeps Important Equipment Secure**

- Side panels and front door lock securely to help prevent damage, tampering or theft
- Vented panels allow generous airflow that keeps equipment cool
- Rotate cabinet 180° before mounting to open reversible front door left or right
- Convenient ports with removable covers allow cable routing through top and bottom

#### Easy Enclosure and Equipment Installation

- Ships fully assembled for quick installation
- Mounts to wall or rolls on floor with Tripp Lite's optional SRCASTER caster kit
- Wall-mounting holes spaced 16 in. apart for standard wall stud placement
- Vertical mounting rails adjust in 7/8 in. increments to accommodate equipment up to 20.5 in. deep, such as network switches and patch panels
- Rails support square-hole or 12-24 threaded-hole mounting
- Rack spaces numbered for easy reference

#### **Meets Payment Card Industry Standards**

 Provides physical equipment and media security required for PCI DSS (Payment Card Industry Data Security Standard) compliance

### **Specifications**

| OVERVIEW                        |                       |  |
|---------------------------------|-----------------------|--|
| UPC Code                        | 037332191472          |  |
| PHYSICAL                        |                       |  |
| Rack Height (U Spaces)          | 12                    |  |
| Maximum Device Depth (in.)      | 20.5                  |  |
| Maximum Device Depth (cm)       | 52.07                 |  |
| Minimum Device Depth (in.)      | 3                     |  |
| Minimum Device Depth (cm)       | 7.62                  |  |
| Shipping Dimensions (hwd / in.) | 29.72 x 28.75 x 26.57 |  |
| Shipping Dimensions (hwd / cm)  | 75.49 x 73.02 x 67.49 |  |
| Shipping Weight (lbs.)          | 61.70                 |  |
| Shipping Weight (kg)            | 27.99                 |  |
| Unit Dimensions (hwd / in.)     | 25.08 x 23.62 x 21.75 |  |





| Unit Dimensions (hwd / cm)             | 63.70 × 60.00 × 55.25      |
|--|----------------------------|
| Unit Weight (lbs.)                     | 58.4                       |
| Unit Weight (kg)                       | 26.49                      |
| Color                                  | Black                      |
| Weight Capacity - Stationary (lbs.)    | 200                        |
| Weight Capacity - Stationary (kg)      | 91                         |
| Cable Access Hole Measurement (inches) | 9.812 x 2.35 (l x w)       |
| Maximum Device Depth (mm)              | 521                        |
| Minimum Device Depth (mm)              | 76                         |
| SPECIAL FEATURES                       |                            |
| Grounding Lug                          | Front and Back door frames |
| CERTIFICATIONS                         |                            |
| Certifications                         | EIA-310-E                  |
| Approvals                              | RoHS                       |
|  |                            |
| WARRANTY                               |                            |
| Product Warranty Period<br>(Worldwide) | 5-year limited warranty    |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>