

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








DATE	REVISIONS	REV	ſ
11-5-97	E.C.N. #10BRDR./	Α	

	2.50[0.098]——				
<del>-</del>	7.00 MIN. [0.276]		7.00 MIN. [0.276]	<u>-</u>	ļ
<u> </u>		+		<del> </del>	<u>'</u> 2.00[0.079]
0.40[0.016]니	ANODE _		0.50[0.020]		T T



drawing number SSL—LXA228ID REV

Ø

ELECTRO-OPTICAL CHARACTERISTICS TA =25°C If =20mA

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH FORWARD VOLTAGE REVERSE VOLTAGE AXIAL INTENSITY VIEWING ANGLE EMITTED COLOR: EPOXY LENS FINISH:	5.0 RED RED (	635 (RED) 2.0 25 50 DIFFUSED	2.8	nm Vr Vr mcd 2x theta	Ir=100 uA Ir=20mA

## LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT* STEADY CURRENT POWER DISSIPATION DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP.	160 30 100 -1.2 -40 TO +85 +260	mA mA mW mW/*C °C °C 3 SEC. MAX

<sup>\$</sup>ىر10\s

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE
THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE
FAILURE, PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX INCORPORATED 29D E. HELLEN ROAD PALATINE, ILLINOIS 60067 (847) 359-2790

CONFIDENTIAL INFORMATION

THE INFORMATION CONTANED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INCOMPORATED.

EXCEPT AS SPECFICALLY AUTHORIZED IN WRING BY LUMEX INCOMPORATED, THE HOLDER OF
THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREN CONFIDENTIAL AND SHALL PROTECT
SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

 DATE:
 1-2-97
 DWN:
 CHK'D:
 APPD:

 SCALE:
 N/A

T-2.5mm AXIAL LEAD LED, RED DIFFUSED.

 DRAWING NUMBER
 REV

 PAGE 1 OF 1
 SSL-LXA228ID
 A