



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



More Possibilities for Your E26/27 with Amphenol LTW's SSL 2.3 "EZ-B"

In order to provide you a complete solution for the LED retrofit bulbs, Amphenol LTW developed the SSL 2.3 EZ-B to replace the conventional screw base. The SSL 2.3 EZ-B equips with a nut for screw thread mating style. The driver/converter board can be inserted to SSL2.3 EZ-B through automation process. It simplifies the assembly process of E26/27 bulb and eliminate labor-intensive task of soldering.

What is SSL 2.3 EZ-B?



Nut

+

Screw Base

Benefits :



PCB Insertion simplifies the assembly process

Cost-effective alternative to hand wire soldering



Cost-effective



Quick Installation



UL94-V0 Flammability Rating

Specifications :

General Specification

Connector Size	ø30.0 x 39.5mm (E26/27 Conn)
Current Rating	3A (E26/27)
Voltage Rating	500 VAC/VDC
Dielectric Withstand Voltage	2000 VAC
Durability	10 Cycles
Color	Natural White
Operating Temperature	-40 ~ +105°C
Material	UL Recognized

Mechanical Conditions and Performance

Durability	Per EIA-364-09, at rated 500±50 cycles/hour, minimum 10 cycles
------------	--

For more information, please contact:

Global: Edward Liu (Business Development Manager) | Email: edward_liu@ltw-tech.com

North America: Anson Ting (LED Market Manager) | Email: anson.ting@industrial-amphenol.com

Europe: Darren Boston (Business Development Manager EMEAR, LED Market) | Email: darren_boston@ltw-tech.com

About Amphenol LTW

Amphenol LTW has actively devoted to various outdoor and industrial applications by successfully developing high-end waterproof connectors to meet strict requirements; also has many worldwide patents and certification such as ISO 14001, ISO 9001 and NMEA 2000...etc.. Now Amphenol LTW is not merely a supplier of waterproof connectors but also a solution provider in diversified market segments.

Amphenol LTW Technology Co., Ltd | 9F No. 657-12 Jungjeng Road, Shinjuang District, New Taipei City, Taiwan
Telephone: +886-2-2908-5626 | Fax: +886-2-2902-9787 | Website : <http://www.amphenolltw.com>

