



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Wireless receiver / repeater RF RxT SW915-USB Material number: 1278205

Features/Options:

- Different operating modes
- USB-Standard Receiver Mode
- USB Gateway Mode

- Sniffer Mode
- Repeater (1-Level and 2-Level Repeater Mode)
- Virtual COM Port driver for Microsoft Windows, Linux, Apple Mac

Product image



Technical data

Standards	EN 60947-5-1; EN 61000-6-2, -6-3, EN 61000-4-2, -4-20, -4-4, -4-6; EN 301 489-1; EN 301 489-3; EN 300 220-1; EN 300 220-2
Connection	USB 2.0
Degree of protection	IP 30 to IEC/EN 60529
Receiver mode	40 sWave transmitters
Gateway mode	indefinite number of transmitters
Power supply	via USB interface
Rated operating current I_e	< 60 mA
Rated operating voltage U_e	5 VDC (USB interface)
Frequency	915 MHz (USA, Canada and Mexico)
Display	green LED: operating state, orange LED: switching conditions
Operation cycles	approx. 12000 telegrams at repetitions/h
Ambient temperature	0 °C ... +55 °C
Dimensions	70 x 23 x 9 mm (incl. transportation cap)
Note	no external antenna required
Approvals	USA: FCC: XK5-RFRXSW915; Canada: IC: 5158A-RFRXSW915; Mexico: IFT/223/UCS/DG-AUSE/6773/2017