



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




STMPS2141, STMPS2151, STMPS2161, STMPS2171

Enhanced single channel power switches

Datasheet — production data

Features

- 90 mΩ high-side MOSFET switch
- 500/1000 mA continuous current
- Thermal and short-circuit protection with overcurrent logic output
- Operating range from 2.7 to 5.5 V
- CMOS and TTL compatible enable input
- Undervoltage lockout (UVLO)
- 12 µA maximum standby supply current
- Ambient temperature range, -40 to 85 °C
- 8 kV ESD protection
- Reverse current protection
- Fault blanking
- UL recognized components (UL file number: E354278)



Description

The STMPS2141, STMPS2151, STMPS2161, STMPS2171 power distribution switches are intended for applications where heavy capacitive loads and short-circuits are likely to be encountered. These devices incorporate 90 mΩ N-channel MOSFET high-side power switches for power distribution. These switches are controlled by a logic enable input.

When the output load exceeds the current limit threshold or a short is present, the device limits the output current to a safe level by switching into a constant current mode. When continuous heavy overloads and short-circuits increase the power dissipation in the switch, causing the junction temperature to rise, a thermal protection circuit shuts the switch off to prevent damage. Recovery from a thermal shutdown is automatic once the device has cooled sufficiently. Internal circuitry ensures the switch remains off until a valid input voltage is present.

Table 1. Device summary

Order codes			Rated continuous output current (mA)	Enable
SO-8	SOT23-5L	MSOP8 ⁽¹⁾		
STMPS2141MTR	STMPS2141STR	STMPS2141TTR	500	Active low
STMPS2151MTR	STMPS2151STR	STMPS2151TTR	500	Active high
STMPS2161MTR	STMPS2161STR	STMPS2161TTR	1000	Active low
STMPS2171MTR	STMPS2171STR	STMPS2171TTR	1000	Active high

1. MSOP8 package is also known as "TSSOP8".

Contents

1	Block diagram	7
2	Pin settings	8
2.1	Pin connections	8
2.2	Pin description	8
3	Functional description	9
3.1	Fault blanking	9
3.2	Overcurrent/overtemperature protection	9
3.3	Fault conditions	9
3.4	Reversed current blocking	10
3.5	UVLO	10
4	Ambient temperature	11
5	Maximum ratings	12
5.1	Absolute maximum ratings	12
5.2	Recommended operating conditions	12
6	Electrical specifications	13
7	Detail device characteristics	16
7.1	STMPs2141, STMPs2151 additional electrical charts	16
7.1.1	Turn-on/off characteristics at $V_{OUT} = 5.0\text{ V}$	16
7.1.2	Turn-on/off characteristics at $V_{OUT} = 3.0\text{ V}$	17
7.1.3	UVLO	18
7.1.4	OC protection characteristics	18
7.1.5	Other electrical characteristics	19
7.2	STMPs2161, STMPs2171 electrical charts	22
7.2.1	Turn-on/off characteristics at $V_{OUT} = 5.0\text{ V}$	22
7.2.2	Turn-on/off characteristics at $V_{OUT} = 3.0\text{ V}$	23
7.2.3	UVLO	24
7.2.4	OC protection characteristics	24
7.2.5	Other electrical characteristics	25

8	Package mechanical data	28
9	Ordering information	35
10	Revision history	36

List of tables

Table 1.	Device summary	1
Table 2.	Pin description	8
Table 3.	Fault conditions.	9
Table 4.	SOT23-5L (191 °C/W)	11
Table 5.	MSOP8 (220 °C/W)	11
Table 6.	SO-8 (160 °C/W).	11
Table 7.	Absolute maximum ratings	12
Table 8.	Recommended operating conditions	12
Table 9.	SOT-23-5L electrical characteristics	13
Table 10.	MSO8P/SO-8 electrical characteristics.	13
Table 11.	Current limit characteristics ($V_{IN} = 5.5$ V, I_{OUT} = rated current, $T_J = 25$ °C, unless otherwise specified)	14
Table 12.	Supply current characteristics ($V_{IN} = 5.5$ V, I_{OUT} = rated current, $T_J = 25$ °C, unless otherwise specified)	14
Table 13.	Thermal characteristics ($V_{IN} = 5.5$ V, I_{OUT} = rated current, $T_J = 25$ °C, unless otherwise specified)	15
Table 14.	UVLO characteristics ($V_{IN} = 5.5$ V, I_{OUT} = rated current, $T_J = 25$ °C, unless otherwise specified)	15
Table 15.	FAULT pin characteristics ($V_{IN} = 5.5$ V, I_{OUT} = rated current, $T_J = 25$ °C, unless otherwise specified)	15
Table 16.	EN pin characteristics ($V_{IN} = 5.5$ V, I_{OUT} = rated current, $T_J = 25$ °C, unless otherwise specified)	15
Table 17.	SOT23-5L package mechanical data	28
Table 18.	SOT23-5L footprint dimensions	29
Table 19.	SO-8 mechanical data	30
Table 20.	MSOP8 package mechanical data	32
Table 21.	Reel mechanical data	34
Table 22.	Order codes	35
Table 23.	Document revision history	36


List of figures

Figure 1.	Block diagram	7
Figure 2.	SOT23-5L, SO-8 and MSOP8 pin connections	8
Figure 3.	Voltage output turn-on delay time (STMPS2141/2151, 5 V)	16
Figure 4.	Voltage output turn-off delay time (STMPS2141/2151, 5 V)	16
Figure 5.	Current output turn-on delay time (STMPS2141/2151, 5 V)	16
Figure 6.	Current output turn-off delay time (STMPS2141/2151, 5 V)	16
Figure 7.	Voltage output turn-on delay time (STMPS2141/2151, 3 V)	17
Figure 8.	Voltage output turn-off delay time (STMPS2141/2151, 3 V)	17
Figure 9.	Current output turn-on delay time (STMPS2141/2151, 3 V)	17
Figure 10.	Current output turn-off delay time (STMPS2141/2151, 3 V)	17
Figure 11.	UVLO rising (STMPS2141/2151)	18
Figure 12.	UVLO falling (STMPS2141/2151)	18
Figure 13.	OC protection at $V_{OUT} = 3.0$ V (STMPS2141/2151)	18
Figure 14.	OC protection at $V_{OUT} = 3.0$ V (STMPS2141/2151 - detail)	18
Figure 17.	I_{CC} vs. V_{IN} (enabled) (STMPS2141/2151)	19
Figure 18.	I_{CC} vs. temperature (enabled) (STMPS2141/2151)	19
Figure 15.	OC protection at $V_{OUT} = 5.0$ V (STMPS2141/2151)	19
Figure 16.	OC protection at $V_{OUT} = 5.0$ V (STMPS2141/2151 - detail)	19
Figure 19.	I_{CC} vs. V_{IN} (disabled) (STMPS2141/2151)	19
Figure 20.	I_{CC} vs. temperature (disabled) (STMPS2141/2151)	19
Figure 21.	R_{ON} vs. V_{IN} (STMPS2141/2151)	20
Figure 22.	R_{ON} vs. temperature (STMPS2141/2151)	20
Figure 23.	I_{OS} vs. temperature (STMPS2141/2151)	20
Figure 24.	Switch leakage vs. temperature (STMPS2141/2151)	20
Figure 25.	Output rise time vs. V_{IN} (STMPS2141/2151)	20
Figure 26.	Output fall time vs. V_{IN} (STMPS2141/2151)	20
Figure 27.	UVLO vs. temperature (STMPS2141/2151)	21
Figure 28.	Voltage output turn-on delay time (STMPS2161/2171, 5 V)	22
Figure 29.	Voltage output turn-off delay time (STMPS2161/2171, 5 V)	22
Figure 30.	Current output turn-on delay time (STMPS2161/2171, 5 V)	22
Figure 31.	Current output turn-off delay time (STMPS2161/2171, 5 V)	22
Figure 32.	Voltage output turn-on delay time (STMPS2161/2171, 3 V)	23
Figure 33.	Voltage output turn-off delay time (STMPS2161/2171, 3 V)	23
Figure 34.	Current output turn-on delay time (STMPS2161/2171, 3 V)	23
Figure 35.	Current output turn-off delay time (STMPS2161/2171, 3 V)	23
Figure 36.	UVLO rising (STMPS2161/2171)	24
Figure 37.	UVLO falling (STMPS2161/2171)	24
Figure 38.	OC protection at $V_{OUT} = 3.0$ V (STMPS2161/2171)	24
Figure 39.	OC protection at $V_{OUT} = 3.0$ V (STMPS2161/2171- detail)	24
Figure 42.	I_{CC} vs. V_{IN} (enabled) (STMPS2161/2171)	25
Figure 43.	I_{CC} vs. temperature (enabled) (STMPS2161/2171)	25
Figure 40.	OC protection at $V_{OUT} = 5.0$ V (STMPS2161/2171)	25
Figure 41.	OC protection at $V_{OUT} = 5.0$ V (STMPS2161/2171- detail)	25
Figure 44.	I_{CC} vs. V_{IN} (disabled) (STMPS2161/2171)	25
Figure 45.	I_{CC} vs. temperature (disabled) (STMPS2161/2171)	25
Figure 46.	R_{ON} vs. V_{IN} (STMPS2161/2171)	26
Figure 47.	R_{ON} vs. temperature (STMPS2161/2171)	26
Figure 48.	I_{OS} vs. temperature (STMPS2161/2171)	26

Figure 49.	Switch leakage vs. temperature (STMPS2161/2171)	26
Figure 50.	Output rise time vs. V_{IN} (STMPS2161/2171)	26
Figure 51.	Output fall time vs. V_{IN} (STMPS2161/2171)	26
Figure 52.	UVLO vs. temperature (STMPS2161/2171)	27
Figure 53.	SOT23-5L package outline	28
Figure 54.	SOT23-5L footprint recommendations	29
Figure 55.	SOT23-5L carrier tape	29
Figure 56.	SO-8 package outline	30
Figure 57.	SO-8 carrier tape	31
Figure 58.	MSOP8 package outline	32
Figure 59.	MSOP8 carrier tape	33
Figure 60.	Reel information	34

1 Block diagram


Figure 1. Block diagram



2 Pin settings

2.1 Pin connections

Figure 2. SOT23-5L, SO-8 and MSOP8 pin connections



2.2 Pin description

Table 2. Pin description

Pin number			Name	Function
SO-8	MSOP8	SOT23-5L		
1	1	2	GND	Ground
2	2	5	IN	2.7 - 5.5 V input
3	3	-	IN	2.7 - 5.5 V input
4	4	4	EN	Enable for power switch
5	5	3	FAULT	Open drain FAULT indicator, active low
6	6	1	OUT	Output of power switch
7	7	-	OUT	Output of power switch
8	8	-	OUT	Output of power switch

3 Functional description

3.1 Fault blanking

The STMPS devices feature a 10 ms fault blanking. Fault blanking allows current limit faults, including momentary short-circuit faults that occur when hot-swapping a capacitive load, and also ensures that no fault is issued during power-up. When a load transient causes the device to enter current limit, an internal counter starts. If the load fault persists beyond the 10 ms fault blanking timeout, the FAULT output asserts “low”. Load transient faults less than 10 ms (typ.) do not cause a FAULT output assertion. Only current limit faults are blanked. Die overtemperature faults and input voltage drops below the UVLO threshold cause an immediate fault output.

3.2 Overcurrent/overtemperature protection

In overcurrent or short-circuit condition, the switch limits the current at a value of about 120% of the rated current. If the temperature of the die goes above the limit value, the switch turns off.

3.3 Fault conditions

In power switch applications, 4 types of fault conditions are common. These fault conditions and the response of the STMPS21x1 power switches are described in [Table 3](#).

Table 3. Fault conditions

Fault	Condition	STMPS21x1 action
Short-circuit	Output shorted to GND via resistance path of $< 1 \Omega$, causing a rapid current surge.	Reduces output voltage to reduce the current. Asserts FAULT pin after a blanking period
Overcurrent	Output connected to a load that sinks current above threshold.	Reduces output voltage to reduce the current. Asserts FAULT pin after a blanking period.
Overheating	Temperature of junction exceeds 135 °C due to any reason.	Turn OFF output until temperature falls below 125 °C. Asserts FAULT pin immediately.
Undervoltage	Input voltage drops below the UVLO threshold.	Turn OFF output until input voltage rises above the UVLO threshold plus hysteresis. Asserts FAULT pin immediately.

3.4 Reversed current blocking

When the switch is OFF (disabled through the EN pin), or when the STMPS device is unpowered ($V_{IN} = 0$ V) the switch behaves as an Hi-Z at the output pin, ensuring that no reverse current will flow into the device when $V_{IN} < V_{OUT}$.

Note: *In the case where the switch is ON, and a voltage higher than V_{IN} is applied to the OUT pin, a reverse current occurs. This operating condition is not allowed.*

3.5 UVLO

When the input voltage drops below critical values, the power switch turns off to prevent improper operation due to low voltage.

4 Ambient temperature

In "Enable" operating mode, an amount of power is dissipated as heat in the power switch due to the on-resistance. The power dissipation is: $P = I^2R$.

Table 4. SOT23-5L (191 °C/W)

Part number	Max. current	Max. R_{ON} at 5 V	Power dissipation	Temperature difference (junction - ambient)	Maximum ambient temperature (at junction temperature 125 °C)
STMPS2141	0.50 A	135 mΩ	33.8 mW	6.5	118.5
STMPS2151					
STMPS2161	1.00 A	135 mΩ	135.0 mW	25.8	99.2
STMPS2171					

Table 5. MSOP8 (220 °C/W)

Part number	Max. current	Max. R_{ON} at 5 V	Power dissipation	Temperature difference (junction - ambient)	Maximum ambient temperature (at junction temperature 125 °C)
STMPS2141	0.50 A	140 mΩ	35.0 mW	7.7	117.3
STMPS2151					
STMPS2161	1.00 A	140 mΩ	140.0 mW	30.8	94.2
STMPS2171					

Table 6. SO-8 (160 °C/W)

Part number	Max. current	Max. R_{ON} at 5 V	Power dissipation	Temperature difference (junction - ambient)	Maximum ambient temperature (at junction temperature 125 °C)
STMPS2141	0.50 A	140 mΩ	35.0 mW	5.6	119.4
STMPS2151					
STMPS2161	1.00 A	140 mΩ	140.0 mW	22.4	102.6
STMPS2171					

5 Maximum ratings

Stressing the device above the rating listed in [Table 7: Absolute maximum ratings](#) may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those indicated in [Section 5.2: Recommended operating conditions](#) of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

5.1 Absolute maximum ratings

Table 7. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{IN}	Input voltage range	-0.3 – 6.0	V
V_{OUT}	Output voltage range	-0.3 – (V_{IN} + 0.3)	V
V_{IENX}	EN Input voltage range	-0.3 – 6.0	V
I_{OUT}	Continuous output current	Internally limited	–
ESD	ESD protection level	8	kV
T_J	Junction operating temperature	-40 to 125	°C
T_{STG}	Storage temperature	-55 to 150	°C
T_R	Thermal resistance (MSOP8)	220	°C/W
T_R	Thermal resistance (SOT23-5L)	191	°C/W
T_R	Thermal resistance (SO-8)	160	°C/W

5.2 Recommended operating conditions

Table 8. Recommended operating conditions

Symbol	Parameter	Value			Unit
		Min.	Typ.	Max.	
V_{IN}	Input voltage	2.7	5.0	5.5	V
V_{OUT}	Output voltage	0	5.0	5.5	V
I_{OUT} (STMPS2141 STMPS2151)	Continuous output current	0	-	500	mA
I_{OUT} (STMPS2161 STMPS2171)	Continuous output current	0	-	1000	mA

6 Electrical specifications

Table 9. SOT-23-5L electrical characteristics

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
R_{ON}	Static drain source ON state resistance SOT23-5L package load = 500 mA (STMP2141/ STMP2151) load = 1000 mA (STMP2161/ STMP2171)	$V_{IN} = 2.7 \text{ V}; T_J = 25 \text{ }^\circ\text{C};$	—	120	160	$\text{m}\Omega$
		$V_{IN} = 5.0 \text{ V}; T_J = 25 \text{ }^\circ\text{C};$	—	90	110	$\text{m}\Omega$
R_{ON}	Static drain source ON state resistance	$V_{IN} = 2.7 \text{ V};$ $-40 < T_J < 125 \text{ }^\circ\text{C}$	—	—	200	$\text{m}\Omega$
		$V_{IN} = 5.0 \text{ V};$ $-40 < T_J < 125 \text{ }^\circ\text{C}$	—	—	135	
t_r	Output rise time	$V_{IN} = 5.0 \text{ V} R_L = 10 \Omega$ $C_L = 1 \mu\text{F}$	0.05	—	2	ms

Table 10. MSO8P/SO-8 electrical characteristics

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
R_{ON}	Static drain source ON state resistance SO-8 and MSO8 package load = 500 mA (STMP2141/ STMP2151) load = 1000 mA (STMP2161/ STMP2171)	$V_{IN} = 2.7 \text{ V}; T_J = 25 \text{ }^\circ\text{C}$	—	130	170	$\text{m}\Omega$
		$V_{IN} = 5.0 \text{ V}; T_J = 25 \text{ }^\circ\text{C}$	—	110	125	$\text{m}\Omega$
R_{ON}	Static drain source ON state resistance	$V_{IN} = 2.7 \text{ V}$ $-40 < T_J < 125 \text{ }^\circ\text{C}$	—	—	200	$\text{m}\Omega$
		$V_{IN} = 5.0 \text{ V}$ $-40 < T_J < 125 \text{ }^\circ\text{C}$	—	—	140	
t_r	Output rise time	$V_{IN} = 5.0 \text{ V} R_L = 10 \Omega$ $C_L = 1 \mu\text{F}$	0.05	—	2	ms

Table 11. Current limit characteristics
 $(V_{IN} = 5.5 \text{ V}, I_{OUT} = \text{rated current}, T_J = 25^\circ\text{C}$, unless otherwise specified)

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
I_{OS} (STMPs2141 STMPs2151)	Overcurrent limiting threshold	$V_{IN} = 5.5 \text{ V}$ $V_{OUT} = 5.0 \text{ V}$	0.60	0.80	1.00	A
I_{OS} (STMPs2161 STMPs2171)	Overcurrent limiting threshold		1.10	1.50	1.90	A
I_{OS} (2141, 2151)	Short-circuit output current	$V_{IN} = 5.5 \text{ V}$, OUT connected to GND, device enabled into short-circuit	—	—	0.9	A
I_{OS} (2161, 2171)	Short-circuit output current		—	—	1.8	A

Table 12. Supply current characteristics
 $(V_{IN} = 5.5 \text{ V}, I_{OUT} = \text{rated current}, T_J = 25^\circ\text{C}$, unless otherwise specified)

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
I_{OFF}	Switch turned off	No load	—	6.0	12	μA
		No load; $-40 < T_J < 125^\circ\text{C}$	—	—	15	
I_{ON}	Switch turned on	No load	—	40	60	μA
		No load; $-40 < T_J < 125^\circ\text{C}$	—	—	70	
$I_{leakage}$	Output leakage current ⁽¹⁾	Output grounded, switch is OFF	—	—	2	μA
		Output grounded, switch is OFF; $-40 < T_J < 125^\circ\text{C}$	—	—	5	
$I_{reverse}$	Reversed leakage current	Switch is off, $V_{IN} < V_{OUT}$, output connected to 5.5 V, 25°C	—	0.5	2	μA
		Switch is off, $V_{IN} < V_{OUT}$, output connected to 5.5 V, 125°C	—	0.5	3	

1. $I_{leakage} = I_{OFF-ground} - I_{OFF}$, where $I_{OFF-ground} =$ current into V_{IN} when switch is off and output is grounded.

Table 13. Thermal characteristics(V_{IN} = 5.5 V, I_{OUT} = rated current, T_J = 25 °C, unless otherwise specified)

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
T1	Thermal shutdown threshold		—	—	145	°C
T2	Recovery from thermal shutdown		120	—	—	°C
Hysteresis	-		—	14	—	°C

Table 14. UVLO characteristics(V_{IN} = 5.5 V, I_{OUT} = rated current, T_J = 25 °C, unless otherwise specified)

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
V _{UVLO}	Undervoltage lockout threshold		2.0	—	2.5	V
Hysteresis	-		40	75	110	mV

Table 15. FAULT pin characteristics(V_{IN} = 5.5 V, I_{OUT} = rated current, T_J = 25 °C, unless otherwise specified)

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
OC blanking	FAULT assertion and de-assertion		4	8	15	ms
V _{OUT}	Output low voltage	I _{OUT} = 5 mA	—	—	0.4	V
I _{OFF}	Off current	V _{FAULT} = 2.7 V, 5.5 V (no OC condition)	—	—	1.0	µA

Table 16. EN pin characteristics(V_{IN} = 5.5 V, I_{OUT} = rated current, T_J = 25 °C, unless otherwise specified)

Symbol	Parameter	Test condition	Value			Unit
			Min.	Typ.	Max.	
V _{IH}	High level input voltage	V _{IN} = 2.7 to 5.5 V	2.0	—	—	V
V _{IL}	Low level input voltage	V _{IN} = 4.5 to 5.5 V	—	—	0.8	V
		V _{IN} = 2.7 to 4.5 V	—	—	0.4	V
I _{IN}	Input current	V _{IEN} = 0 V or V _{IN}	-0.5	—	0.5	µA
t _{ON}	Turn-ON time ⁽¹⁾	R _L = 10 Ω C _L = 100 µF	—	—	5	ms
t _{OFF}	Turn-OFF time ⁽¹⁾	R _L = 10 Ω C _L = 100 µF	—	—	10	ms

1. Not tested in production, specified by design.

7 Detail device characteristics

7.1 STMPS2141, STMPS2151 additional electrical charts

The waveforms displayed in [Section 7.1](#) are captured with the STMPS2141 device. The STMPS2151 device is expected to have the same characteristics with EN in the opposite polarity.

7.1.1 Turn-on/off characteristics at $V_{OUT} = 5.0$ V

Figure 3. Voltage output turn-on delay time (STMPS2141/2151, 5 V)




Figure 4. Voltage output turn-off delay time (STMPS2141/2151, 5 V)




Figure 5. Current output turn-on delay time (STMPS2141/2151, 5 V)





Figure 6. Current output turn-off delay time (STMPS2141/2151, 5 V)



7.1.2 Turn-on/off characteristics at $V_{OUT} = 3.0$ V

Figure 7. Voltage output turn-on delay time
(STMPs2141/2151, 3 V)




Figure 8. Voltage output turn-off delay time
(STMPs2141/2151, 3 V)




Figure 9. Current output turn-on delay time
(STMPs2141/2151, 3 V)





Figure 10. Current output turn-off delay time
(STMPs2141/2151, 3 V)



7.1.3 UVLO

Figure 11. UVLO rising (STMPS2141/2151)





Figure 12. UVLO falling (STMPS2141/2151)



7.1.4 OC protection characteristics

Figure 13. OC protection at $V_{OUT} = 3.0$ V
(STMPS2141/2151)




Figure 14. OC protection at $V_{OUT} = 3.0$ V
(STMPS2141/2151 - detail)




Figure 15. OC protection at $V_{OUT} = 5.0$ V
(STMPS2141/2151)





Figure 16. OC protection at $V_{OUT} = 5.0$ V
(STMPS2141/2151 - detail)



7.1.5 Other electrical characteristics

Figure 17. I_{CC} vs. V_{IN} (enabled)
(STMPS2141/2151)




Figure 18. I_{CC} vs. temperature (enabled)
(STMPS2141/2151)




Figure 19. I_{CC} vs. V_{IN} (disabled)
(STMPS2141/2151)




Figure 20. I_{CC} vs. temperature (disabled)
(STMPS2141/2151)











Figure 21. R_{ON} vs. V_{IN} (STMPs2141/2151)**Figure 22.** R_{ON} vs. temperature (STMPs2141/2151)**Figure 23.** I_{OS} vs. temperature (STMPs2141/2151)**Figure 24.** Switch leakage vs. temperature (STMPs2141/2151)**Figure 25.** Output rise time vs. V_{IN} (STMPs2141/2151)**Figure 26.** Output fall time vs. V_{IN} (STMPs2141/2151)

Figure 27. UVLO vs. temperature (STMPS2141/2151)

7.2 STMPS2161, STMPS2171 electrical charts

The waveforms displayed in [Section 7.2](#) are captured with the STMPS2161 device. The STMPS2171 device is expected to have the same characteristics with EN in the opposite polarity.

7.2.1 Turn-on/off characteristics at $V_{OUT} = 5.0$ V

Figure 28. Voltage output turn-on delay time (STMPS2161/2171, 5 V)




Figure 29. Voltage output turn-off delay time (STMPS2161/2171, 5 V)




Figure 30. Current output turn-on delay time (STMPS2161/2171, 5 V)





Figure 31. Current output turn-off delay time (STMPS2161/2171, 5 V)



7.2.2 Turn-on/off characteristics at $V_{OUT} = 3.0$ V

Figure 32. Voltage output turn-on delay time
(STMPS2161/2171, 3 V)




Figure 34. Current output turn-on delay time
(STMPS2161/2171, 3 V)

Figure 33. Voltage output turn-off delay time
(STMPS2161/2171, 3 V)






Figure 35. Current output turn-off delay time
(STMPS2161/2171, 3 V)



7.2.3 UVLO

Figure 36. UVLO rising (STMPS2161/2171)





Figure 37. UVLO falling (STMPS2161/2171)



7.2.4 OC protection characteristics

Figure 38. OC protection at $V_{OUT} = 3.0$ V
(STMPS2161/2171)




Figure 39. OC protection at $V_{OUT} = 3.0$ V
(STMPS2161/2171- detail)




Figure 40. OC protection at $V_{OUT} = 5.0$ V
(STMPS2161/2171)





Figure 41. OC protection at $V_{OUT} = 5.0$ V
(STMPS2161/2171- detail)



7.2.5 Other electrical characteristics

Figure 42. I_{CC} vs. V_{IN} (enabled)
(STMPS2161/2171)




Figure 43. I_{CC} vs. temperature (enabled)
(STMPS2161/2171)




Figure 44. I_{CC} vs. V_{IN} (disabled)
(STMPS2161/2171)




Figure 45. I_{CC} vs. temperature (disabled)
(STMPS2161/2171)

