



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Diodes and rectifiers



High power efficiency and density



Content



Schottky barrier diodes	2
Signal Schottky diodes.....	2
Power Schottky diodes.....	4
Silicon-carbide diodes.....	11
Ultrafast rectifiers.....	13
Ultrafast rectifiers 200 V, 300 V and 400 V.....	13
Ultrafast rectifiers 600 V.....	16
Hyperfast Tandem rectifiers 600 V	18
Ultrafast rectifiers 800 V, 1000 V and 1200 V.....	19
Automotive-grade diodes.....	20
Automotive-grade Schottky diodes.....	20
Automotive-grade ultrafast diodes.....	22
Automotive-grade ultrafast silicon-carbide diodes	24
Automotive-grade Signal Schottky diodes.....	24
Field effect rectifiers.....	25
Ordering information	26

Schottky barrier diodes

SIGNAL SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V _{RWM})	Average rectified current (I _o)	Forward voltage (V _F)	V _F measure condition (@ I _o) spec	Reverse current (I _R)	Junction capacitance (C _J)	Reverse recovery time (t _{rr})
			max (V)	max (A)	max (V)	(A)	max (mA)	max (pF)	max (ns)
10 V and 20 V									
BAT60	SOD-323	1	10	3	0.4	0.1	0.006	60	0
BAT20J	SOD-323	1	23	1	0.62	1	0.012	35	0
30 V									
BAR42	SOT-23	1	30	0.1	1	0.1	0.1	10	5
BAR43	SOT-23	1, 2	30	0.1	1	0.1	0.1	10	5
BAT42	DO-35	1	30	0.2	0.65	0.05	0.0005	15	5
BAT43	DO-35	1	30	0.2	0.45	0.015	0.0005	15	5
TMMBAT42	MiniMELF	1	30	0.2	0.65	0.05	0.0005	15	5
TMMBAT43	MiniMELF	1	30	0.2	0.45	0.015	0.0005	15	5
BAT30	SOD-523, SOT-323	1, 2	30	0.3	0.58	0.2	0.005	35	0
BAT30F3	Flip-Chip 400μ	1	30	0.3	0.545	0.2	0.006	-	0
BAT30F4	FLAT CSPS	1	30	-	0.205	0.005	0.05	-	-
40 V									
BAT54	SOD-123, SOD-323, SOD-523, SOT-23, SOT-323	1, 2	40	0.3	0.9	0.1	0.001	10	5
BAT48	SOD-123, SOD-323	1	40	0.35	0.9	0.5	0.05	40	10
BAT48RL	DO-35	1	40	0.35	0.9	0.5	0.05	40	10
TMMBAT48	MiniMELF	1	40	0.35	0.9	0.5	0.05	40	10
TMBYV10-40	MELF	1	40	1	0.55	1	0.5	400	0
60 V, 70 V and 80 V									
IN6263	DO-35	1	60	0.015	1	0.015	0.2	2.2	0.1
TMM6263	MiniMELF	1	60	0.015	1	0.015	0.2	2.2	0.1
TMBYV10-60	MELF	1	60	1	0.7	1	0.5	300	0
IN5711	DO-35	1	70	0.015	1	0.015	0.02	2	0.1
BAR18	SOT-23	1	70	0.07	0.41	0.001	0.0002	2	0.1
BAS70	SOD-323, SOD-523, SOT-23, SOT-323	1, 2	70	0.07	1	0.015	0.01	2	0

SIGNAL SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_{av})	Forward voltage (V_F)	V_r , measure condition (@ I_F) spec	Reverse current (I_R)	Junction capacitance (C_J)	Reverse recovery time (t_{rr})
			max (V)	max (A)	max (V)	(A)	max (mA)	max (pF)	max (ns)
TMBAT49	MELF	1	80	0.5	1	1	0.2	200	0
100 V									
BAR46	SOT-23	1, 2	100	0.15	0.45	0.01	0.005	20	0
BAT46	DO-35, SOD-123, SOD-323, SOT-323	1, 2	100	0.15	1	0.25	20	20	0
TMMBAT46	MiniMELF	1	100	0.15	1	0.25	20	20	0
BAT41	DO-35, SOD-123, SOD-523	1	100	0.2	1	0.2	0.1	10	0
TMMBAT41	MiniMELF	1	100	0.2	1	0.2	0.1	10	0

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T _j)
			max (V)	(A)	max (V)	(A)	max (mA)	max (A)	max (°C)
15 V									
STPS20L15	D ² PAK, TO-220AC	1	15	20	0.33	19	6	310	125
STPS40L15C	TO-220AB, TO-247	2	15	2 x 20	0.33	19	6	310	125
STPS120L15	ISOTOP	2	15	2 x 60	0.31	60	22	1200	125
20 V									
STPS0520Z	SOD-123	1	20	0.5	0.385	0.5	0.15	5.5	125
1N5817	DO-35	1	20	1	0.45	1	0.5	25	150
STPS120M	STmite	1	20	1	0.49	1	0.004	50	150
STPS120MF	STmiteFlat	1	20	1	0.49	1	0.004	50	150
STPS1L20MF	STmiteFlat	1	20	1	0.43	1	0.075	50	150
1N5822	DO-201AD	1	20	3	0.525	3	2	80	150
25 V									
STPS2L25	SMB	1	25	2	0.375	2	0.09	75	150
STPS3L25S	SMC	1	25	3	0.44	3	0.09	75	150
STPS5L25	DPAK	1	25	5	0.35	5	0.35	75	150
STPS10L25	D ² PAK, TO-220AC	1	25	10	0.35	10	0.8	200	150
STPS15L25	TO-220AC	1	25	15	0.35	15	1.3	250	150
STPS20L25C	D ² PAK, TO-220AB	2	25	2 x 10	0.35	10	0.8	220	150
30 V									
STPS0530Z	SOD-123	1	30	0.5	0.33	0.5	0.012	5.5	150
1N5818	DO-35	1	30	1	0.5	1	0.5	25	150
STPS130	SMA, SMB	1	30	1	0.46	1	0.01	45	150
STPS1L30	SMA, SMB, Stmite	1	30	1	0.3	1	0.2	75	150
STPS1L30MF	STmiteFlat	1	30	1	0.34	1	0.39	50	150
STPS2L30	SMA, SMAflat, SMBflat	1	30	2	0.375	2	0.2	75	150
STPS8L30B-TR	DPAK	1	30	8	0.4	8	1	75	150
STPS8L30DEE	PowerFLATT™ 3.3 x 3.3	1	30	8	0.39	8	1	100	150
STPS15L30C	DPAK	2	30	2 x 7.5	0.39	7.5	1	75	150
STPS15L30CDJF	PowerFLAT™ 5 x 6	2	30	2 x 7.5	0.39	7.5	1	75	150
STPS2030C	TO-220AB	2	30	2 x 10	0.4	10	1	180	150

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T _j)
			max (V)	(A)	max (V)	(A)	max (mA)	max (A)	max (°C)
STPS3030C	D ² PAK, I ² PAK, TO-220AB	2	30	2 x 15	0.4	15	1	250	150
STPS30L30C	D ² PAK, I ² PAK, TO-220AB	2	30	2 x 15	0.37	15	1.5	220	150
STPS30L30DJF	PowerFLAT™ 5 x 6	1	30	30	0.45	30	0.75	250	150
STPS4030C	TO-220AB	2	30	2 x 15	0.4	20	1	220	150
STPS41L30C	D ² PAK	2	30	2 x 20	0.38	20	1.5	220	150
STPS60L30C	TO-247	2	30	2 x 30	0.38	30	4	600	150
40 V									
STPS0540Z	SOD-123	1	40	0.5	0.4	0.5	0.04	5.5	150
1N5819	DO-35	1	40	1	0.5	1	0.5	25	150
STPS140	SMA, SMB	1	40	1	0.45	1	0.012	60	150
STPS140Z	SOD-123	1	40	1	0.51	1	0.04	5.5	150
STPS1L40	SMA, SMB	1	40	1	0.42	1	0.035	60	150
STPS1L40M	STmite	1	40	1	0.4	1	0.063	50	150
STPS2L40	SMAflat, SMB, SMBflat	1	40	2	0.34	2	0.22	75	150
STPS340	DPAK, SMBflat, SMB, SMC	1	40	3	0.57	3	0.02	75	150
STPS3L40	SMBflat, SMC	1	40	3	0.44	3	0.1	75	150
STPS5L40	DO-201AD	1	40	5	0.44	5	0.2	150	150
STPS640C	DPAK	2	40	2 x 3	0.57	3	0.1	75	150
STPS10L40C	D ² PAK, TO-220AB	2	40	2 x 5	0.46	5	0.2	150	150
45 V									
STPS3L45AF	SMAflat	1	45	3	0.51	3	0.3	75	150
STPS745	D ² PAK, TO-220AC, TO-220FPAC	1	45	7	0.57	7.5	0.1	150	175
STPS1045	TO-220AC, TO-220FPAC	1	45	10	0.6	10	0.1	180	175
STPS1045B	DPAK	1	45	10	0.57	10	0.1	75	175
STPS1045DEE	PowerFLATT™ 3.3 x 3.3	1	45	10	0.53	10	0.2	100	175
STPS1545	TO-220AC, TO-220FPAC	1	45	15	0.57	15	0.2	220	175
STPS1545C	D ² PAK, I ² PAK, TO-220AB	2	45	2 x 7.5	0.72	15	0.1	150	175
STPS15L45C	DPAK	2	45	2 x 7.5	0.63	15	1	75	150
STPS2045C	D ² PAK, TO-220AB, TO-220FPAC	2	45	2 x 10	0.72	20	0.1	180	175
STPS2045CH	IPAK	2	45	2 x 10	0.72	20	0.1	150	175
STPS20L45C	D ² PAK, TO-220AB, TO-220FPAC	2	45	2 x 10	0.5	10	0.2	180	150

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	(A)	max (V)	(A)	max (mA)	max (A)	max (°C)
STPS2545C	D ² PAK, TO-220AB	2	45	2 x 12.5	0.72	25	0.125	200	175
STPS3045C	D ² PAK, TO-220AB, TO-247, TOP3 Ins	2	45	2 x 15	0.72	30	0.2	220	175
STPS3045DJF	PowerFLAT™ 5 x 6	1	45	30	0.56	30	0.3	200	175
STPS30L45C	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC, TO-247	2	45	2 x 15	0.5	15	0.4	220	150
STPS30S45C	TO-247, TO-220AB	2	45	2 x 15	0.6	15	0.2	180	150
STPS4045C	TO-247	2	45	2 x 20	0.63	20	0.2	220	175
STPS40L45C	D ² PAK, TO-220AB, TO-247	2	45	2 x 20	0.49	20	0.6	220	150
STPS41L45C	D ² PAK	2	45	2 x 20	0.47	20	1.2	220	150
STPS5045S	D ² PAK	1	45	50	0.56	50	0.36	600	200
STPS6045C	TO-247	2	45	2 x 30	0.78	60	0.5	400	175
STPS60L45C	TO-247	2	45	2 x 30	0.72	60	1.5	220	150
STPS61L45C	TO-220AB, TO-247	2	45	2 x 30	0.51	30	1.5	500	150
STPS16045	ISOTOP	2	45	2 x 80	0.9	160	1	900	150
STPS24045	ISOTOP	2	45	2 x 120	0.87	240	2	1500	150
60 V									
STPS0560Z	SOD-123	1	60	0.5	0.5	0.5	0.05	5.5	150
STPS160	SMA, SMB	1	60	1	0.57	1	0.004	75	150
STPS1L60	D0-41, SMA, Stmite flat	1	60	1	0.54	1	0.05	40	150
STPS2L60	D0-41, SMA, SMBflat	1	60	2	0.55	2	0.1	75	150
STPS3L60	D0-15, D0-201AD, SMB, SMBflat	1	60	3	0.59	3	0.15	100	150
STPS3L60S	SMC	1	60	3	0.65	3	0.055	75	150
STPS5L60	D0-201AD, SMC, SMB	1	60	5	0.48	5	0.22	150	150
STPS660CB	DPAK	2	60	2 x 3	0.59	3	0.03	50	125
STPS10L60	TO-220AC	1	60	10	0.56	10	0.35	220	150
STPS10L60C	TO-220FPAC	2	60	2 x 5	0.52	5	0.22	180	150
STPS15L60C	DPAK	2	60	2 x 7.5	0.57	7.5	0.2	75	150
STPS20L60C	D ² PAK, TO-220AB, TO-220NL	2	60	2 x 10	0.56	10	0.35	220	150
STPS20M60	TO-220AC	1	60	20	0.585	20	0.13	400	150
STPS20M60C	D ² PAK, I ² PAK, TO-220AB	2	60	2 x 10	0.57	10	0.065	300	150
STPS20M60S	D ² PAK, I ² PAK, TO-220AB	1	60	20	0.505	20	0.125	600	150

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			(V _{RRM})	(A)	(V)	(A)	(mA)	(A)	max (°C)
STPS20SM60	TO-220AC	1	60	20	0.6	20	0.085	400	150
STPS20SM60C	TO-220AC	2	60	2 x 10	0.6	10	0.04	220	150
STPS20SM60S	D ² PAK, I ² PAK, TO-220AB	1	60	20	0.58	20	0.085	400	150
STPS3060C	TO-247	2	60	2 x 15	0.75	15	0.15	200	150
STPS30H60C	D ² PAK, TO-220AB, TO-220FPAC	2	60	2 x 15	0.57	15	0.06	230	175
STPS30L60C	D ² PAK, TO-220AB, TO-220AB narrow leads, TO-247	2	60	2 x 15	0.56	15	0.48	230	150
STPS30M60	TO-220AC, D ² PAK	1	60	30	0.52	30	0.165	450	150
STPS30M60C	TO-220AC	2	60	2 x 15	0.53	15	0.08	400	150
STPS30M60DJF	PowerFLAT™ 5 x 6	1	60	30	0.67	30	0.09	250	150
STPS30M60S	D ² PAK, I ² PAK, TO-220AB	1	60	30	0.535	30	0.165	600	150
STPS30SM60	TO-220AC	1	60	30	0.635	30	0.135	400	150
STPS30SM60C	D ² PAK, I ² PAK, TO-220AB	2	60	2 x 15	0.62	15	0.065	300	150
STPS30SM60S	D ² PAK, I ² PAK, TO-220AB	1	60	30	0.57	30	0.135	600	150
STPS40M60C	TO-220AB	2	60	2 x 20	0.535	20	0.11	220	150
STPS40SM60C	TO-220AB	2	60	2 x 20	0.575	20	0.09	400	150
STPS41L60C	D ² PAK, TO-220AB	2	60	2 x 20	0.58	20	0.6	220	150
STPS61L60C	TO-220AB, TO-247	2	60	2 x 30	0.62	30	0.8	400	150
STPS80L60C	Max247	2	60	2 x 40	0.56	40	1.8	400	150
80 V									
STPS10SM80C	TO-220FPAC	2	80	2 x 5	0.745	5	0.015	150	175
STPS20SM80C	TO-220AB, TO-220FPAC	2	80	2 x 10	0.78	20	0.025	220	175
STPS30M80C	TO-220AB	2	80	2 x 15	0.795	30	0.04	150	175
STPS30SM80C	TO-220FPAC	2	80	2 x 15	0.83	30	0.04	220	175
STPS40M80C	D ² PAK, TO-220AB	2	80	2 x 20	0.795	40	0.065	200	175
100 V									
STPS1H100	SMA, SMAflat, SMB	1	100	1	0.62	1	0.004	50	175
STPS1H100MF	STmiteFlat	1	100	1	0.62	1	0.004	50	175
STPS2H100	SMA, SMAflat, SMB, SMBflat	1	100	2	0.65	2	0.001	75	175
STPS2H100RL	DO-35	1	100	2	0.7	2	0.001	50	175
STPS3H100	SMB, SMBflat	1	100	3	0.68	3	0.001	75	175

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	(A)	max (V)	(A)	max (mA)	max (A)	max (°C)
STPS5H100	DPAK, I ² PAK	1	100	5	0.61	5	0.0035	75	175
STPS6M100DEE	PowerFLATT™ 3.3 x 3.3	1	100	6	0.64	6	0.003	100	150
STPS8H100	D ² PAK, TO-220AC, TO-220FPAC	1	100	8	0.58	8	0.0045	250	175
STPS8H100DEE	PowerFLATT™ 3.3 x 3.3	1	100	8	0.68	8	0.0045	100	175
STPS10H100C	D ² PAK, TO-220AB, TO-220FPAC, TO-220AB narrow leads	2	100	2 x 5	0.71	10	0.0035	180	175
STPS15H100C	DPAK	2	100	2 x 7.5	0.67	7.5	0.003	75	175
STPS16H100C	D ² PAK	2	100	2 x 8	0.64	8	0.0036	200	175
STPS20100	TO-220AB	2	100	2 x 10	0.95	20	0.15	200	175
STPS20H100C	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC, TO-220AB narrow leads	2	100	2 x 10	0.77	10	0.0045	250	175
STPS20M100S	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC	1	100	20	0.69	20	0.04	530	150
STPS20S100C	TO-220AB, TO-220FPAC	2	100	2 x 10	0.71	10	0.0035	180	175
STPS20SM100S	I ² PAK, TO-220AB	1	100	20	0.7	20	0.03	350	150
STPS30100ST	TO-220AB	1	100	30	0.655	30	0.175	300	150
STPS30H100C	TO-220AB, TO-220AB narrow leads, TO-247	2	100	2 x 15	0.8	15	0.005	250	175
STPS30H100DJF	PowerFLATT™ 5 x 6	1	100	30	0.71	30	0.006	250	150
STPS30M100DJF	PowerFLATT™ 5 x 6	1	100	30	0.73	30	0.1	200	150
STPS30M100S	I ² PAK, TO-220AB, TO-220FPAC	1	100	30	0.655	30	0.175	300	150
STPS30SM100S	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC	1	100	30	0.69	30	0.045	530	150
STPS40H100CW	TO-247	2	100	2 x 20	0.61	20	0.01	300	175
STPS40M100C	I ² PAK, TO-220AB	2	100	2 x 20	0.64	20	0.07	530	150
STPS40SM100C	D ² PAK, TO-220AB	2	100	2 x 20	0.665	20	0.045	530	150
STPS41H100C	D ² PAK, I ² PAK, TO-220AB	2	100	2 x 20	0.67	20	0.01	220	175
STPS60H100C	TO-220AB	2	100	2 x 30	0.72	30	0.01	300	175
STPS61H100C	TO-247	2	100	2 x 30	0.67	30	0.016	450	175
STPS80H100	ISOTOP	2	100	2 x 40	0.65	40	0.02	700	150
STPS80H100C	Max247	2	100	2 x 40	0.7	40	0.02	400	175
STPS160H100	ISOTOP	2	100	2 x 80	0.68	80	0.04	1000	150

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	(A)	max (V)	(A)	max (mA)	max (A)	max (°C)
120 V									
STPS10120C	TO-220AB	2	120	2 x 5	0.85	5	0.006	120	175
STPS20120C	DPAK, I ² PAK, TO-220AB, TO-220AB narrow leads	2	120	2 x 10	0.74	10	0.01	150	175
STPS20120D	TO-220AC	1	120	20	0.66	10	0.02	200	175
STPS20M120S	I ² PAK, TO-220AB narrow leads	1	120	20	0.57	10	0.275	240	150
STPS20SM120S	I ² PAK, TO-220AB narrow leads, TO-220FP	1	120	20	0.62	10	0.21	220	150
STPS40M120C	I ² PAK, TO-220AB, TO-220AB narrow leads	2	120	2 x 10	0.67	20	0.37	220	150
STPS30120C	TO-220AB, TO-220AB narrow leads	2	120	2 x 15	0.74	15	0.015	180	175
STPS30120DJF	PowerFLATT™ 5 x 6	1	120	30	0.75	30	0.035	200	150
STPS30L120C	I ² PAK, TO-220AB, TO-220FPAC	2	120	2 x 15	0.71	15	0.2	220	150
STPS30M120S	I ² PAK, TO-220AB narrow leads	1	120	30	0.73	30	0.345	260	150
STPS30SM120S	I ² PAK, TO-220AB narrow leads, TO-220FP	1	120	30	0.76	30	0.275	240	150
STPS40120C	TO-220AB	2	120	2 x 20	0.73	20	0.025	200	175
STPS40SM120C	I ² PAK, TO-220AB, TO-220AB narrow leads	2	120	2 x 20	0.69	20	0.275	210	150
150 V									
STPS1150	DO-35, SMA, Stmite	1	150	1	0.67	1	0.001	50	175
STPS2150	DO-15, SMA	1	150	2	0.67	2	0.0015	75	175
STPS3150	DO-201AD, SMB, SMBflat	1	150	3	0.67	3	0.002	80	175
STPS10150C	D ² PAK, TO-220AB, TO-220FPAC	2	150	2 x 5	0.75	5	0.002	120	175
STPS16150C	TO-220AB	2	150	2 x 8	0.75	8	0.003	150	175
STPS20150C	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC	2	150	2 x 10	0.75	10	0.005	180	175
STPS30150C	D ² PAK, TO-220AB, TO-220FPAC, TO-247	2	150	2 x 15	0.75	15	0.0065	220	175
STPS40150C	D ² PAK, TO-220AB, TO-247	2	150	2 x 20	0.75	20	0.008	250	175
STPS60150C	TO-220AB	2	150	2 x 30	0.76	30	0.015	270	175
STPS61150C	TO-247	2	150	2 x 30	0.67	30	0.02	500	175
STPS80150C	TO-247	2	150	2 x 40	0.74	40	0.03	500	175

POWER SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average forward current (I_F)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	(A)	max (V)	(A)	max (mA)	max (A)	max (°C)
170 V									
STPS2170AF	SMA Flat	1	170	2	0.67	2	0.028	70	175
STPS3170	SMA Flat, SMB Flat	1	170	3	0.67	3	0.04	75	175
STPS8170DEE	PowerFLAT™ 3.3 x 3.3	1	170	8	0.72	8	0.015	100	175
STPS10170C	D²PAK, DPAK	2	170	2 x 5	0.75	5	0.01	75	175
STPS1170AF	SMA Flat	1	170	1	0.67	1	0.015	45	175
STPS16170C	D²PAK, DPAK, I²PAK	2	170	2 x 8	0.75	8	0.015	150	175
STPS20170C	D²PAK, TO-220AB, TO-220FPAC	2	170	2 x 10	0.86	20	0.015	180	175
STPS30170C	D²PAK, TO-247	2	170	2 x 15	0.86	30	0.02	220	175
STPS30170DJF	PowerFLAT™ 5 x 6	1	170	30	0.79	30	0.015	200	150
STPS40170C	D²PAK, TO-220AB, TO-247	2	170	2 x 20	0.75	20	0.03	250	175
STPS60170C	TO-220AB	2	170	2 x 30	0.76	30	0.035	270	175
STPS61170C	TO-247	2	170	2 x 30	0.67	30	0.06	500	175
STPS80170C	TO-247	2	170	2 x 40	0.74	40	0.08	500	175
STPS200170TV1	ISOTOP	2	170	2 x 100	0.68	100	0.2	700	150
200 V									
STPS2200	SMB, SMBflat	1	200	2	0.64	2	0.005	180	175
STPS20200C	D²PAK, TO-220AB, TO-220AB narrow leads, TO-220FPAB	2	200	20	0.7	10	0.015	180	175
STPS60SM200C	TO-247	2	200	2 x 30	0.69	30	0.05	500	175
STPS4S200	DPAK, SMC, SMB Flat	1	200	4	0.71	4	0.025	130	175

Silicon-carbide diodes

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_{av})	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Total capacitive charge (Qc)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (Tj)
			max (V)	max (A)	max (V)	(A)	max (mA)	(nC)	max (A)	max (°C)
Low V_F 600 V SiC diodes										
STPSC406	T0-220AC, DPAK	1	600	4	1.9	4	0.05	3	14	175
STPSC606	D ² PAK, T0-220AC	1	600	6	1.7	6	0.075	6	27	175
STPSC806	D ² PAK, T0-220AC	1	600	8	1.7	8	0.1	10	30	175
STPSC1006	T0-220AC	1	600	10	1.7	10	0.15	12	40	175
STPSC1206	T0-220AC	1	600	12	1.7	12	0.15	12	50	175
STPSC2006C	T0-247	2	600	2 x 10	1.7	10	0.15	12	40	175
STPSC40065C	T0-247	2	650	2 x 20	1.7	20	0.3	42	70	175
High surge 650 V SiC diodes										
STPSC4H065	DPAK, T0-220AC, T0-220AC Ins	1	650	4	1.75	4	0.04	12.5	38	175
STPSC6H065	D ² PAK; T0-220AC; DPAK, T0-220AC Ins	1	650	6	1.75	6	0.06	18	60	175
STPSC8H065	D ² PAK, DPAK, T0-220AC, T0-220AC Ins	1	650	8	1.75	8	0.08	23.5	75	175
STPSC8H065C	DPAK; D ² PAK; T0-220AC	2	650	2 x 4	1.75	4	0.04	12.5	38	175
STPSC10H065	D ² PAK, T0-220AC, DPAK, T0-220AC Ins, Power Flat 5x6	1	650	10	1.75	10	0.10	28.5	100	175
STPSC12H065	T0-220AC, D ² PAK	1	650	12	1.75	12	0.12	36	100	175
STPSC12H065C	D ² PAK, T0-220AC	2	650	12	1.75	6	0.06	18	60	175
STPSC12065	T0-220	1	650	12	1.45	12	0.15	36	50	175
STPSC16H065C	T0-220AB, D ² PAK	2	650	16	1.75	8	0.08	23.5	75	175
STPSC8H065C	T0-220AB	2	650	8	1.75	4	0.04	12.5	38	175
STPSC20H065C	T0-220AB; T0-247; D ² PAK	2	650	10	1.75	10	0.1	28.5	100	175
STPSC20065	T0-247, T0-220AC, T0-220AC Ins	1	650	20	1.45	20	0.3	62	90	175
Dual in series High surge 650 V SiC diode										
STPSC10TH13TI	T0-220AB Ins	2	650	10	1.75	10	0.1	28.5	90	175
STPSC6TH13TI	T0-220AB Ins	2	650	6	1.75	6	0.06	18	60	175
STPSC8TH13TI	T0-220AB Ins	2	650	8	1.75	8	0.08	23.5	75	175

Silicon-carbide diodes

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_{av})	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Total capacitive charge (Qc)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (Tj)
			max (V)	max (A)	max (V)	(A)	max (mA)	(nC)	max (A)	max (°C)
1200 V										
STPSC6H12B-TR1	DPAK-2L	1	1200	6	1.86	6	0.40	28	36	175
STPSC10H12	TO-220AC; D ² PAK	1	1200	10	1.5	10	0.06	57	71	175
STPSC15H12	TO-220AC	1	1200	15	1.5	15	0.09	94	105	175
STPSC20H12	TO-220AC; D ² PAK; TO-247	1	1200	20	1.5	20	0.12	130	140	175

Ultrafast rectifiers

ULTRAFAST RECTIFIERS 200 V, 300 V AND 400 V

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current ($I_{\bar{A}}$)	Forward Voltage (V_F)	V_F measure condition (@ $I_{\bar{A}}$)	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
200 V										
STTH102	DO-35, SMA	1	200	1	0.97	1	0.001	20	40	175
STTH1R02	DO-15, DO-41, SMA, SMB	1	200	1	0.8	1.5	0.003	20	60	175
STTH2R02	SMA, SMB	1	200	2	0.8	2	0.003	20	75	175
STTH3R02	DO-15, DO-247, SMC	1	200	3	0.8	3	0.003	20	75	175
STTH4R02	DPAK, SMB, SMC	1	200	4	0.83	4	0.003	20	70	175
STTH602C	TO-220AB	2	200	2 x 3	1.05	6	0.003	20	60	175
STTH802	D ² PAK, TO-220AC, DPAK, TO-220FPAC	1	200	8	0.9	8	0.006	30	100	175
STTH802C	DPAK	2	200	2 x 4	1.1	8	0.004	20	50	175
STTH1002C	D ² PAK, DPAK, I ² PAK, TO-220AB, TO-220FPAC	2	200	2 x 5	1.05	10	0.005	25	50	175
STTH1202	TO-220AC, TO-220AC Ins	1	200	12	0.95	12	0.01	24	100	175
STTH1302C	D2PAK	2	200	2 x 6.5	1.1	13	0.006	25	70	175
STTH1502	TO-220AC, TO-220AC Ins, TO-220FPAC	1	200	15	0.95	15	0.001	25	150	175
STTH1602C	D ² PAK, TO-220AB, TO-220FPAC	2	200	2 x 8	1.05	16	0.006	26	80	175
STTH2002	D ² PAK, TO-220AC, TO-220AC Ins	1	200	20	0.95	20	0.01	20	175	175
STTH2002C	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC	2	200	2 x 10	1.05	20	0.01	27	90	175
STTH20W02C	TO-247	2	200	2 x 10	1.3	20	0.005	25	80	175
STTH3002	D ² PAK, DO-247, DOP3 Ins	1	200	30	0.88	30	0.02	27	300	175
STTH3002C	D ² PAK, TO-220AB, TO-247	2	200	2 x 15	0.99	30	0.02	22	180	175
STTH30R02DJF	PowerFLAT™ 5 x 6	1	200	30	0.95	30	0.01	35	300	175
STTH30W02C	TO-247	2	200	2 x 15	1.3	30	0.01	25	140	175
STTH6002C	TO-247, TOP3 Ins	2	200	2 x 30	0.99	60	0.03	27	330	175
STTH60W02C	TO-247	2	200	2 x 30	1.25	60	0.01	30	250	175
STTH10002	ISOTOP	2	200	2 x 50	0.97	100	0.05	37	750	150
STTH20002TV	ISOTOP	2	200	2 x 100	1.05	200	0.1	50	1000	150

ULTRAFAST RECTIFIERS 200 V, 300 V AND 400 V

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_{av})	Forward Voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
300 V										
STTH803	D ² PAK, TO-220AC	1	300	8	1	8	0.02	25	100	175
STTH8R03	TO-220AC	1	300	8	1.3	8	0.01	30	80	175
STTH8R03DJF	PowerFLATTM 5 x 6	1	300	8	1	8	0.04	35	280	175
STTH1003S	DPAK	1	300	10	1.1	10	0.01	13	100	175
STTH20L03C	D ² PAK, TO-220AB	2	300	2 x 10	0.95	10	0.01	35	150	175
STTH30W03C	TO-247	2	300	2 x 15	1.35	30	0.01	25	150	175
STTH2003	D ² PAK, I ² PAK, TO-220AB, TO-220FPAC	2	300	2 x 10	1	10	0.02	25	110	175
STTH3003	TO-247	2	300	2 x 15	1	15	0.04	30	140	175
STTH30R03	D ² PAK, TO-247	2	300	2 x 15	1.4	15	0.02	35	120	175
STTH50W03C	TO-247	2	300	2 x 25	1.2	25	0.015	27	200	175
STTH6003C	TO-247	2	300	2 x 30	1	30	0.06	40	300	175
STTH60W03C	TO-247	2	300	2 x 30	1.15	30	0.02	35	280	175
STTH60SW03C	TO-247	2	300	2 x 30	1.25	30	0.015	27	200	175
STTH60P03S	TO-247	1	300	60	1.5	30	0.1	50	250	175
STTH8003	Max247	2	300	2 x 40	1	40	0.08	50	400	175
STTH12003	ISOTOP	2	300	2 x 60	1	60	0.12	55	600	150
STTH16003	ISOTOP	2	300	2 x 80	0.95	80	0.2	60	800	150
STTH20003	ISOTOP	2	300	2 x 100	0.95	100	0.2	90	1000	150
STTH200W03T	ISOTOP	2	300	3 x 100	1.15	100	0.1	50	800	150
400 V										
STTH1R04	D0-15, D0-35, SMA, SMB	1	400	1	1.15	1	0.005	20	30	175
STTH3R04	D0-15, D0-201AD, SMB, SMC	1	400	3	1.15	3	0.005	25	60	175
STTH5L04DEE	PowerFLATTM 3.3 x 3.3	1	400	5	1.05	5	0.0025	60	60	150
STTH8R04	D ² PAK, TO-220AC, TO-220AC Ins	1	400	8	1.1	8	0.01	35	120	175
STTH10R04	D ² PAK	1	400	10	1.35	10	0.001	20	100	175
STTH16R04C	D ² PAK, TO-220AB	2	400	2 x 8	1.37	16	0.01	35	120	175
STTH20R04	D ² PAK, TO-220AC, TO-220FPAC	1	400	20	1.35	20	0.02	25	150	175
STTH30R04	D ² PAK, TO-220AC, D0-247	1	400	30	1.2	30	0.015	35	300	175
STTH6004W	DO-247	1	400	60	1	60	0.05	50	600	175
STTH60R04	DO-247	1	400	60	1.2	60	0.06	45	650	175

ULTRAFAST RECTIFIERS 200 V, 300 V AND 400 V

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current ($I_{\bar{A}}$)	Forward Voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
STTH61R04TV	ISOTOP	2	400	2 x 30	1.2	30	0.015	35	350	150
STTH61W04S	TO-247	1	400	60	1.15	60	0.02	55	500	175
STTH100W04C	TO-247	2	400	2 x 50	1.2	50	0.025	50	350	175
STTH120R04TV	ISOTOP	2	400	2 x 60	1.2	60	0.06	45	700	150
STTH20004TV1	ISOTOP	2	400	2 x 100	1	100	0.1	60	900	150
STTH200L04TV1	ISOTOP	2	400	2 x 100	1	100	0.1	60	900	150
STTH200R04TV	ISOTOP	2	400	2 x 100	1.1	100	0.08	55	1000	150
STTH200W04T	ISOTOP	2	400	2 x 100	1.3	100	0.04	55	800	150
STTH240F04TV1	ISOTOP	2	400	2 x 120	1.2	120	0.085	70	1000	150

ULTRAFAST RECTIFIERS 600 V

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_{av})	Forward voltage (V_F)	V_F measure condition (@ I_F) spec	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
STTH1L06	DO-41, SMA, SMB	1	600	1	1.05	1	0.001	80	20	175
STTH1R06	DO-41, SMA, SMB	1	600	1	1.25	1	0.001	25	20	175
STTH2L06	DO-41, SMA, SMB	1	600	2	1.05	2	0.002	85	35	175
STTH2R06	DO-41, SMA, SMB, SMC	1	600	2	1.25	2	0.002	30	30	175
STTH3L06	DO-201AD, SMB, SMC	1	600	3	1.05	3	0.003	85	60	175
STTH3R06	DO-201AD, SMB, SMC	1	600	3	1.25	3	0.003	30	45	175
STTH4L06	DO-201AD	1	600	4	1.05	3	0.003	55	80	175
STTH4R06DEE	PowerFLATT™ 3.3 x 3.3	1	600	4	1.25	4	0.003	40	60	150
STTH506	DPAK	1	600	5	1.4	5	0.005	30	55	175
STTH5L06	TO-220AC, DO-201AD, DPAK, TO-220FPAC	1	600	5	1.05	5	0.005	95	60	175
STTH5R06	D²PAK, TO-220AC, DPAK, TO-220FPAC	1	600	5	1.8	5	0.02	25	50	175
STTH5R06DJF	PowerFLAT™ 5 x 6	1	600	5	1.2	5	0.06	40	190	175
STTH806	D²PAK, TO-220AC Ins, TO-220AC	1	600	8	1.4	8	0.008	35	90	175
STTH8L06	D²PAK, TO-220AC, TO-220FPAC, TO-220 Ins	1	600	8	1.05	8	0.008	105	120	175
STTH8R06	D²PAK, TO-220AC, TO-220AC Ins, TO-220FPAC	1	600	8	1.8	8	0.03	25	80	175
STTH8S06	TO-220AC, TO-220FPAC, DPAK	1	600	8	1.9	8	0.02	18	60	175
STTH12R06	D²PAK, TO-220AC, TO-220AC Ins, TO-220FP	1	600	12	1.8	12	0.045	25	100	175
STTH12S06	TO-220FPAC	1	600	12	1.9	12	0.03	21	100	175
STTH15L06	D²PAK, TO-220AC, TO-220FPAC	1	600	15	1.2	15	0.015	55	150	175
STTH15R06	TO-220AC, TO-220FPAC	1	600	15	1.8	15	0.06	30	150	175
STTH16L06C	D²PAK, TO-220AB, TO-220FPAC	2	600	2 x 8	1.64	8	0.008	35	120	175
STTH3006	TO-247, DOP3 Ins	1	600	30	1.4	30	0.025	50	300	175
STTH30L06	D²PAK, TO-247	1	600	30	1.25	30	0.025	65	300	175
STTH30L06C	D²PAK, TO-247	2	600	2 x 15	1.45	15	0.015	55	130	175
STTH30R06	DO-247, DOP3 Ins	1	600	30	1.4	30	0.025	50	300	175
STTH30AC06C	TO-247 long leads, TO-3P, TO-3PF	2	600	2 x 15	1.8	15	0.01	30	140	175
STTH30ACS06W	TO-247	1	600	30	1.9	30	0.005	30	190	175
STTH30R06C	TO-247	2	600	2 x 15	1.8	15	0.06	30	120	175

ULTRAFAST RECTIFIERS 600 V

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_{av})	Forward voltage (V_F)	V_z measure condition (@ I_z) spec	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
STTH30S06	D0-247	1	600	30	2.2	30	0.05	30	180	175
STTH31AC06	TO-3PF, TP-247LL	1	600	30	1.75	30	0.01	65	150	175
STTH50W06S	TO-247	1	600	50	1.6	50	0.05	45	390	175
STTH6006TV	ISOTOP	2	600	2 x 30	1.4	30	0.025	50	210	150
STTH6006W	TO-247	1	600	60	1.4	60	0.05	60	400	175
STTH60L06	TO-247	1	600	60	1.2	60	0.05	70	600	175
STTH60AC06C	TO-247, TO-247LL	2	600	2 x 30	1.7	60	0.01	40	280	175
STTH60L06C	TO-247	2	600	2 x 30	1.55	60	0.025	65	210	175
STTH60L06TV	ISOTOP	2	600	2 x 30	1.25	60	0.025	65	210	150
STTH8006	D0-247	1	600	80	1.3	80	0.05	70	500	150
STTH80S06W	TO-247	1	600	80	2.15	80	0.05	45	400	175
STTH100W06C	TO-247	1	600	80	2.15	80	0.05	45	400	175
STTH120L06TV	ISOTOP	2	600	2 x 60	1.2	60	0.05	70	500	150
STTH200L06TV	ISOTOP	2	600	2 x 100	1.2	100	0.08	80	800	150
STTH200W06T	ISOTOP	2	600	2 x 100	1.3	100	0.03	75	800	150

HYPERFAST TANDEM RECTIFIERS 600 V

Generic part number	Package	Number of diodes	Repetitive peak reverse voltage (V _{RRM})	Average rectified current (I _a)	Forward voltage (V _F)	V _F measure condition (@ I _F) spec	Reverse current (I _R)	Reverse recovery time (t _{rr})	Non-repetitive peak forward surge current (I _{FSM})	Junction temperature (T _j)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
STTH506D	T0-220AC Ins	1	600	5	2.4	5	0.006	15	60	150
STTH806DTI	T0-220AC Ins	1	600	8	2.4	8	0.01	30	180	150
STTH806TTI	T0-220AB Ins	1	600	8	2.6	8	0.01	30	80	150
STTH8ST06	T0-220AC Ins	1	600	8	3.1	8	0.006	26	55	175
STTH8T06	T0-220AC Ins	1	600	8	2.55	8	0.01	30	80	175
STTH1008DTI	T0-220AC AC ISOL.	1	800	10	2.05	10	0.02	55	120	150
STTH12T06DI	T0-220AC Ins	1	600	12	2.55	12	0.02	33	90	175
STTH1506D	DOP3 Ins	1	600	15	2.4	15	0.02	35	130	150
STTH1506TPI	TOP3 Ins	1	600	15	2.6	15	0.02	35	130	150
STTH3006D	DOP3 Ins	1	600	30	2.4	30	0.04	45	180	150

ULTRAFAST RECTIFIERS 800 V, 1000 V AND 1200 V

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_o)	Forward voltage (V_F)	V_F measure condition (@ I_o)	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_j)
			max (V)	max (A)	max (V)	spec (A)	max (mA)	max (ns)	max (A)	max (°C)
800 V										
STTH108	DO-35, SMA	1	800	1	1.25	1	0.005	75	20	175
STTH208	DO-15, SMB	1	800	2	1.25	2	0.005	75	35	175
1000 V										
STTH110	DO-35, SMA	1	1000	1	1.42	1	0.01	75	18	175
STTH310	DO-201AD bent, DO-201AD, SMC	1	1000	3	1.42	3	0.01	75	45	175
STTH810	D ² PAK, TO-220AC, TO-220AC Ins, TO-220FPAC	1	1000	8	1.7	8	0.005	65	60	175
STTH1210	TO-220AC, TO-220AC Ins	1	1000	12	1.7	12	0.01	65	80	175
STTH3010	TO-220AC, DO-247, DOP3 Ins	1	1000	30	1.7	30	0.015	55	180	175
STTH6010	DO-247	1	1000	60	1.7	60	0.02	65	400	175
STTH6110TV	ISOTOP	2	1000	2 x 30	1.7	30	0.015	55	240	150
STTH12010TV	ISOTOP	2	1000	2 x 60	1.7	60	0.02	65	400	150
1200 V										
STTH112	DO-35, SMA, SMB	1	1200	1	1.55	1	0.005	75	18	175
STTH212	SMB, SMC	1	1200	2	1.5	2	0.01	75	40	175
STTH312	DPAK	1	1200	3	1.65	3	0.01	80	35	175
STTH512	TO-220AC, DPAK, TO-220FPAC	1	1200	5	1.9	5	0.005	70	55	175
STTH812	D ² PAK, TO-220AC, TO-220AC Ins, TO-220FPAC	1	1200	8	1.9	8	0.008	70	80	175
STTH8S12	TO-220AC	1	1200	8	2.5	8	0.005	45	70	175
STTH1212	TO-220AC	1	1200	12	1.9	12	0.01	70	100	175
STTH1512	D ² PAK, DO-247, DOP3 Ins	1	1200	15	1.8	15	0.015	75	200	175
STTH15S12	TO-220AC, DO-247	1	1200	15	2.7	15	0.01	40	130	175
STTH3012	TO-220AC, DO-247, TO-247LL	1	1200	30	1.95	30	0.02	80	210	175
STTH30S12	DO-247	1	1200	30	2.7	30	0.015	50	180	175
STTH6012	DO-247	1	1200	60	1.95	60	0.03	70	400	175
STTH6112TV	ISOTOP	2	1200	2 x 30	1.95	30	0.02	65	250	150
STTH75S12	DO-247	1	1200	75	2.7	75	0.05	55	370	175
STTH9012TV	ISOTOP	2	1200	2 x 45	1.8	45	0.03	85	420	150
STTH12012TV	ISOTOP	2	1000	2 x 60	1.95	60	0.02	70	420	150

Automotive-grade diodes

AUTOMOTIVE-GRADE SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_o)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (A)	max (°C)
30 V									
STPS8L30BY-TR	DPAK	1	30	8	0.4	0.4	1	75	150
STPS60L30CKY-TR	PowerSO-20	2	30	2 x 30	0.49	30	2	250	150
40 V									
STPS0540ZY	SOD-123	1	40	0.5	0.5	0.5	0.04	5.5	150
STPS140	SMA, SMB	1	40	1	0.55	1	0.012	60	150
STPS140ZY	SOD-123	1	40	1	0.55	1	0.012	5.5	150
STPS1L40	SMA, SMB	1	40	1	0.42	1	0.035	60	150
STPS340	SMB, SMC	1	40	3	0.63	3	0.02	75	150
STPS3L40SY	SMC	1	40	3	0.5	3	0.1	75	150
STPS640CBY-TR	DPAK	2	40	3	0.57	3	0.01	75	150
45 V									
STPS1045BY	DPAK	1	45	10	0.63	10	0.1	75	175
STPS1545DY	T0-220AC	1	45	15	0.57	15	0.2	220	175
STPS1545CGY-TR	D2PAK	2	45	2 x 7.5	0.84	15	0.1	150	175
STPS15L45CBY-TR	DPAK	2	45	2 x 7.5	0.64	15	1	75	150
STPS2045CGY-TR	D2PAK	2	45	2 x 10	0.84	20	0.1	180	175
STPS2545CGY-TR	D2PAK	2	45	2 x 12.5	0.84	25	0.125	200	175
STPS2545CTY	T0-220AB	2	45	2 x 12.5	0.84	25	0.125	200	175
STPS3045CGY-TR	D2PAK	2	45	2 x 15	0.84	30	0.2	220	175
STPS3045DJFY-TR	PowerFLAT™ 5 x 6	1	45	30	0.56	30	0.3	200	175
STPS4045CWY	T0-247	2	45	2 x 20	0.76	20	0.2	220	175
STPS40L45CGY-TR	D2PAK	2	45	2 x 20	0.49	20	0.6	230	150
STPS6045CWY	T0-247	2	45	2 x 30	0.63	30	0.5	400	175
60 V									
STPS160	SMA, SMB	1	60	1	0.57	1	4	75	150
STPS360AFY	SOD128Flat	1	60	3	0.58	3	0.15	60	175
STPS2L60AY	SMA	1	60	2	0.6	2	0.1	75	150

AUTOMOTIVE-GRADE SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current (I_o)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (A)	max (°C)
STPS30H60CGY-TR	D ² PAK	2	60	2 x 15	0.57	15	0.06	230	175
STPS3L60SY	SMC	1	60	3	0.65	3	0.055	75	150
STPS3L60UY	SMB	1	60	3	0.62	3	0.15	100	150
STPS5L60SY	SMC	1	60	5	0.48	5	0.22	150	150
STPS20L60CGY-TR	D ² PAK	2	60	2 x 10	0.6	10	0.35	220	150
100 V									
STPS1H100	SMA, SMB	1	100	1	0.77	1	0.004	50	175
STPS2H100	SMA, SMB	1	100	2	0.79	2	0.001	75	175
STPS3H100AFY	SOD128Flat	1	100	3	0.68	3	0.001	25	175
STPS5H100BY-TR	DPAK	1	100	5	0.79	5	0.0035	75	175
STPS15H100CBY-TR	DPAK	2	100	2 x 7.5	0.8	7.5	0.003	75	175
STPS20H100CGY-TR	D ² PAK	2	100	2 x 10	0.73	10	0.0045	250	175
STPS41H100CGY-TR	D ² PAK	2	100	2 x 20	0.8	20	0.01	220	175
STPS41H100CTY	T0-220AB	2	100	3 x 20	0.8	20	0.01	220	175
140 V									
STPS41140CGY-TR	D ² PAK	2	140	2 x 20	0.68	20	0.03	240	175
150 V									
STPS1150AY	SMA	1	150	1	0.67	1	0.001	50	175
STPS3150UY	SMB	1	150	3	0.82	3	0.002	80	175
170 V									
STPS40170CGY-TR	D ² PAK	2	170	2 x 20	0.92	20	0.03	250	175
STPS200170TV1Y	ISOTOP	2	170	200	0.85	100	0.2	700	150

AUTOMOTIVE-GRADE ULTRAFAST DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current ($I_{\bar{r}}$)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
200 V and 300 V										
STTH102AY	SMA	1	200	1	0.97	1	0.001	20	40	175
STTH2R02UY	SMB	1	200	2	1	2	0.003	20	75	175
STTH2R02AFY	SOD128Flat	1	200	2	0.83	2	0.008	20	50	175
STTH3R02AFY	SOD128Flat	1	200	3	0.83	3	0.0016	21	80	175
STTH4R02BY-TR	DPAK	1	200	4	1.05	4	0.003	20	70	175
STTH4R02SY	SMC	1	200	4	0.83	4	0.003	20	70	175
STTH4R02UY	SMB	1	200	4	0.83	4	0.003	20	70	175
STTH602CBY-TR	DPAK	2	200	2 x 3	0.95	3	0.003	20	60	175
STTH802BY-TR	DPAK	1	200	8	1.05	8	0.006	30	100	175
STTH1002C-Y	D ² PAK, DPAK	2	200	2 x 5	1.1	5	0.005	20	50	175
STTH1003SBY-TR	DPAK	1	300	10	1.3	10	0.1	35	100	175
STTH2003CGY-TR	D ² PAK	2	300	2 x 10	1.25	10	0.02	40	110	175
400 V										
STTH1R04AY	SMA	1	400	1	0.9	1	0.05	20	30	175
STTH1R04UY	SMB	1	400	1	0.9	1	0.05	20	30	175
STTH3R04DY	T0-220AC	1	400	30	1	30	0.03	45	280	175
STTH3R04WY	DO-247	1	400	30	1	30	0.03	45	280	175
600 V										
STTH1L06UFY	SMBflat	1	600	1	1.4	1	0.001	60	20	175
STTH1R06UFY	SMBflat	1	600	1	1.9	1	0.001	45	17	175
STTH2L06UFY	SMBflat	1	600	2	1.4	2	0.002	70	30	175
STTH2R06UFY	SMBflat	1	600	2	1.9	2	0.002	50	28	175
STTH3L06UFY	SMBflat	1	600	3	1.4	3	0.003	70	30	175
STTH3R06UFY	SMBflat	1	600	3	1.9	3	0.003	50	30	175
STTH5R06BY-TR	DPAK	1	600	5	3.2	5	0.03	35	50	175
STTH5R06GY-TR	D ² PAK	1	600	5	3.2	5	0.03	35	50	175
STTH8R06GY-TR	D ² PAK	1	600	8	3.2	8	0.03	45	90	175
STTH16L06CTY	T0-220AB	2	600	2 x 8	1.35	8	0.008	55	120	175
STTH30L06WY	DO-247	1	600	30	1.55	30	0.025	65	300	175

AUTOMOTIVE-GRADE ULTRAFAST DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current ($I_{\bar{r}}$)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Reverse recovery time (t_{rr})	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (ns)	max (A)	max (°C)
STTH30ST06GY-TR	D ² PAK	1	600	30	2.2	30	0.05	50	160	175
STTH30ST06WY	DO-247	1	600	30	2.2	30	0.05	50	160	175
800 V										
STTH208FY	SMBflat	1	800	2	1.25	2	0.005	75	30	175
1000 V										
STTH110UFY	SMBflat	1	1000	1	1.7	1	0.005	75	20	175
STTH310UFY	SMBflat	1	1000	3	1.42	3	0.01	75	30	175
STTH810GY-TR	D ² PAK	1	1000	8	2	8	0.005	85	60	175
STTH1210DY	T0-220AC	1	1000	12	2	12	0.01	90	80	175
STTH3010GY-TR	D ² PAK	1	1000	30	2	30	0.015	100	300	175
STTH3010WY	DO-247	1	1000	30	2	30	0.015	100	300	175
STTH6010WY	DO-247	1	1000	60	1.7	60	0.02	65	400	175
1200 V										
STTH112UFY	SMBflat	1	1200	1	1.9	1	0.005	75	18	175
STTH1512GY-TR	D ² PAK	1	1200	15	2.1	15	0.015	75	200	175

AUTOMOTIVE-GRADE ULTRAFAST SILICON-CARBIDE DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current ($I_{\bar{r}}$)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Total capacitive charge (Q_c)	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	(nC)	max (A)	max (°C)
STPSC10H065DY	TO-220AC	1	650	10	2.5	10	0.1	28.5	90	175
STPSC10H065GY-TR	D ² PAK	1	650	10	2.5	10	0.1	28.5	90	175
STPSC12C065DY	TO-220AC	1	650	12	2.5	12	0.12	29.3	92	175
STPSC12H065DY	TO-220AC	1	650	12	2.5	12	0.12	36	100	175
STPSC12H065GY-TR	D ² PAK	1	650	12	2.5	12	0.12	36	100	175
STPSC12065DY	TO-220AC	1	650	12	1.45	12	0.15	36	50	175
STPSC20065DY	TO-220AC	1	650	20	1.45	20	0.3	30	90	175
STPSC20065WY	TO-247	1	650	20	1.45	20	0.3	30	90	175
STPSC20H065CTY	TO-220AB	2	650	2 x 10	2.5	10	0.1	28.5	90	175
STPSC20H065CWY	TO-247	2	650	2 x 10	2.5	10	0.1	28.5	90	175
STPSC40065CWY	TO-247	2	650	2 x 20	1.45	20	0.35	30	90	175

AUTOMOTIVE-GRADE SIGNAL SCHOTTKY DIODES

Part number	Package	Number of diodes	Repetitive peak reverse voltage (V_{RRM})	Average rectified current ($I_{\bar{r}}$)	Forward voltage (V_F)	V_F measure condition (@ I_F)	Reverse current (I_R)	Total capacitance	Non-repetitive peak forward surge current (I_{FSM})	Junction temperature (T_J)
			max (V)	max (A)	max (V)	(A)	max (mA)	max (pF)	max (A)	max (°C)
BAT54AWFILMY	SOT-323	2	40	0.3	0.24	0.0001	0.001	10	1	150
BAT54CWFILMY	SOT-323	2	40	0.3	0.24	0.0001	0.001	10	1	150
BAT54FILMY	SOT-23	1	40	0.3	0.24	0.0001	0.001	10	1	150
BAT54SFILMY	SOT-23	2	40	0.3	0.24	0.0001	0.001	10	1	150
BAT54WFILMY	SOT-323	1	40	0.3	0.24	0.0001	0.001	10	1	150