



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



WHA 3000PS

Product no.: T0053355699N



Benefits

- > 700 W
- > Integrated turbine
- > Set with Infrared preheating plate and circuit board holder



For this purpose, we recommend:



Solder fume extractors



Pre-heating plates



Zubehoer




Soldering tips



Technical Data

Dimensions L x W x H (inches)	9,44 x 10,63 x 6,69
Dimensions L x W x H (mm)	240 x 270 x 170 (WHA3000P)
Space requirement/workspace L x W x H (inches)	23,6 x 23,6 x 19,7 (WHA3000P + WBHS + WHP3000)
Space requirement/workspace L x W x H (mm)	600 x 600 x 500 (WHA3000P + WBHS + WHP3000)
Recommended assembly size (mm)	310 x 320
Recommended component size (mm)	4,5 x 4,5 - 43x43
Compressed air connection	X
Compressed air connection accessory	X
Compressed air supply kPa/bar	X
Air consumption l/min	X
Max. hot air flow rate l/min	5 - 50
ESD-safe	on
Noise level (distance 1 m) dB(A)	tbd
Weight (approx.) in kg	tbd
Power consumption	1200 W
Rated output of top heating (W)	700
Rated output of bottom heating (W)	600
Protection class	1 (control unit and hand piece hard grounded)
Voltage	220-230V/50-60Hz
Temperature range of top heating (°C)	50 - 500
Temperature range of bottom heating (°C)	50 - 400
Optical positioning	---
Positioning aid	X
Temperature accuracy of top heating	± 30 °C (± 54 °F)
Temperature accuracy of bottom heating	tbd
Thermocouple connection	1x Type-K

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE