



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# WXD 2010

2-Channel Solder- and Desoldering Station, 200 W (255 W)  
Product no.: T0053428699N



## Benefits

- › Desoldering station WXD 2, 2 channels digital and electronically controlled with desoldering iron WXDP 120
- › Soldering- and desoldering tools with intelligent WX technology
- › Connection to external compressed air supply required
- › Energy effective: automatic stand-by mode for tools
- › Patented, ESD safe glass display. Simple and fast setting of soldering parameter.




For this purpose, we recommend:



Solder fume extractors



Soldering irons



Cleaning



Pre-heating plates



**Technical Data**

Dimensions L x W x H (mm)	174 x 154 x 135
Dimensions L x W x H (inches)	6,69 x 5,94 x 5,12
Weight (approx.) in kg	3.2
Voltage	230 V, 50 Hz
Power	200 W (255 W)
Channels	2
Temperature range (depends on tool) °C	50 - 550
Temperature range (depends on tool) °F	150 - 999
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding socket	Via 3, 5 mm pawl socket on back of unit.
Display	255 x 128 dots / Backlighting
Air consumption l/min	35
Operating pressure in bar/psi	4,0 - 6,0 / 58 - 87
Capacity l/min	---
Vacuum	55 kPA (8 psi)

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE