Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!

Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Thermal Transfer Labels

PANDUIT®

Thermal Transfer Labels

Panduit is a global leader in reliable and innovative solutions for identification and safety. Products are engineered for a wide variety of industries and applications – including electrical, electronics, industrial, and network. Panduit offers a complete, leading-edge line of labeling software, high-performance label materials (all RoHS compliant), and printers that provide enhanced productivity, dependability, and value to all infrastructure labeling requirements.

Cable/Wire Labels

Turn-Tell® Labels 4
Self-Laminating Labels . . . . . 5 – 7
LabelCore™ Fiber Optic Cable Identification System . . . . . 7 – 8
Flag Labels 8
Non-Laminated Vinyl Cloth Labels 9
Non-Laminated Nylon Cloth Labels 10

Marker Plates

High-Temperature Flame-Retardant Marker Plates 11
Halogen-Free Flame-Retardant Marker Plates 11
Standard Marker Plates 12

Heat Shrink Labels

Military Grade – Single-Sided Labels 13
Military Grade – Two-Sided Labels 14
Halogen-Free – Two-Sided Labels 15
Fluid-Resistant – Two-Sided Labels 16

Component Labels/Continuous Tapes

Raised Panel Labels . . . . . 17 – 20
Polyester Component Labels 21
Super-Tack Polyester Component Labels 22
Tedlar® Component Labels 23
Tamper-Evident Polyester Component Labels 23
Non-Adhesive Polyester Component Labels 24
Vinyl Cloth Component Labels 24
Polyimide Component Labels 25
Paper Component Labels 26
Continuous Tapes . . . . . 26 – 28

Safety and Solar Labels

Super-Tack Polyester Arc Flash Labels 29
Raised Panel Arc Flash Labels 29
Super-Tack Arc Flash Continuous Tapes 30
Super-Tack Polyester Facility Identification Labels 30
Polyester Photoluminescent Tapes 31
Raised Panel Solar Labels 31
Over-Laminate Labels 32
Super-Tack Polyester Solar Labels 32
Reflective Continuous Tapes for Solar Applications 32

Software/Printers/Accessories

Software 33
TDP43ME Printers, Accessories and Ribbons 34
TDP43HE & TDP46HE Printers, Accessories & Ribbons . . . 35

Tedlar is a registered trademark of E.I. du Pont de Nemours and Company.

Turn-Tell® Labels

PATENTED

- Allows labels to rotate for visibility from any angle, and allows repositioning on the wire/cable to align legends for improved aesthetics
- Ideal for use in high-density or space-constrained cable applications
- Use thermal transfer hybrid ribbon
- Temperature range: -40°F to 150°F (-40°C to 66°C)



2015 Cabling Installation & Maintenance Silver Innovators Awards

Part Number	Print-On Area Color	Width In.	Width mm	Length In.	Length mm	Print-On Area Height In.	Print-On Area Height mm	Min. Cable O.D. In.	Min. Cable O.D. mm	Max. Cable O.D. In.	Max. Cable O.D. mm	Wire Range	Labels Per Row	Std. Pkg. Qty.
R050X075V1T	White	0.50	12.7	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	8	5000
R050X125V1T				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP/12 – 10 AWG		
R050X150V1T				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/Cat. 5e FTP/ 10 – 6 AWG		
R100X075V1T		1.00	25.4	0.75	19.1	0.25	6.4	0.12	3.1	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	4	2500
R100X125V1T				1.25	31.8	0.38	9.7	0.16	4.1	0.22	5.6	Cat. 3 UTP/12 – 10 AWG		
R100X150V1T				1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/		
R100X150V2T	TIA Blue													
R100X150V3T	TIA Green													
R100X150V4T	TIA Gray													
R100X150V7T	TIA Red													
R100X150V8T	TIA Yellow													
R100X225V1T	White			2.25	57.2	0.75	19.1	0.28	7.1	0.39	9.9	Cat. 6 FTP/Cat. 6 UTP/ Cat. 6A FTP/8-4 AWG		
R100X225V2T	TIA Blue													
R100X225V3T	TIA Green													
R100X225V4T	TIA Gray													
R100X225V7T	TIA Red													
R100X225V8T	TIA Yellow													
R100X400V1T	White			4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG		1000
R150X150V1T		1.50	38.1	1.50	38.1	0.50	12.7	0.22	5.6	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/ Cat. 6A UTP/Cat. 5e FTP/ 10 – 6 AWG	2	
R200X150V1T		2.00	50.8											
R200X225V1T				2.25	57.2	0.75	19.1	0.28	7.1	0.39	9.9	Cat. 6 FTP/Cat. 6A UTP/ Cat. 6A FTP/8 – 4 AWG	4	
R200X400V1T				4.00	101.6	1.00	25.4	0.39	9.9	0.95	24.1	2 – 1 AWG	2	

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Vinyl Self-Laminating Labels

- Includes a colored print-on area and clear overlaminate to protect the legend for clear and durable identification
- Sized specifically for wire and cable applications
- Thin and conformable; preferred material for most general wire/cable labeling
- Use thermal transfer hybrid ribbon
- Temperature range: -40°F to 150°F (-40°C to 66°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15-01, File # MH14979



Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
S050X075VA1Y	White	0.50	12.7	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.1	Cat. 6 28 AWG/ 18 – 14 AWG	8	5000
S050X075VATY*														2500
S050X125VA1Y				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG		5000
S050X125VATY*														
S050X150VA1Y				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG		
S050X150VATY*														
S050X250VATY*				2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 – 2 AWG		
S075X075VATY*		0.75	19.1	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	5	
S075X100VATY*				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG		
S075X125VATY*														
S075X150VATY*				1.50	38.1.	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG		
S100X075VA1Y		1.00	25.4	0.75	19.1	0.25	6.4	0.08	0.50	2.0	4.0	Cat. 6 28 AWG/ 18 – 14 AWG	4	2500
S100X075VATY*														5000
S100X125VA1Y				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/ 12 - 10 AWG		2500
S100X125VATY*														5000
S100X150VA1Y				1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/10 - 6 AWG	4	2500
S100X150VATY														5000
S100X150VBTY	TIA Blue													
S100X150CVTY	TIA Brown													
S100X150VDTY	TIA Green													
S100X150VETY	TIA Gray													
S100X150VFTY	TIA Orange													
S100X150VGTY	TIA Purple													

Order number of labels required in multiples of Standard Package Quantity.
*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Vinyl Self-Laminating Labels (continued)

Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
S100X150VHTY*	TIA Red	1.00	25.4	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/ Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	4	5000
S100X150VITY*	TIA Yellow													
S100X150V0TY*	Black													
S100X150V9TY*	Gold													
S100X225VA1Y	White			2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/8 – 4 AWG		
S100X225VATY*	White													
S100X225VBTY*	TIA Blue													
S100X225VCTY*	TIA Brown													
S100X225VDTY*	TIA Green													
S100X225VETY*	TIA Gray													
S100X225VFTY*	TIA Orange													
S100X225VGTY*	TIA Purple													
S100X225VHTY*	TIA Red													
S100X225VITY*	TIA Yellow													
S100X225V0TY*	Black													
S100X225V9TY*	Gold													
S100X250VA1Y	White			2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 - 2 AWG		1500
S100X250VATY*														5000
S100X400VA1Y				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 - 1 AWG		1000
S100X400VATY*														2500
S100X650VA1Y				6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 - 250 MCM		250
S100X650VATY*														1000
S150X150VATY*		1.50	38.1	1.50	38.1.	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG	2	5000
S150X225VATY*				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	8 – 4 AWG		
S150X400VATY*				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.1	2 – 1 AWG		2500
S200X150VATY*		2.00	50.8	1.50	38.1	0.50	21.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/10 – 6 AWG		5000
S200X225VA1Y				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/Cat. 6A FTP/8 - 4 AWG		500
S200X225VATY*														1000
S200X250VATY*				2.50	63.5	1.00	25.4	0.32	8.1	0.48	12.1	6 – 2 AWG		
S200X400VA1Y				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 - 1 AWG		500
S200X400VATY*														1000
S200X650VA1Y				6.50	165.1	1.50	38.1	0.48	12.1	1.59	40.4	1/0 - 250 MCM		250
S200X650VATY*														1000

Order number of labels required in multiples of Standard Package Quantity.
*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

PVDF Self-Laminating Labels

- Self-extinguishing material and recommended alternative to Tedlar®
- Sized specifically for wire and cable applications
- Use thermal transfer hybrid ribbon
- Temperature range: -65°F to 275°F (-54°C to 135°C)
- UL969 recognized File # MH14979; cUL recognized C22.2 No. 0.15.01, File # MH149799

Part Number	Print-On Area Color	Width		Length		Print-On Area Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
S050X150T1T	White	0.50	12.7	1.50	38.1	0.50	12.7	0.16	4.0	0.32	8.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/ Cat. 5e FTP/ 10 – 6 AWG	8	5000
S075X125T1T		0.75	19.1	1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	Cat. 3 UTP/12 – 10 AWG	5	
S100X075T1T		1.00	25.4	0.75	19.1	0.25	6.4	0.08	2.0	0.16	4.0	Cat. 6 28 AWG/18 – 14 AWG	4	2500
S100X125T1T				1.25	31.8	0.38	9.7	0.12	3.1	0.28	7.0	12 – 10 AWG		
S100X150T1T				1.50	38.1	0.50	12.7	0.16	4.0	0.28	7.1	Cat. 5e UTP/Cat. 6 UTP/Cat. 6A UTP/Cat. 5e FTP/ 10 - 6 AWG		
S100X225T1T				2.25	57.2	0.75	19.1	0.24	6.1	0.48	12.1	Cat. 6 FTP/Cat. 6A UTP/ Cat. 6A FTP/8 – 4 AWG		1500
S100X400T1T				4.00	101.6	1.00	25.4	0.32	8.1	0.95	24.3	2 – 1 AWG		2500
S200X400T1T		2.00	50.8										2	500

Tedlar® is a registered trademark of E.I. du Pont de Nemours and Company.
Order number of labels required in multiples of Standard Package Quantity.
*Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

LabelCore™ Fiber Optic Cable Identification System

PATENTED

- Provides a larger labeling surface on small fiber cables and allows legends to be clearly seen
- Sleeves are made of flexible PVC material
- Locate sleeve on straight section of cable at least 2 inches from fiber boot



Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex fiber cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	100
NWSLC-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 1" long, use with labels: S100X150YAJ (Laser/Inkjet); S100X150VAC (LS8E Hand-held Printer); S100X150VA1Y or S100X150VATY (Thermal Transfer Printer).	
NWSLC-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 1" long, use with labels: S100X225YAJ (Laser/Inkjet); S100X225VAC (LS8E Hand-held Printer); S100X225VATY or S200X225VATY (Thermal Transfer Printer).	

Order number of labels required in multiples of Standard Package Quantity.

LabelCore™ Fiber Optic Cable Identification System (continued)

Part Number	Color	Part Description	Std. Pkg. Qty.
NWSLC2-2Y	Yellow	Yellow cable identification sleeve for 2mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	100
NWSLC2-2Y-AQ	Aqua	Aqua cable identification sleeve for 2mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-3Y	Orange	Orange cable identification sleeve for 3mm simplex cable, 2 inches long, use with labels: S200X150YAJ (Laser/Inkjet) or S200X150VATY (Thermal Transfer Printer).	
NWSLC2-7Y	White	White cable identification sleeve for 3mm duplex fiber cable, 2 inches long, use with labels: S200X225YAJ (Laser/Inkjet) S200X225VATY (Thermal Transfer Printer).	

Order number of labels required in multiples of Standard Package Quantity.

Flag Labels

- Halogen-free, white polyester flag-style marker for wire/cable labeling
- Improved legibility and more information on small wires and cables provide clearer, more complete identification
- Innovative design allows the product to be applied as a permanent adhesive label or as a repositionable non-adhesive label
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized C22.2 No. 0.15-01, File # MH14979



Part Number	Width		Height		Print-On Area				Min. Cable O.D.		Max. Cable O.D.		Wire Range	Std. Pkg. Qty. Roll
	In.	mm	In.	mm	Width		Height		In.	mm	In.	mm		
F100X150AJT	1.00	25.4	1.50	38.1	0.88	22.4	0.75	19.1	0.12	3.1	0.20	5.1	12 – 10 AWG	2500
F100X213AJT			2.13	54.1					0.32	8.1	0.38	9.7	Cat. 5e – Cat. 6	
F100X300AJT			3.00	76.2			2.00	50.8	0.09	2.3	0.28	7.1	8 – 4 AWG	
F100X363AJT			3.63	92.2					0.20	5.1	0.46	11.7	2 – 1 AWG	

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Non-Laminated Vinyl Cloth Labels

- Thin and conformable material with repositionable adhesive allows label to be removed and reused in temporary applications
- Works well on Teflon® coated wires*
- Use thermal transfer hybrid ribbon
- Temperature range: -40° F to 170° F (-40° C to 77° C)
- UL969 recognized, File # MH14576 and MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14576

Part Number	Print-On Area Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm			
N025X075CBT	White	0.25	6.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	7	10000
N025X125CBT				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N025X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		2500
N025X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		10000
N050X075CBT		0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG		
N050X100CBT				1.00	25.4	0.16	4.1	0.24	6.1	10 – 8 AWG		
N050X125CBT				1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N050X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		2500
N050X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		
N100X075CBT		1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	3	10000
N100X125CBT				1.25	31.8	0.20	4.1	0.32	8.1	10 – 6 AWG		5000
N100X150CBT				1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N100X175CBT				1.75	44.5	0.28	7.1	0.48	12.2	6 – 1 AWG		2500
N150X075CBT		1.50	38.1	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	1	5000

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.
* Teflon® is a registered trademark of E. I du Pont de Nemours and Company

Non-Laminated Nylon Cloth Labels

- Offer crisp, clear legends with superior legibility
- Used in flat applications and in a wrap format for wire/cable marking
- Use thermal transfer resin ribbon
- Temperature range: -65°F to 275°F (-54°C to 135°C)



Part Number	Color	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm			
N050X075C1T	White	0.50	12.7	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	5	10000
N050X075C2T	Yellow											
N050X125C1T	White			1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		
N050X125C2T	Yellow											
N050X150C1T	White			1.50	38.1	0.24	6.1	0.40	10.5	8 – 2 AWG		5000
N050X150C2T	Yellow											
N100X075C1T	White	1.00	25.4	0.75	19.1	0.12	3.1	0.16	4.1	12 – 10 AWG	3	10000
N100X075C2T	Yellow											
N100X125C1T	White			1.25	31.8	0.20	5.1	0.32	8.1	10 – 6 AWG		5000
N100X125C2T	Yellow											
N100X150C1T	White			1.50	38.1	0.24	6.1	0.40	10.2	8 – 2 AWG		
N100X150C2T	Yellow											

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME Printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

High-Temperature Flame-Retardant Marker Plates

- Used for identification markers in (Class 1E) harsh environments
- Compatible with Intermediate Cross Section cable ties
- Use thermal transfer RMER4BL-A resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)



Part Number	Color	Width		Height		Print-On Area Width		Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm		
M200X042FQT	White	2.00	50.8	0.42	10.7	1.22	31.0	500	1
M200X042FQT-B								2000	
M200X080FQT				0.80	20.3			250	
M200X080FQT-B								1000	

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Halogen-Free Flame-Retardant Marker Plates

- Used to identify wires, cables, equipment, and many other applications
- Offer crisp, clear legend with superior legibility and engineered to withstand high temperatures, harsh solvents, oils, and chemicals without over-lamination
- Compatible with Intermediate Cross Section cable ties
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 193°F (-40°C to 90°C)



Part Number	Color	Width		Height		Print-On Area Width		Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm		
M200X042UPT	White	2.00	50.8	0.42	10.7	1.30	33.0	500	1
M200X042UPT-B								2000	
M200X080UPT				0.80	20.3			500	
M200X080UPT-B								2000	

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Standard Marker Plates

- Non-adhesive and halogen free; used to identify wires, cables, equipment, and many other applications
- Attachable in horizontal or vertical orientation. The 0.5" Plenum rated and 0.33" non-Plenum rated Hook & Loop Cable Ties can be used in hanging position
- Meets the outgassing requirements of ASTM E-595 suitable for use in air handling spaces
- Available in a variety of colors and sizes
- Use thermal transfer resin ribbon
- Temperature range: -58°F to 221°F (-50°C to 105°C)





Part Number	Color	Width		Height		Print-On Area Width		Cable Type	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm			
M200X050Y6T	TIA Yellow	2.00	50.8	0.50	12.7	1.07	27.3	Intermediate Cross Section Cable Ties	500	1
M200X050Y7T	White									
M200X050ACT	TIA Blue									
M200X050AET	TIA Green									
M200X050AFT	TIA Gray									
M200X050AGT	TIA Orange									
M200X050AIT	TIA Red									
M200X100Y6T	TIA Yellow			1.00	25.4	0.80	20.3	Standard Cross Section Cable Ties		
M200X100Y6T-B									2000	
M200X100Y7T	White								500	
M200X100Y7T-B									2000	
M200X100ACT	TIA Blue								500	
M200X100AET	TIA Green									
M200X100AFT	TIA Gray									
M200X100AGT	TIA Orange									
M200X100AIT	TIA Red									
M300X050Y6T	TIA Yellow	3.00	76.2	0.50	12.7	2.07	52.6	Intermediate Cross Section Cable Ties		
M300X050Y7T	White									
M300X050ACT	TIA Blue									
M300X050AET	TIA Green									
M300X050AFT	TIA Gray									
M300X050AGT	TIA Orange									
M300X050AIT	TIA Red									
M300X100Y6T	TIA Yellow			1.00	25.4	1.80	45.7	Standard Cross Section Cable Ties		
M300X100Y7T	White									
M300X100ACT	TIA Blue									
M300X100AET	TIA Green									
M300X100AFT	TIA Gray									
M300X100AGT	TIA Orange									
M300X100AIT	TIA Red									

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Military Grade Single-Sided Heat Shrink Labels

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Meet UL Standard 224 with a VW-1 rating for flammability and AMS-DTL-23053/5C (Class 1 and Class 3)
- Meet SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin and hybrid thermal transfer ribbons
- Shrink ratio 3:1
- Tested for use as an identification marker in (Class 1E) harsh environments
- Use thermal transfer hybrid ribbon or white resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)
- UL224 recognized, File # E205133; CSA certified, C22.2 No. 198.1.06, File # 256205

Part Number	Part Number	Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
				In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H050X025H1T*	H050X025H2T	H050X025H3T	H050X025H4T	0.13	3.1	0.50	12.7	0.25	6.4	0.04	1.0	0.13	3.3	22 – 18 AWG	4	2000	1
H075X025H1T*	H075X025H2T	H075X025H3T	H075X025H4T			0.75	19.1								2	1000	
H100X025H1T*	H100X025H2T	H100X025H3T	H100X025H4T			1.00	25.4										
H150X025H1T*	H150X025H2T	H150X025H3T	H150X025H4T			1.50	38.1								1	500	
H200X025H1T*	H200X025H2T	H200X025H3T	H200X025H4T			2.00	50.8										
H050X034H1T*	H050X034H2T	H050X034H3T	H050X034H4T	0.19	4.7	0.50	12.7	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	4	2000	
H075X034H1T*	H075X034H2T	H075X034H3T	H075X034H4T			0.75	19.1								2	1000	
H100X034H1T*	H100X034H2T	H100X034H3T	H100X034H4T			1.00	25.4										
H150X034H1T*	H150X034H2T	H150X034H3T	H150X034H4T			1.50	38.1								1	500	
H200X034H1T*	H200X034H2T	H200X034H3T	H200X034H4T			2.00	50.8										
H050X044H1T*	H050X044H2T	H050X044H3T	H050X044H4T	0.25	6.3	0.50	12.7	0.44	11.2	0.08	2.0	0.25	6.4	16 – 10 AWG	4	2000	
H075X044H1T*	H075X044H2T	H075X044H3T	H075X044H4T			0.75	19.1								2	1000	
H100X044H1T*	H100X044H2T	H100X044H3T	H100X044H4T			1.00	25.4										
H150X044H1T*	H150X044H2T	H150X044H3T	H150X044H4T			1.50	38.1								1	500	
H200X044H1T*	H200X044H2T	H200X044H3T	H200X044H4T			2.00	50.8										
H050X064H1T*	H050X064H2T	H050X064H3T	H050X064H4T	0.38	9.7	0.50	12.7	0.64	16.3	0.13	3.3	0.38	9.7	12 – 6 AWG	4	2000	
H100X064H1T*	H100X064H2T	H100X064H3T	H100X064H4T			1.00	25.4								2	1000	
H200X064H1T*	H200X064H2T	H200X064H3T	H200X064H4T			2.00	50.8								1	500	
H050X084H1T	—	—	—	0.50	12.7	0.50	12.7	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	4	2000	
H100X084H1T	H100X084H2T	H100X084H3T	H100X084H4T			1.00	25.4								2	1000	
H200X084H1T	H200X084H2T	H200X084H3T	H200X084H4T			2.00	50.8								1	500	
H050X165H1T	—	—	—	1.00	25.4	0.50	12.7	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG– 500 MCM	4	2000	
H100X165H1T	H100X165H2T	H100X165H3T	H100X165H4T			1.00	25.4								2	500	
H200X165H1T	H200X165H2T	H200X165H3T	H200X165H4T			2.00	50.8								1	250	
H200X240H1T	H200X240H2T	—	—	1.50	38.1	2.00	50.8	2.40	61.0	0.50	12.7	1.50	38.1	1 AWG - 1000 MCM	1	100	

Order number of labels required in multiples of Standard Package Quantity.
*Available in Bulk packages (5 times Labels Per Roll), add -B to end of part number

Military Grade Two-Sided Heat Shrink Labels

PATENTED

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Can be printed on both sides for improved visibility
- Meet the material requirements and physical properties of AMS-DTL-23053/5C (Class 1 and Class 3) and UL standard 224 with a VW-1 rating
- Meet SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B and D, and MIL-STD-202G Method 215K, Solutions A,C and D when printed using resin or hybrid thermal transfer ribbons
- Shrink ratio 3:1
- Tested as an identification marker for use in (Class 1E) harsh environments
- Use thermal transfer hybrid ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)
- UL224 recognized, File # E205133; CSA certified, C22.2 No. 198.1-06, File # 256205

Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X025H1T-2	H100X025H2T-2	0.13	3.1	1.00	25.4	0.25	6.4	0.04	1.0	0.13	3.3	22 – 18 AWG	2	1000	1
H100X025H1T-2-B	H100X025H2T-2-B													5000	
H200X025H1T-2	H200X025H2T-2			2.00	50.8								1	500	
H200X025H1T-2-B	H200X025H2T-2-B													2500	
H100X034H1T-2	H100X034H2T-2	0.19	4.7	1.00	25.4	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	2	1000	
H100X034H1T-2-B	H100X034H2T-2-B													5000	
H200X034H1T-2	H200X034H2T-2			2.00	50.8								1	500	
H200X034H1T-2-B	H200X034H2T-2-B													2500	
H100X044H1T-2	H100X044H2T-2	0.25	6.3	1.00	25.4	0.44	11.2	0.08	2.0	0.25	6.4	16 – 10 AWG	2	1000	
H100X044H1T-2-B	H100X044H2T-2-B													5000	
H200X044H1T-2	H200X044H2T-2			2.00	50.8								1	500	
H200X044H1T-2-B	H200X044H2T-2-B													2500	
H100X064H1T-2	H100X064H2T-2	0.38	9.7	1.00	25.4	0.64	16.3	0.13	3.3	0.38	9.7	12 – 6 AWG	2	1000	
H100X064H1T-2-B	H100X064H2T-2-B													5000	
H200X064H1T-2	H200X064H2T-2			2.00	50.8								1	500	
H200X064H1T-2-B	H200X064H2T-2-B													2500	
H100X084H1T-2	H100X084H2T-2	0.50	12.7	1.00	25.4	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	2	1000	
H100X084H1T-2-B	H100X084H2T-2-B													5000	
H200X084H1T-2	H200X084H2T-2			2.00	50.8								1	500	
H200X084H1T-2-B	H200X084H2T-2-B													2500	
H100X122H1T-2	H100X122H2T-2	0.75	19.0	1.00	25.4	1.22	31.0	0.25	6.3	0.75	19.0	8 – 4/0 AWG	2	500	
H200X122H1T-2	H200X122H2T-2			2.00	50.8								1	250	
H100X165H1T-2	H100X165H2T-2	1.00	25.4	1.00	25.4	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	2	500	
H200X165H1T-2	H200X165H2T-2			2.00	25..4								1	250	

Order number of labels required in multiples of Standard Package Quantity.

Halogen-Free Two-Sided Heat Shrink Labels

PATENTED

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Can be printed on both sides for improved visibility
- Meet SAE-AS5942, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and MIL-STD-202G Method 215K,Solutions A, C, and D when printed with resin and hybrid thermal transfer ribbons
- Meet BS6853; 1999 Vehicle Category 1A for burning behavior and toxic gas emissions; Smoke Density Class II
- Shrink ratio 2:1
- Use thermal transfer hybrid ribbon
- Temperature range: -22°F to 221°F (-30°C to 105°C)



Part Number	Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X025HFT-2	H100X025HGT-2	0.13	3.1	1.00	25.4	0.25	6.4	0.06	1.5	0.13	3.3	22 – 18 AWG	2	1000	1
H200X025HFT-2	H200X025HGT-2			2.00	50.8								1	500	
H100X034HFT-2	H100X034HGT-2	0.19	4.7	1.00	25.4	0.34	8.6	0.09	2.3	0.19	4.8	18 – 12 AWG	2	1000	
H200X034HFT-2	H200X034HGT-2			2.00	50.8								1	500	
H100X044HFT-2	H100X044HGT-2	0.25	6.4	1.00	25.4	0.44	11.1	0.13	3.3	0.25	6.4	16 – 10 AWG	2	1000	
H200X044HFT-2	H200X044HGT-2			2.00	50.8								1	500	
H100X064HFT-2	H100X064HGT-2	0.38	9.7	1.00	25.4	0.64	16.2	0.19	4.8	0.38	9.7	12 – 6 AWG	2	1000	
H200X064HFT-2	H200X064HGT-2			2.00	50.8								1	500	
H100X084HFT-2	H100X084HGT-2	0.50	12.7	1.00	25.4	0.84	21.3	0.25	6.4	0.50	12.7	8 – 1 AWG	2	1000	
H200X084HFT-2	H200X084HGT-2			2.00	50.8								1	500	
H100X165HFT-2	H100X165HGT-2	1.00	25.4	1.00	25.4	1.65	41.9	0.50	12.7	1.00	25.4	8 AWG – 500 MCM	2		
H200X165HFT-2	H200X165HGT-2			2.00	50.8								1	250	

Order number of labels required in multiples of Standard Package Quantity.

Fluid-Resistant Two-Sided Heat Shrink Labels

PATENTED

- Permanent, one-piece, heat shrink sleeve designed to provide clear, durable identification of wires and cables
- Cross-linked, semi-rigid, fluid-resistant, shrinkable polyolefin material
- Available in yellow only
- Can be printed on both sides for improved visibility
- Meet the material requirements and physical properties AMS-DTL-23053/6 Class 1 and NF F00-608 Class A and H when printed with resin thermal transfer ribbons
- Meet SAE-AS5942, MIL-STD-883F Method 2015.13 Solutions A and D, and MIL-STD-202G Method 215K, Solutions A and D when printed with resin thermal transfer ribbons
- Shrink ratio 3:1
- Use thermal transfer RMER4BL-C resin ribbon
- Temperature range: -67°F to 275°F (-55°C to 135°C)



Part Number	Diameter		Width		Height		Min. Cable O.D.		Max. Cable O.D.		Wire Range	Labels Per Row	Labels Per Roll	Std. Pkg. Qty. (Roll)
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
H100X034HST-2	0.19	4.7	1.00	25.4	0.34	8.6	0.06	1.5	0.19	4.8	18 – 12 AWG	2	1000	1
H200X034HST-2			2.00	50.8								1	500	
H100X044HST-2	0.25	6.4	1.00	25.4	0.44	11.1	0.08	2.0	0.25	6.4	16 – 10 AWG	2	1000	
H200X044HST-2			2.00	50.8								1	500	
H100X064HST-2	0.38	9.7	1.00	25.4	0.64	16.2	0.13	3.3	0.38	9.7	12 – 6 AWG	2	1000	
H200X064HST-2			2.00	50.8								1	500	
H100X084HST-2	0.50	12.7	1.00	25.4	0.84	21.3	0.17	4.3	0.50	12.7	8 – 1 AWG	2	1000	
H200X084HST-2			2.00	50.8								1	500	
H100X165HST-2	1.00	25.4	1.00	25.4	1.65	41.9	0.33	8.4	1.00	25.4	4 AWG – 500 MCM	2		
H200X165HST-2			2.00	50.8								1	250	

Order number of labels required in multiples of Standard Package Quantity.

Raised Panel Push Button Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposure)
- Meet ASTM D3389 standard for abrasion resistance and also meet solar application standards
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

Part Number	Color	Width		Height		Print-On Area Height		Hole Diameter		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		
C120X150APT-22	White	1.20	30.5	1.50	38.1	0.45	11.4	0.87	22.0	3	500
C120X150A8T-22	Yellow										
C120X150AST-22	Green										
C120X150AWT-22	Red										
C120X150A0T-22	Black										
C120X190APT-22	White			1.90	48.3	0.85	21.6				
C120X190A8T-22	Yellow										
C120X190AST-22	Green										
C120X190AWT-22	Red										
C120X190A0T-22	Black										
C180X180APT-30	White	1.80	45.7	1.80	45.7	0.36	9.1	1.18	30.0	2	
C180X180A8T-30	Yellow										
C180X180AST-30	Green										
C180X180AWT-30	Red										
C180X180A0T-30	Black										
C240X240APT-30	White	2.40	61.0	2.40	61.0	0.90	22.9			1	
C240X240A8T-30	Yellow										
C240X240AST-30	Green										
C240X240AWT-30	Red										
C240X240A0T-30	Black										

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Raised Panel Push Button Over-Laminate Labels

- Provide additional print protection in harsh environments
- Over-laminates are not printable
- Temperature range: -51°F to 275°F (-46°C to 135°C)

Part Number	Color	Width		Height		Hole Diameter		Labels Per Roll	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm		
C120X150YK-22	Clear	1.20	30.5	1.50	38.1	0.87	22.0	3	500
C120X190YK-22				1.90	48.3				
C180X180YK-30		1.80	45.7	1.80	45.7	1.18	30.0	2	
C240X240YK-30		2.40	60.9	2.40	60.9	1.18	30.0	1	

Order number of labels required in multiples of Standard Package Quantity.

Raised Panel Half Push Button Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

Part Number	Color	Width		Height		Print-On Area Height		Hole Diameter		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		
C180X130APT-30H	White	1.80	45.7	1.30	33.0	0.73	18.5	1.18	30.0	1	500
C240X200APT-30H		2.40	61.0	2.00	50.8	1.43	36.3				

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Raised Panel Component Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Provide crisp, clear, and durable legends for your reliable, high-performance identification needs
- Meet ASTM G154 for outdoor durability (simulating 20 years of UV resistance under normal conditions but not all outdoor exposure)
- Meet ASTM D3389 standard for abrasion resistance, and also meet solar application standards
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

Part Number	Color	Width In.	Width mm	Height In.	Height mm	Labels Per Row	Std. Pkg. Qty.
C100X050APT	White	1.00	25.4	0.50	12.7	3	500
C100X050A8T	Yellow						
C100X050AST	Green						
C100X050AUT	Orange						
C100X050AWT	Red						
C100X050A0T	Black						
C100X050AMT	Silver						
C125X030APT	White	1.25	31.8	0.30	7.6	1	
C125X030A0T	Black						
C170X090APT	White	1.70	43.2	0.90	22.9		
C170X090A8T	Yellow						
C170X090AST	Green						
C170X090AWT	Red						
C170X090AMT	Silver						
C200X100APT	White	2.00	50.8	1.00	25.4		
C200X100A8T	Yellow						
C200X100AST	Green						
C200X100AUT	Orange						
C200X100AWT	Red						
C200X100A0T	Black						
C200X100AMT	Silver						
C252X030APT	White	2.52	64.0	0.30	7.6		
C252X030A0T	Black						
C300X100APT	White	3.00	76.2	1.00	25.4		
C300X100A8T	Yellow						
C300X100AUT	Orange						
C300X100AWT	Red						
C300X100A0T	Black						
C300X250APT	White			2.50	63.5		
C300X250A8T	Yellow						
C300X250AST	Green						
C300X250AUT	Orange						
C300X250AWT	Red						
C300X250A0T	Black						
C300X250AMT	Silver						
C350X300APT	White	3.50	88.9	3.00	76.2		
C350X300A8T	Yellow						
C350X300AUT	Orange						
C350X300A0T	Black						
C379X030APT	White	3.79	96.3	0.30	7.6		
C379X030AQT	Blue						
C379X030AWT	Red						
C379X030A0T	Black						
C400X100APT	White	4.00	101.6	1.00	25.4		
C400X100A8T	Yellow						
C400X100AST	Green						
C400X100AUT	Orange						
C400X100AWT	Red						
C400X100A0T	Black						
C400X100AMT	Silver						

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Raised Panel Component Over-Laminate Labels

- Provide additional print protection in harsh environments
- Over-laminates are not printable
- Temperature range: -51°F to 275°F (-46°C to 135°C)

Part Number	Color	Width		Height		Labels Per Roll	Std. Pkg. Qty.
		In.	mm	In.	mm		
C100X050YK	Clear	1.00	25.4	0.50	12.7	1	500
C170X090YK		1.70	43.2	0.90	22.9		
C200X100YK		2.00	50.8	1.00	25.4		
C300X100YK		3.00	76.2	1.00	25.4		
C300X250YK				2.50	63.5		
C350X300YK		3.50	88.9	3.00	76.2		
C400X100YK		4.00	101.6	1.00	25.4		

Order number of labels required in multiples of Standard Package Quantity.

Raised Panel Pre-Printed Emergency Stop Labels

- Deliver the look of engraved laminated plates with the convenience of printing on demand
- Strong holding power for rough, textured, and powder-coated surfaces
- Temperature range: -40°F to 212°F (-40°C to 100°C)
- UL969 recognized, File # MH14576; cUL recognized C22.2 No. 0.15.01, File # MH14576

Part Number	Color	Diameter		Hole Diameter		Std. Pkg. Qty.
		In.	mm	In.	mm	
C235A8-30-ES	Black on Yellow	2.35	60.0	1.18	30.0	25
C235AW-30-ES	White on Red					
C350A8-30-ES	Black on Yellow	3.50	89.0			
C350AW-30-ES	White on Red					

Order number of labels required in multiples of Standard Package Quantity.

Polyester Component Labels

- Provide durability; high-temperature resistance and dimensional stability; does not easily stretch or tear
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width In.	Width mm	Height In.	Height mm	Labels Per Row	Std. Pkg. Qty.
C025X025YJT	White	0.25	6.4	0.25	6.4	12	10000
C038X038YJT	White	0.38	9.7	0.38	9.7	7	10000
C050X044YJT	White	0.50	12.7	0.44	11.2	5	10000
C060X020YJT	White	0.60	15.2	0.20	5.1	3	10000
C075X025YJT	White	0.75	19.1	0.25	6.4	3	10000
C075X025YMT	Silver	0.75	19.1	0.25	6.4	3	10000
C080X020YJT	White	0.80	20.3	0.20	5.1	3	10000
C090X025YJT	White	0.90	22.9	0.25	6.4	3	10000
C100X025YJT	White	1.00	25.4	0.25	6.4	3	10000
C100X038YJT	White	1.00	25.4	0.38	9.7	3	10000
C100X050YJT	White	1.00	25.4	0.50	12.7	3	10000
C100X050YKT	Clear	1.00	25.4	0.50	12.7	3	10000
C100X050YMT	Silver	1.00	25.4	0.50	12.7	3	10000
C125X038YJT	White	1.25	31.8	0.38	9.7	3	10000
C150X050YJT	White	1.50	38.1	0.50	12.7	1	5000
C150X075YJT	White	1.50	38.1	0.75	19.1	1	5000
C150X075YMT	Silver	1.50	38.1	0.75	19.1	1	5000
C160X020YJT	White	1.60	40.6	0.20	5.1	1	10000
C200X025YJT	White	2.00	50.8	0.25	6.4	1	5000
C200X038YJT	White	2.00	50.8	0.38	9.7	1	5000
C200X050YJT	White	2.00	50.8	0.50	12.7	1	5000
C200X100YJT	White	2.00	50.8	1.00	25.4	1	2500
C200X100YKT	Clear	2.00	50.8	1.00	25.4	1	2500
C200X100YMT	Silver	2.00	50.8	1.00	25.4	1	2500
C275X125YJT	White	2.75	69.9	1.25	31.8	1	2500
C275X125YMT	Silver	2.75	69.9	1.25	31.8	1	2500
C300X025YJT	White	3.00	76.2	0.25	6.4	1	5000
C300X038YJT	White	3.00	76.2	0.38	9.7	1	5000
C300X100YJT	White	3.00	76.2	1.00	25.4	1	2500
C300X100YMT	Silver	3.00	76.2	1.00	25.4	1	2500
C300X200YJT	White	3.00	76.2	2.00	50.8	1	1000
C300X200YMT	Silver	3.00	76.2	2.00	50.8	1	1000
C350X100YJT	White	3.50	88.9	1.00	25.4	1	2500
C400X100YJT	White	4.00	101.6	1.00	25.4	1	2500
C400X200YJT	White	4.00	101.6	2.00	50.8	1	1000
C400X200YMT	Silver	4.00	101.6	2.00	50.8	1	1000
C400X300YJT	White	4.00	101.6	3.00	76.2	1	2500
C400X400YJT	White	4.00	101.6	4.00	101.6	1	1000
C400X600YJT	White	4.00	101.6	6.00	152.4	1	1000

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Super-Tack Polyester Component Labels

- Provide durability; high-temperature resistance and dimensional stability; does not stretch or easily tear; and has high-tack permanent adhesive
- Used to identify patch panels, faceplates, punchdown blocks, and other network systems hardware
- Meets DIN 40050-9, IP69K for washdown applications
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979



Part Number	Color	Width In.	Width mm	Height In.	Height mm	Type of Application	Labels Per Row	Std. Pkg. Qty.
C061X030YPT	White	0.61	15.5	0.30	7.6	1-port	4	2500
C100X050YPT		1.00	25.4	0.50	12.7	general identifier	3	10000
C125X030YPT		1.25	31.8	0.30	7.6	2-port		
C138X019YPT		1.38	35.1	0.19	4.8	module	1	2500
C138X019Y0T	Black							
C188X030YPT	White	1.88	47.8	0.30	7.6	3-port		
C200X100YPT		2.00	50.8	1.00	25.4	general identifier		
C200X100Y0T	Black							
C252X030YPT	White	2.52	64.0	0.30	7.6	4-port		
C252X030YPT-P*						1, 2, 3, or 4-port		
C252X030YQT-P*	TIA Blue							
C252X030YRT-P*	TIA Brown							
C252X030YST-P*	TIA Green							
C252X030YTT-P*	TIA Gray							
C252X030YUT-P*	TIA Orange							
C252X030YVT-P*	TIA Purple							
C252X030YWT-P*	TIA Red							
C252X030Y0T-P*	Black							
C252X030Y8T-P*	TIA Yellow							
C252X030Y9T-P*	Gold							
C261X030YPT	White	2.61	66.3	0.30	7.6	4-port		
C275X125YPT		2.75	69.9	1.25	31.8	general identifier		
C275X125Y0T	Black							
C288X030YPT	White	2.88	73.2	0.30	7.6	5-port		
C300X200YPT		3.00	76.2	2.00	50.8	general identifier		
C315X030YPT		3.15	80.0	0.30	7.6	5-port		
C379X030YPT		3.79	96.3	0.30	7.6	6-port		
C379X030YPT-P*						1, 2, 3, 4, 5 or 6-port		
C379X030YQT-P*	TIA Blue							
C379X030YRT-P*	TIA Brown							
C379X030YST-P*	TIA Green							
C379X030YTT-P*	TIA Gray							
C379X030YUT-P*	TIA Orange							
C379X030YVT-P*	TIA Purple							
C379X030YWT-P*	TIA Red							
C379X030Y0T-P*	Black							
C379X030Y8T-P*	TIA Yellow							
C379X030Y9T-P*	Gold							
C400X200Y8T	Yellow	4.00	101.6	2.00	50.8	general identifer		1000
C400X300YPT	White			3.00	76.2			2500

*Label is perforated to be used in 1, 2, 3, 4, or 6-Port position applications.
Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Tedlar® Component Labels

- Self-extinguishing and ideal for labeling high-temperature areas
- Meet Federal Motor Vehicle Safety Standard (FMVSS-302) for flammability
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 225°F (-40°C to 106°C); tests at 275°F have shown acceptable results

Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C060X020TJT	White	0.60	15.2	0.20	5.1	3	10000
C090X025TJT		0.90	22.9	0.25	6.4		
C100X038TJT		1.00	25.4	0.38	9.7		
C100X050TJT				0.50	12.7		
C125X038TJT		1.25	31.8	0.38	9.7		2500
C200X038TJT		2.00	50.8			1	5000
C200X100TJT				1.00	25.4		2500
C300X038TJT		3.00	76.2	0.38	9.7		5000

Tedlar® is a registered trademark of E.I. du Pont de Nemours and Company.
Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Tamper-Evident Polyester Component Labels

- Leaves a checkerboard of silver material allowing you to see if label has been tampered with
- Use thermal transfer resin ribbon
- Temperature range: -40°F to 302°F (-40°C to 150°C)
- UL969 recognized, File # MH14576 and File # MH14979



Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C075X025AAT	Silver	0.75	19.1	0.25	6.4	3	10000
C100X050AAT		1.00	25.4	0.50	12.7		
C200X100AAT		2.00	50.8	1.00	25.4	1	2500
C275X125AAT		2.75	69.9	1.25	31.8		

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Non-Adhesive Polyester Component Labels

- Used to identify patch panels, faceplates, punchdown blocks, and other network systems hardware
- Use thermal transfer resin ribbon
- Temperature range: -10°F to 302°F (-23°C to 150°C)

Part Number	Color	Width		Height		Application	Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm			
C150X030Y1T	White	1.50	38.1	0.30	7.6	3-port identifier	2	1000
C195X040Y1T		1.95	49.5	0.40	10.2	Single-gang faceplate		
C261X035Y1T		2.61	66.3	0.35	8.9	4-port identifier		
C288X040Y1T		2.88	73.2	0.40	10.2	Double-gang faceplate		
C390X030Y1T		3.90	99.1	0.30	7.6	6-port identifier		
C750X050Y1T		7.50	190.5	0.50	12.7	110 block		
C788X050Y1T		7.88	200.2	0.50	12.7	GP6™ Punchdown System		

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Vinyl Cloth Component Labels

- Ideal for temporary marking of chips, boards, and ICs
- Removable without leaving any residue
- Pliable material is suitable for rough texture surfaces
- Use thermal transfer hybrid ribbon
- Temperature range: 50°F to 170°F (10°C to 77°C)
- UL969 recognized, File # MH14576 and File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14576

Part Number	Color	Width		Height		Labels Per Row	Std. Pkg. Qty.
		In.	mm	In.	mm		
C050X044CBT	White	0.50	12.7	0.44	11.2	5	10000
C060X020CBT		0.60	15.2	0.20	5.1	3	
C075X025CBT		0.75	19.1	0.25	6.4		
C100X025CBT		1.00	25.4				
C100X038CBT				0.38	9.7		
C100X050CBT				0.50	12.7		
C150X075CBT		1.50	38.1	0.75	19.1	1	5000
C160X020CBT		1.60	40.6	0.20	5.1		10000
C200X050CBT		2.00	50.8	0.50	12.7		5000
C400X100CBT		4.00	101.6	1.00	25.4		2500

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Polyimide Component Labels

- Ideal for electronic components and internal circuitry applications
- Intended for applications requiring solvent and high-temperature resistance performance, such as the wave solder process
- Use thermal transfer resin ribbon on white polyimide
- Use thermal transfer hybrid ribbon on tan polyimide
- Temperature range: -40°F to 350°F (-40°C to 177°C)
- UL969 recognized, File # MH14979; cUL recognized, C22.2 No. 0.15.01, File # MH14979

Part Number	Color	Width In.	Width mm	Height In.	Height mm	Labels Per Row	Std. Pkg. Qty.
C025X025KBT	White	0.25	6.4	0.25	6.4	12	10000
C025X025KCT	Tan						
C038X038KBT	White	0.38	9.7	0.38	9.7	7	
C038X038KCT	Tan						
C050X013KBT	White	0.50	12.7	0.13	3.3	5	
C050X013KCT	Tan						
C050X020KBT	White			0.20	5.1		
C050X044KBT				0.44	11.2		
C050X044KCT	Tan						
C060X020KBT	White	0.60	15.3	0.20	5.1	3	
C060X020KCT	Tan						
C065X019KBT	White	0.65	16.5	0.19	4.8		
C065X019KCT	Tan						
C075X025KBT	White	0.75	19.1	0.25	6.4		
C075X025KCT	Tan						
C080X020KBT	White	0.80	20.3	0.20	5.1		
C080X020KCT	Tan						
C090X025KBT	White	0.90	22.9	0.25	6.4		
C090X025KCT	Tan						
C100X019KBT	White	1.00	25.4	0.19	4.8		
C100X019KCT	Tan						
C100X025KBT	White			0.25	6.4		
C100X025KCT	Tan						
C100X038KBT	White			0.38	9.7		
C100X038KCT	Tan						
C125X025KBT	White	1.25	31.8	0.25	6.4	2	
C125X025KCT	Tan						
C150X025KBT	White	1.50	38.1				5000
C150X025KCT	Tan						
C160X020KBT	White	1.60	40.6	0.20	5.1	1	10000
C160X020KCT	Tan						
C200X025KBT	White	2.00	50.8	0.25	6.4		5000
C200X025KCT	Tan						
C200X038KBT	White			0.38	9.7		
C300X025KBT		3.00	76.2	0.25	6.4		
C300X025KCT	Tan						

Order number of labels required in multiples of Standard Package Quantity.
Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.