



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: T150L0K2



Article Number	111-15404
Type	T150L
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Heavy-duty design offers higher tensile strength.• Buckle feature on head allows excess strap to be tucked away after installation.• Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy Duty Cable Tie, 32.3" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 50/pkg

Global Part Name	T150L-PA66-BK
Minimum Tensile Strength (Imperial)	175.0
Minimum Tensile Strength (Metric)	780.0
Length L (Imperial)	32.3
Length L (Metric)	820.0
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.35
Width W (Metric)	8.9
Bundle Diameter Min (Imperial)	0.32
Bundle Diameter Min (Metric)	8.0
Bundle Diameter Max (Imperial)	9.6
Bundle Diameter Max (Metric)	243.8
Thickness T (Metric)	1.9

Material	Polyamide 6.6 (PA66)		
Material Shortcut	PA66		
US MIL SPEC	MIL 53421	Flammability	
UL 94 V2		Halogen free	
Yes		Operating Temperature (Metric)	
-40°F to +185°F (-40°C to +85°C)		ROHS Complaint	
Yes		Certification/Specification WEB	
UL-ZODZ2.E64139		UL Recognized (US)	
Yes		UL Recognized (US and Canada)	
Yes			
Package Quantity(Imperial)	50		
Package Quantity (Metric)	50		
Customs Number	3926909987		

