

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Specification Sheet

Part Number: T18R3M4



Standard Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Orange, 1000/pkg

Article Number	111-01877
Type	T18R
Color	Orange (OG)
Features & Benefits	<ul style="list-style-type: none">Inside serrations allow for strong hold on cables and wire bundles.Head design provides high tensile strength with very low insertion force.Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description

Standard Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Orange, 1000/pkg

Global Part Name

T18R-PA66-OG

Minimum Tensile Strength (Imperial)

18.0

Minimum Tensile Strength (Metric)

80.0

Length L (Imperial)

4.0

Length L (Metric)

100.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.10

Width W (Metric)

2.5

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

0.87

Bundle Diameter Max (Metric)

22.0

Thickness T (Metric)	1.0
Height H (Metric)	3.7
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MIL SPEC	SAE-AS33671
MS3367-4-3	
Flammability	
UL 94 V2	Halogen free
Yes	Operating Temperature (Metric)
-40°F to +185°F (-40°C to +85°C)	ROHS Complaint
Yes	Certification/Specification WEB
CAGE Code 53421 UL-ZODZ.E64139	UL Recognized (US)
Yes	UL Listed (US and Canada)
Yes	UL Recognized (US and Canada)
Yes	
Package Quantity(Imperial)	1000

Package Quantity (Metric) 1000

Customs Number 3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)